



Fac/Perm/Co ID #	Date	Initials
bc	7/3/93	DN

State of North Carolina
Department of Environment, Health, and Natural Resources
512 North Salisbury Street • Raleigh, North Carolina 27604

James B. Hunt, Jr., Governor

Division of Solid Waste Management
Telephone (919)733-0692

Jonathan B. Howes, Secretary

July 27, 1993

Mr. Wayne Hooper
County Manager, Jackson County
County Administration Building
Sylva, N.C. 28779

Re: Implementation Of Subtitle 'D' Ground-water Monitoring Program

Dear Mr. Hooper,

The purpose of this correspondence is to provide information and clarification on the changes in ground-water monitoring requirements for MSWLF facilities that remain in operation after October 9, 1993. The proposed North Carolina Solid Waste Management Rules reflect significant changes for ground-water monitoring based on requirements of the E.P.A. Subtitle D Rules.

Attachment A to this letter provides a summary of important dates and significant activities that must be accomplished in order to be in compliance with the new rules. Attachment B contrasts existing and proposed ground-water monitoring and assessment requirements based on changes in the rules. Because of significant increases in costs that will be incurred in order to operate a MSWLF under the new Subtitle D Rules, including financial assurance and increased costs for ground-water monitoring and assessment, you may wish to seriously consider closing your sanitary landfill prior to October 9, 1993, when the new rules become effective.

When the new rules take effect, MSWLF facilities that have violations of the North Carolina Groundwater Quality Standards or facilities that show a significant statistical increase in the level of any Appendix I constituent will quickly be required to implement assessment monitoring for all Appendix II constituents. Since the Groundwater Quality Standards are also used in establishing the ground-water protection standards, MSWLF facilities with violations may also rapidly move into assessment of corrective action alternatives based on a full-scale ground-water investigation to determine the nature and extent of contamination at the site.

If Jackson County chooses to continue to operate their MSWLF facility after October 9, 1993, then you need to begin planning and budgeting immediately for the activities outlined in Attachment A. A revised Water Quality Monitoring Plan must be submitted as part of the Transition Plan on or before April 9, 1994. The present monitoring system at the facility will require upgrading to meet the requirements of the new N.C. Solid Waste Management Rules for MSWLF facilities. All background sampling and related activities for the upgraded monitoring system must be completed and reported to the Division in order to demonstrate compliance with the new water quality monitoring requirements on or before October 9, 1994.

Please note that the goals and objectives for ground-water assessment monitoring and ground-water contamination investigations are the same under both the current and the proposed rules and shall be accomplished in a way that is protective of human health and the environment. However, current rules allow for greater flexibility in the assessment and investigation activities and the sample analytical costs could be substantially less using the constituent list required under current rules and policy as compared to analytical costs required by the new rules based on Subtitle D, which require sampling for the Appendix II list of constituents.

I hope this letter has been helpful in providing you more insight into the actions that will be required by Jackson County to maintain compliance with the water quality monitoring requirements of the Solid Waste Management Rules as we make the transition to the new rules growing out of the E.P.A. Subtitle D Regulations. If you have any questions or comments regarding this letter, please contact the Solid Waste Section at (919) 733-0692.

Sincerely,

Bobby Lutfy

Bobby Lutfy, Hydrogeologist

Solid Waste Section

cc: James Patterson
50-02
Attachments

ATTACHMENT A

Important dates and significant activities that must be accomplished in order to be in compliance with the new rules on ground-water monitoring at MSWLF facilities:

April 9, 1994: A Water Quality Monitoring Plan that fulfills the requirements of the new Solid Waste Management Rules must be submitted to the Division as part of the Transition Plan on or before April 9, 1994.

October 9, 1994: Compliance with the new ground-water monitoring requirements must be demonstrated to the Division on or before October 9, 1994. In order to demonstrate compliance, the MSWLF owner or operator must perform the following activities and provide documentation to the Division.

1. Upgrade the ground-water monitoring system so that it meets the criteria of the new rules for monitoring systems.
Rule .1631
 - (a) Monitoring wells shall be installed at the relevant point of compliance based upon the waste boundaries established on October 9, 1993. - Rule .1631(a)(2)
 - (b) Monitoring wells shall be designed and constructed in accordance with the applicable North Carolina Well Construction Standards as codified in 15A NCAC 2C. - Rule .1631(b)
2. In order to accurately determine ground-water elevations for each monitoring well, the wells shall have been accurately surveyed by a North Carolina Registered Land Surveyor.
- Rule .1632(d)(1)
3. In order to determine the rate of ground-water flow, the owner or operator shall provide data for hydraulic conductivity and porosity for the formation materials at each of the well locations. - Rule .1632(d)(2)
4. A minimum of four independent samples from each well (background and downgradient) shall be collected and analyzed for the Appendix I constituents during the first semiannual sampling event. - Rule .1633(b)
5. The owner or operator shall determine whether or not there is a statistically significant increase over background values for each parameter or constituent required in the particular ground-water monitoring program that applies to the MSWLF unit. - .1632(i)

ATTACHMENT B

Contrasts between the existing and the new ground-water monitoring and assessment requirements based on changes in the Solid Waste Management Rules. All MSWLF units that are in operation on or after October 9, 1993, will be subject to the new rules.

EXISTING RULES

NEW RULES

Detection monitoring:

Monitoring frequency:
Semiannual monitoring

Monitoring frequency:
Semiannual monitoring

Monitoring parameters:
23 landfill constituents

Monitoring parameters:
Appendix I constituents

Data evaluation based on:
N.C. Groundwater Quality
Standards

Data evaluation based on:
N.C. Groundwater Quality
Standards and statistical
increase over background
levels

Post Closure Monitoring:

Length of time:
5 years and reevaluate need
for further monitoring

Length of time:
30 years and reevaluate need
for further monitoring

Monitoring parameters:
23 landfill constituents &
occasional VOCs

Monitoring parameters:
Appendix I constituents

Data evaluation based on:
N.C. Groundwater Quality
Standards

Data evaluation based on:
N.C. Groundwater Quality
Standards and statistical
increase over background
levels

Assessment monitoring and ground-water investigations:

Monitoring parameters:
23 landfill constituents,
VOCs, semi-VOCs

Monitoring parameters:
Appendix II constituents
(213 constituents)

Data evaluation based on:
N.C. Groundwater Quality
Standards

Data evaluation based on:
N.C. Groundwater Quality
Standards and statistical
increase over background
levels

Greater flexibility

Flexibility more limited

WHILE YOU WERE OUT

FOR <u>Larry</u>		DATE <u>12-1</u>	TIME <u>12:03</u> A.M. P.M.
M. <u>Tammera Christ</u>			
OF _____			<input checked="" type="checkbox"/> PHONED
PHONE <u>704 586 4055</u>	AREA CODE	NUMBER	EXTENSION
MESSAGE <u>well</u>			<input checked="" type="checkbox"/> PLEASE CALL
<u>re: well monitoring request</u>			<input type="checkbox"/> WILL CALL AGAIN
<u>call after 1:00</u>			<input type="checkbox"/> CAME TO SEE YOU
SIGNED <u>SD Pace to send copy</u>	<u>of 1993 MW</u>		<input type="checkbox"/> WANTS TO SEE YOU

FORM 400B