Permit No.	Date	Document ID No.
44-07	**September 12, 2008**	**5807**

BLE INC.
BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL, ENVIRONMENTAL AND CONSTRUCTION MATERIALS CONSULTANTS

DESIGN HYDROGEOLOGIC REPORT
PHASES 3 AND 4

WHITE OAK MSW LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA

Prepared For:

MCGILL ASSOCIATES, P.A.
55 Broad Street
Asheville, North Carolina 28801





Prepared By:

BUNNELL-LAMMONS ENGINEERING, INC.
6004 Ponders Court
Greenville, South Carolina 29615

July 11, 2008



BLE Project Number J07-1957-02

Fac/Perm/Co ID #	Date	Doc ID#
44-07	9,12,08	5807

BLE INC.
BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL, ENVIRONMENTAL AND CONSTRUCTION MATERIALS CONSULTANTS

July 11, 2008

McGill Associates, P.A.
55 Broad Street
Asheville, North Carolina 28801

Attention: Mr. Jeffrey Bishop, P.E.

Subject: **Design Hydrogeologic Report**
Phases 3 & 4
White Oak MSW Landfill
Haywood County, North Carolina
BLE Project Number J07-1957-02

Gentlemen:

Bunnell-Lammons Engineering, Inc. (BLE) has completed the Design Hydrogeologic Study for Phases 3 & 4 at the White Oak MSW Landfill. This report addresses the relevant site application requirements as outlined in the North Carolina Rules for Solid Waste Management, 15A NCAC 13B .1623 (b). The attached report describes the work performed and presents the results obtained.

We appreciate the opportunity to serve as your geological and geotechnical consultant on this project and look forward to continue working with you at the White Oak MSW Landfill. If you have any questions, please contact us at (864) 288-1265.

Sincerely,

BUNNELL-LAMMONS ENGINEERING, INC.

NORTH CAROLINA LICENSED 7-11-08 SEAL 1043 GEOLOGIST MARK S. PREDDY

Mark S. Preddy, P.G.
Senior Hydrogeologist
Registered, North Carolina #1043

NORTH CAROLINA LICENSED 7-11-08 SEAL 1475 GEOLOGIST ANDREW W. ALEXANDER

Andrew W. Alexander, P.G.
Senior Hydrogeologist
Registered, North Carolina #1475

NORTH CAROLINA PROFESSIONAL SEAL No. 13814 7-11-08 ENGINEER DANIEL B. BUNNELL

Daniel B. Bunnell, P.E.
Principal Geotechnical Engineer
Registered, North Carolina #13814

c:\msp files\haywood co lfs nc\active white oak lf\195702\white oak dhr.doc

RECEIVED
SEP [redacted]
SOLID WASTE SECTION
ASHEVILLE REGIONAL OFFICE

6004 PONDERS COURT
GREENVILLE, SOUTH CAROLINA 29615

PHONE (864) 288-1265
FAX (864) 288-4430

TABLE OF CONTENTS

LIST OF TABLES

Table

LIST OF FIGURES

Figure

LIST OF APPENDICES

Appendix

REPORT CROSS-REFERENCE INDEX OF APPLICABLE NORTH CAROLINA STATE REGULATIONS

15A NCAC 13B .1623 (b) Design Hydrogeologic Report Requirements

STATE REGULATIONS	LOCATION IN REPORT
(b) (1) (A)	Sections 3.5.2.1, 3.6.3; Table 3; Figures 5, 7; Appendices E, I
(b) (1) (B)	Section 3.5; Tables 3, 4, 5,7, 8, 9; Figures 4, 6, 7, 8; Appendices C, F, H
(b) (2) (A)	From 15A NCAC 13B .1623(a)
(a) (4) (A)	Sections 2.1, 3.4.1; Appendices A, B, C
(a) (4) (B)	Sections 2.3, 3.4.3; Tables 5, 6; Appendices G, H
(a) (4) (C)	Sections 3.4.1, 3.4.3; Tables 5, 6; Appendices B, C, H
(a) (4) (D)	Sections 3.4; Tables 5, 6; Appendices B, C
(a) (4) (E)	Sections 3.4.3, 3.5.5; Tables 4, 5, 8; Appendices F, H
(a) (5)	Sections 2.4, 3.4.2
(a) (6)	Figure 4
(a) (7) (A)	Table 3
(a) (7) (B)	Table 3; Appendix E
(a) (7) (C)	Section 3.5.2.2; Table 3; Figure 8; Appendix E
(a) (7) (D)	Sections 3.2, 3.5.2, 3.5.3, 3.5.4
(a) (8)	Sections 3.5.5, 3.5.6; Tables 7, 9; Figures 4, 6; Appendix F
(a) (9)	Figures 6, 7, 8
(a) (10)	Figure 3
(a) (11)	Appendices B, C
(a) (12)	Sections 3.3, 3.4.2; Appendix I
(b) (2) (B)	Sections 3.4, 3.5; Tables 3, 4, 7, 8, 9; Figures 4, 5, 6, 7, 8
(b) (2) (C)	Sections 3.0; Tables 3, 4, 7, 8, 9; Figures 4, 5, 6, 7, 8
(b) (2) (D)	Sections 2.1, 2.4, 3.4.1.3, 3.4.2; Figure 5; Appendices B, C
(b) (2) (E)	Figure 7
(b) (2) (F)	Figure 5
(b) (2) (G)	Figure 4
(b) (2) (H)	Section 3.5; Tables 3, 4, 7, 8, 9; Figures 4, 6, 7, 8
(b) (2) (I)	Section 2.2
(b) (3) (A)	Included in a separate document prepared by BLE
(b) (3) (B)	Included in a separate document prepared by BLE
(b) (3) (C)	Included in a separate document prepared by BLE

-oOo-

1.0 PROJECT INFORMATION

The existing 286-acre White Oak Municipal Solid Waste (MSW) Landfill facility is located in Haywood County, North Carolina, approximately 12 miles north of Waynesville at the Fines Creek Exit (Exit 15) off of Interstate 40 (Figure 1). The landfill is owned and operated by Haywood County. Currently, Phase 1 and 2 cell areas have been developed. Haywood County now plans to develop the Phase 3 and 4 cell area. The existing and proposed waste cell layout is provided on Figure 3.

The landfill development is being implemented in phases as new solid waste cells are needed. This *Design Hydrogeologic Report* (DHR) addresses the geological and geotechnical investigation required for the construction permitting process. The investigation was performed in accordance with the applicable North Carolina Rules for Solid Waste Management (15A NCAC 13B .1623 (b)). Data from previously performed investigations are compiled into this report, as is relevant to the Phase 4 area. The previous investigations include the following:

- *Project Design Manual, White Oak Sanitary Landfill*, Tribble & Richardson, Inc, dated March 1992.
- *Permit Renewal, Landfill Expansion, Design Hydrogeologic Report, White Oak Sanitary Landfill*, Steffen, Robertson, and Kirsten, Inc. Project Number 83507, dated September, 1997.
- *Permit Renewal, Landfill Expansion, Design Hydrogeologic Report (REV 1), White Oak Sanitary Landfill*, Steffen, Robertson, and Kirsten, Inc. Project Number 83507, dated July, 1998.
- *Site Hydrogeologic Report, White Oak Subtitle D Landfill*, Municipal Engineering Project Number G98010.5, dated February 8, 2000.

-oOo-

2.0 FIELD INVESTIGATION

The field investigation of the Phase 3 and 4 areas was conducted during July 2007 and February 2008. Taken together, the investigation of the Phase 3 and 4 areas has included:

- performing soil test borings and rock coring;
- installing permanent groundwater monitoring wells and temporary piezometers;
- measuring water levels;
- performing hydraulic testing on piezometers;
- performing soil laboratory testing;
- performing settlement and slope stability evaluations; and
- evaluating location restrictions as outlined in the applicable solid waste regulations.

A discussion of the investigative methodologies used in the site evaluation is provided below. The field activities reported below were performed under the direction of a North Carolina-licensed geologist or engineer. A North Carolina-licensed driller performed the borings, piezometer installation, and monitoring well installation. The boring locations/piezometers were surveyed for horizontal and vertical control, by McGill Associates, Inc. of Asheville, North Carolina, after completion of the drilling activities.

2.1 TEST BORING AND SOIL SAMPLING

The North Carolina Department of Environment and Natural Resources (DENR) requires that Design Hydrogeologic Studies include the performance of one boring per acre of permitted cell area, and on the area within 150 feet downgradient of the cells. The area of Phases 3 and 4, including the area downgradient of the cells, is approximately 19.9 acres. Including previous phases of work and this project, 26 borings have been performed in the Phase 3 and 4 areas, which include 24 piezometers/wells. Eight of the borings were pre-existing and 18 new borings were performed during this phase of work.

The new soil test boring locations and depths were selected to comply with the applicable NCDENR rules and were performed in general accordance with ASTM D 1586. Soil samples were obtained from the soil test borings at 2.5-foot intervals within the upper ten feet below the ground surface, and at five-foot intervals deeper than ten feet below the ground surface. Drilling techniques consisted of hollow-stem augering and rock coring. Refer to Appendix A for discussion of the various drilling techniques used.

Soil test boring logs were produced in the field by a geologist (Appendix B). The soil descriptions on the field logs were based on visual examination and grain-size estimations in accordance with the Unified Soil Classification System (USCS). Upon completion of laboratory grain-size and Atterberg Limit analyses, the preliminary field classifications were adjusted accordingly on the final boring logs. The final boring log records are included in Appendix C.

2.2 GROUNDWATER INVESTIGATION

Nineteen piezometers were installed to monitor water table elevations and further characterize the study area hydrogeology. The piezometers supplement the five monitoring wells installed by

others during previous phases of work in the Phase 3 and 4 areas. Piezometer installation records are included with the boring logs in Appendix C, and field installation procedures are described in Appendix D. Survey information for the piezometers and monitoring wells is presented on Table 1, and well/piezometer construction details are summarized on Table 2.

Groundwater elevations were measured in the new piezometers at the time of boring and after 24 hours. Measurements were taken in the piezometers and monitoring wells during the period from September 2007 to February 2008 to determine the seasonal groundwater trends. The historical water level data is included on Table 3, which includes available water level information from the monitoring wells from June 1998 to April 2007. Historical precipitation data for the Haywood County region is included in Appendix E.

Field permeability (slug) tests were performed in six piezometers in the study area to measure the *in situ* hydraulic conductivity of different units of the water table aquifer. Slug test field procedures and data plots are presented in Appendix F and a summary of the results are presented on Table 4.

The piezometers are intended only for investigation use, were not constructed as permanent monitoring wells, and will not be part of the permanent groundwater monitoring system. Prior to construction activities, the piezometers will be abandoned in accordance with 15A NCAC 2C, Rule .0113(a)(2) by drilling them out and filling the resulting boreholes with a grout mixture.

2.3 LABORATORY TESTING

Laboratory tests were conducted to confirm the field classifications and quantify pertinent engineering soil properties. Soil samples were collected using split-spoon samplers, Shelby tubes (undisturbed), and from the auger cuttings (bulk samples). The laboratory tests were performed in general accordance with applicable ASTM specifications, where available. Brief descriptions of the test procedures are included in Appendix G. Soil laboratory testing results are included in Appendix H and are summarized on Tables 5 and 6, which include laboratory results from tests performed during this phase of work.

2.4 FRACTURE TRACE ANALYSIS

The fracture trace analysis consisted of evaluating exposed rock outcrops and topographic fracture traces and lineaments as discussed below. The data was included in the *Site Hydrogeologic Report, White Oak Subtitle D Landfill*, Municipal Engineering Project Number G98010.5, dated February 8, 2000.

Exposed Rock Outcrops: Using a Brunton compass, the orientations of exposed bedrock fractures (open joints, open foliation, open bedding planes) were measured. The field measurements were plotted on a Schmidt lower hemisphere equal-area stereonet and Rose diagrams.

Topographic Fracture Traces and Lineaments: Regionally, pronounced depressions typically develop along zones of weakness in the bedrock where fractures induce preferential weathering. This preferential weathering along the bedrock fractures is ultimately expressed topographically as linear valleys. The trend of fracture traces and lineaments greater than 1,000 feet in length within a

1-mile radius of the site were measured from topographic maps and plotted as data on Rose diagrams.

2.5 FIELD RECONNAISSANCE

The study area was traversed to map rock outcrops and surface drainage features. The information obtained was integrated with the geologic information already collected at the site during previous phases of work. Bedrock fracture orientations were measured from the rock outcrops as part of the fracture trace analysis.

-oOo-

3.0 RESULTS OF INVESTIGATION

3.1 REGIONAL GEOLOGY

The subject site is located within the Blue Ridge Belt (Figure 2). The crystalline rocks of the Blue Ridge occur in generally northeast-southwest trending geologic belts in the Carolinas and Virginia. Precambrian-age (Proterozoic) basement complexes of metamorphosed igneous and sedimentary rocks underlie the region (Hadley and Goldsmith, 1963; Horton and Zullo, 1991). The site is underlain by the Middle to Late Proterozoic-aged Spring Creek Granitoid Gneiss, which are metamorphosed-igneous rocks. The multiple metamorphic deformations of the igneous rocks have resulted in biotite granitic gneiss interlayered with biotite granodiorite gneiss, tonalitic gneiss, quartz monzodiorite gneiss, amphibolite, biotite gneiss, and biotite schist (Carter and Weiner, 1999). Late Proterozoic-aged Great Smoky Group has been mapped southeast of the facility boundary, which are metamorphosed-sedimentary rocks. The multiple metamorphic deformations of the sedimentary rocks have resulted in metagraywache, with lesser amounts of locally interbedded kyanite-garnet-mica schist, garnet-mica schist, and calc-silicate granofels (Carter and Weiner, 1999). In the vicinity of the site, bedding and foliation generally strike northeast-southwest and dips moderately to the southeast. Structurally, the contact between the Spring Creek Granitoid Gneiss and the Great Smoky Graywacke is mapped as a thrust fault in which the Great Smokey formation overlies the Spring Creek formation (Carter and Weiner, 1999).

Holocene and younger age faults were not indicated on site or within 200 feet of the site from the literature review or from the field reconnaissance.

The typical residual soil profile consists of clayey soils near the surface, where soil weathering is more advanced, underlain by sandy silts and silty sands. Residual soil zones develop by the *in situ* chemical weathering of bedrock, and are commonly referred to as "saprolite." Saprolite usually consists of silt with lessor amounts of sand, clay, and large rock fragments. The thickness of the saprolite in the Piedmont ranges from a few feet to more than 100 feet. The boundary between soil and rock is not sharply defined.

A transitional zone of partially weathered rock is normally found overlying the parent bedrock. Partially weathered rock is defined, for engineering purposes, as residual material with standard penetration resistance in excess of 100 blows per foot (bpf). Fractures, joints, and the presence of less resistant rock types facilitate weathering. Consequently, the profile of the partially weathered rock and hard rock is quite irregular and erratic, even over short horizontal distances. Also, it is not unusual to find lenses and boulders of hard rock and zones of partially weathered rock within the soil mantle, well above the general bedrock level. Often during construction, this material can be excavated using conventional earth moving equipment.

3.2 REGIONAL HYDROGEOLOGY

The uppermost groundwater in the Blue Ridge in the vicinity of the site usually occurs as unconfined, water table aquifers in three primary geologic zones: 1) residual soil; 2) partially weathered rock; and 3) fractured bedrock. These zones are typically interconnected through open fractures and pore spaces. The configuration of the water table generally resembles the local topography.

In the residual soil and partially weathered rock zone, groundwater is stored within the pore spaces and is released to the underlying bedrock through gravity drainage. Groundwater within the bedrock zones occurs primarily in fracture voids. Generally, fractures within the bedrock are very small but may extend to several hundred feet.

Infiltration of precipitation to recharge the water table aquifer is primarily affected by rainfall intensity and duration, pre-existing soil moisture conditions, temperature (evaporation), and plant uptake (transpiration). Seasonal high-water tables are typically observed during the late winter and early spring months of the year when maximum infiltration efficiency occurs due to lower temperatures and less plant uptake (i.e., many plants are dormant). Seasonal low-water tables are typically observed during the summer and fall months when minimum infiltration efficiency occurs due to higher temperatures and greater plant uptake of water.

3.3 STUDY AREA PHYSIOGRAPHY AND TOPOGRAPHY

The landfill is located in Haywood County, North Carolina, as shown in Figure 1. The Phase 3 and 4 areas are located to the north and west of existing Phases 1 and 2.

Topographically, the Phase 3 and 4 areas consist of a hill with radial topography in Phase 4, and a north-northeast trending drainage ravine in Phase 3. The upland portion of the hill in Phase 4 has been used as borrow soils for landfill activities is relatively flat. A portion of the drainage ravine in Phase 3 has been used as a temporary surface water sediment pond. The highest elevation in the proposed cell area is approximately 2620 feet above mean sea level (MSL) in the western portion of Phase 4, and the lowest elevation is approximately 2488 feet MSL in the northern portion of Phase 3 along the drainage ravine. The relief across Phases 3 and 4 is approximately 132 feet. Steep topography on the hillsides and side slopes of the ravines are common in Phases 3 and 4.

The surface drainage is radial around the upland portion of Phase 4 and converges towards the north-northeast trending ravine in Phase 3 and the northwest trending ravine south of Phase 4. These drainage ravines ultimately converge with the Pigeon River at the facility's northern property boundary. A topographic map/site plan is provided as Figure 3.

3.4 STUDY AREA SUBSURFACE CONDITIONS

Twenty-six borings (twenty-three soil test borings and three auger borings) have been performed in the Phase 3 and 4 areas, and rock coring was performed at four of these locations. The geologic conditions encountered while drilling were often variable with boulders and seams of partially weathered rock occurring throughout the subsurface soil overburden profile. In general, three zones were encountered: 1) the residual soils from weathered gneiss, 2) the partially weathered rock, 3) the fractured gneiss bedrock. Subsurface geology at the site is shown on two cross sections designated A-A', and B-B' (Figure 4). The subsurface conditions encountered in the Phase 3 and 4 areas are generally consistent with previous evaluations at the site (Section 1.0). A description of the subsurface materials encountered is provided below.

3.4.1 Geologic Unit Description

3.4.1.1 Residual Soil

Residual soils are the result of in-place weathering of gneiss bedrock. The residual soil profile below the topsoil consists of two identifiable components based on the USCS.

The upper soil component consists of brown and gray, sandy clayey silt and sandy silty clay and was encountered in four soil test borings in the Phase 3 and 4 areas. Where encountered, the thickness of this component varies, and generally ranging from 2.5 to 13.5 feet below ground surface, with an average thickness of 5.5 feet. USCS classifications of these soils are ML-CL, ML, and MH. Standard penetration resistance values (N-values) range from 4 to 19 with an average value of 10, indicating a stiff average consistency.

The upper soil component grades with depth into a coarser grained, less plastic, gray and brown micaceous, sandy silt and silty sand which extends to the depth of the partially weathered rock and/or auger refusal. Where encountered, the thickness of this component ranges from 3 to greater than 98 feet, with an average thickness of 49.3 feet. USCS classifications of these soils are ML and SM. N-values range from 3 to 91 with an average of 27, indicating a very firm average consistency.

Float rock (small boulders) was present in some locations at the ground surface and within the residual soil zone above the partially weathered rock level.

3.4.1.2 Partially Weathered Rock

The transition between soil and rock at the site is irregular and consists of partially weathered rock overlying the parent bedrock. Where encountered, this zone ranges in thickness from 0.5 to 12.5 feet in the Phase 3 and 4 areas.

A map of the approximate bedrock surface (auger refusal) is shown as Figure 5. Auger refusal depths may represent competent bedrock or possibly boulders of hard rock within the residual soil and partially weathered rock units. The depth to auger refusal can vary even over short horizontal distances due to boulders, fractures, joints, and the presence of less resistant rock types. Therefore, the actual depth to continuous bedrock will vary somewhat from that presented on Figure 5 and may actually be deeper than indicated.

3.4.1.3 Fractured Bedrock

Bedrock coring has been performed at four different locations for a total of 76.4 feet in the Phase 3 and 4 areas. The upper bedrock profile consists of well-foliated, moderately weathered to fresh, quartz-biotite-feldspar gneiss, which is part of the Spring Creek Granitoid Gneiss Formation. The bedrock core had generally "good" recovery (range of 42 to 100 percent; average of 88 percent) and "good" RQD (range of 25 to 100 percent; average of 76 percent). In general, the bedrock becomes more competent with depth.

3.4.2 Fracture Trace Analysis

A fracture trace analysis was performed and reported along with the data plots as part of *Site Hydrogeologic Report, White Oak Subtitle D Landfill*, Municipal Engineering Project Number G98010.5, dated February 8, 2000. A summary of the fracture trace analysis is provided below.

The trend of topographic fracture traces and lineaments within one mile of the site were measured from the Cove Creek Gap and Fines Creek USGS topographic maps. Two primary trends were observed: N5°-25°W and N35°-45°W. Two secondary trends were observed: N5°-30°E and N75°-85°E.

The primary foliation trends are N5°-20°W and N9°-20°E. The primary joint trends are N20°-40°W and N10°-20°E.

Results of the fracture trace analysis indicate that from local lineament trends, and bedrock joint and foliation orientations that the prevailing fracture trends are northwest. The primary north-northeast lineament trend was observed in the bedrock foliation pattern. The primary northwest lineament trend was observed in the bedrock joint pattern.

3.4.3 Laboratory Testing Results

A list of the soil laboratory tests performed in the Phase 3 and 4 areas is provided in the table below. The laboratory test results are summarized in Tables 5 and 6. Laboratory data sheets are in Appendix H.

SAMPLE ANALYSES	SPLIT SPOON SAMPLES TESTED	SHELBY TUBE SAMPLES TESTED	REMOLDED BAG SAMPLES TESTED
Grain-Size Analysis	10	8	3
Natural Moisture Content	10	8	-
Atterberg Limits	10	8	3
Total Porosity	10	8	-
Effective Porosity	10	8	-
In Situ Saturated permeability*	-	8	-
Triaxial Shear	-	1	-
Consolidation	-	1	-
Standard Proctor	-	-	3
Remolded permeability	-	-	3

* Hydraulic Conductivity

Ten split-spoon samples, eight undisturbed Shelby Tube samples, and three bulk samples were collected and tested in the laboratory to measure natural soil conditions in the Phase 3 and 4 areas.

Testing results of the sample collected from the upper residual soil component consisted of:

- Natural moisture content values ranging from 20.2 to 35.4 percent;
- with Liquid Limits (LL) values ranging from 52 to 59;
- Plasticity Index (PI) values ranging from 13 to 18;
- Average gravel, sand, silt, and clay contents of 0.1, 38.7, 44.6, and 16.6 percent, respectively;
- In-situ hydraulic conductivity values ranging from 1.1×10^{-5} to 2.6×10^{-4} cm/sec;

- Total porosity values ranging from 47.9 to 52.5 percent;
- Effective porosity values ranging from 3.5 to 21.0 percent;
- Standard Proctor results with optimum moisture contents of 23.8 and 25.7 percent and maximum dry densities (MDD) of 94.7 and 94.3 pcf; and
- Remolded hydraulic conductivity values of 4.8×10^{-7} and 8.8×10^{-8} cm/sec (at 7.2 and 5.4 percent wet of optimum and 95.1 and 95.0 percent of the MDD).

Testing results of the samples collected from the deeper residual soil component consisted of:

- Natural moisture content values ranging from 14.4 to 31.6 percent;
- LL values ranging from 34 to 55;
- PI values ranging from 4 to 13;
- Average gravel, sand, silt, and clay contents of 4.7, 54.8, 33.0, and 7.5 percent, respectively;
- In-situ hydraulic conductivity values ranging from 2.4×10^{-5} to 2.2×10^{-4} cm/sec;
- Total porosity values ranging from 39.4 to 52.5 percent;
- Effective porosity values ranging from 10.5 to 32.0 percent;
- Triaxial testing of an in-situ sample indicated total and effective cohesive strength (C) of 0.063 and 0.064 kips per square foot (ksf), respectively, and a total and effective Phi (ϕ) angle of 18.80 and 36.73 degrees, respectively;
- Consolidation testing of an in-situ sample indicated a preconsolidation pressure (P_p) of 8.06 ksf, a virgin slope (c_c) of 0.12, and a void ratio (e_o) of 0.760;
- A Standard Proctor result with an optimum moisture content of 22.4 percent and a MDD of 97.9 pcf; and
- A remolded hydraulic conductivity value of 2.9×10^{-7} (at 5.6 percent wet of optimum and 95.0 percent of the MDD).

Testing results of the sample collected from the partially weathered rock component consisted of:

- Natural moisture content values of 12.6 and 13.7 percent;
- LL values of 29 and 30;
- PI values of 3 to 8;
- Average gravel, sand, silt, and clay contents of 1.1, 64.8, 29.3, and 4.8 percent, respectively;
- Total porosity values of 49.0 and 49.5 percent; and
- Effective porosity values of 23.5 and 30.5 percent.

3.5 STUDY AREA HYDROGEOLOGY

Nineteen piezometers and five monitoring wells have been installed in, or close to, the Phase 3 and 4 areas. Groundwater is present above the bedrock surface in the lower elevation areas, but at or below the bedrock surface in higher elevation areas. The water-table aquifer consists of the residual soil, partially weathered rock, and fractured bedrock. These three units are hydraulically connected and thus comprise a single unconfined aquifer, although recharge rates, flow rates and storativity differ between the units based on the unique geologic conditions of each zone. The generalized configuration of the water table surface is a subdued replica of the ground surface. Generally, shallow groundwater flows to the north towards the Pigeon River. There is also a southwestward component of flow on the southern side of Phase 3. The hydrogeologic conditions encountered in the Phase 3 and 4 areas are generally consistent with the conditions encountered during previous phases of work at the landfill. A description of the hydrogeologic conditions in the study area is provided below.

3.5.1 Piezometer and Monitoring Wells

The piezometers and monitoring wells are set to intersect the groundwater in the deep residuum, partially weathered rock, or bedrock as indicated on Table 2. Piezometer and monitoring well installation diagrams are included in Appendix C and installation procedures are included in Appendix D.

3.5.2 Groundwater Elevations

3.5.2.1 Seasonal High Groundwater Elevations

Historical NOAA monthly precipitation data were obtained from Division 1, North Carolina. The data are summarized seasonally such that January-March represents *winter*, April-June represents *spring*, July-September represents *summer*, and October-December represents *fall*.

Historically in the Haywood County region, summer months will experience the most precipitation. However, the effects of evapotranspiration offset the contribution of this precipitation to recharge of the uppermost aquifer. Significant precipitation also occurs in the spring and winter months when evapotranspiration is limited. Because of these natural trends, the amount of groundwater recharge, and subsequent increase in water table level is typically greatest during winter and spring seasons.

Monthly water levels were collected from the piezometers and monitoring wells on site during September 2007 to February 2008 to establish seasonal high water levels. Hydrographs of the data indicate that the 2007 seasonal high water levels were near typical levels as observed in prior years (Appendix E). Figure 7 represents the seasonal high water table, in which the highest water level collected from September 2007 to February 2008 in each piezometer/well was used for contouring.

3.5.2.2 Estimated Long-Term Seasonal High Groundwater Elevations

Groundwater levels were periodically recorded in piezometers and monitoring wells at the site between June 1998 and February 2008 (Table 3). On the average, the groundwater levels in the pre-existing monitoring wells and piezometer have typically varied on the average of 3.61 feet between the historical highest water level elevations and the 2007-2008 seasonal high levels (Table 3). Based on these water level trends, an estimated long-term seasonal high water table elevation contour map was prepared (Figure 8). This map is a composite water table contour map using: 1) the historical highest water level elevation in the pre-existing monitoring wells and piezometers; and 2) adding 3.61 feet to the maximum observed water level in each of the newly installed piezometer in the Phase 3 and 4 areas.

3.5.3 Groundwater Flow Direction

Groundwater at the site flows in a radial pattern around the upland areas, and has a configuration similar to topography. Flow beneath the Phase 3 and 4 areas is predominantly to the north towards the Pigeon River. There is also a southwestward component of flow on the southern side of Phase 3. Groundwater flow is through the soil matrix, the weathered fracture openings, and the bedrock fractures. Recharge to the unconfined aquifer occurs at the higher elevations. Groundwater

discharge is to the northeastward trending drainage features on the northern side of Phases 3 and 4, and to the northwestward trending drainage feature located south of Phase 3.

3.5.4 Man-made Influences to Groundwater Levels

Man-made features that could influence groundwater levels at the site include existing and proposed lined waste cells, and existing and proposed sediment ponds.

Currently, Phases 1 and 2 have been constructed in the upland (recharge) area in the central portion of the site. As cell construction proceeds, groundwater infiltration and recharge of the water table aquifer will be limited, resulting in lower groundwater levels in the vicinity of the cells.

One sediment basin and one leachate lagoon have been constructed north of Phase 1. Four additional sediment basins are proposed to be constructed during the development of Phases 3 and 4 (two north and one northeast of Phases 3 and 4, and one southwest of Phase 4; Figure 3). It is our understanding that the leachate lagoon has a liner system, and the sediment ponds do not have liner systems. As a result, the groundwater table may be slightly mounded in the vicinity of the existing and proposed sediment ponds.

There are no groundwater receptors located between the proposed location of landfill cell construction and the Pigeon River, which is the downgradient groundwater discharge area at the site.

3.5.5 Hydraulic Coefficients and Groundwater Flow Velocity

The velocity of groundwater flow is derived from the equation:

$$V = \frac{Ki}{n_e}$$

Where

V is the flow velocity
K is the hydraulic conductivity
i is the hydraulic gradient; and
n_e is the effective porosity.

Estimated values for these parameters are provided below and summarized on Tables 4, 5, and 8.

3.5.5.1 Hydraulic Conductivity

Hydraulic conductivity is defined as the ability of the aquifer material to conduct water under a hydraulic gradient. Six slug tests have been performed in the Phase 3 and 4 areas to measure the *in situ* hydraulic conductivity of the different zones of the water-table aquifer. The slug test results were evaluated using the Bouwer and Rice Method for partially-penetrating wells in an unconfined aquifer. The slug tests performed at the site include:

- Three tests performed in piezometers set in the deep residual soil;
- One test in a piezometer set in the partially weathered rock; and

- Two tests performed in piezometers set in the bedrock.

The water table was encountered below the upper residual soil; therefore, hydraulic conductivity in the unsaturated zone was determined by laboratory testing four undisturbed soil samples (Section 3.4.3 and Table 5). Based on the slug tests conducted in the Phase 3 and 4 areas, the range of hydraulic conductivity values is as follows:

- 1.1×10^{-5} cm/sec (BLE-11) to 4.7×10^{-4} cm/sec (BLE-3) in deep residuum;
- 2.6×10^{-5} cm/sec (BLE-14) in partially weathered rock; and
- 1.9×10^{-6} cm/sec (BLE-9) to 2.0×10^{-4} cm/sec (BLE-7D) in the bedrock.

3.5.5.2 Hydraulic Gradient

The hydraulic gradient is determined by dividing the difference in groundwater elevations at two locations by the horizontal distance between those locations along the direction of groundwater flow. Hydraulic gradients in the Phase 3 and 4 areas range from about 0.222 in the northern portion of proposed Phase 4, to about 0.0435 in the central portion of proposed Phase 3. The average hydraulic gradient across the study areas is 0.133 (Table 7).

3.5.5.3 Effective Porosity and Specific Yield

Effective porosity is the volume of void spaces through which water or other fluids can travel in soil divided by the total volume of the soil. Effective porosity can be assumed to be approximately equal to specific yield. Specific yield is defined as the ratio of the volume of water that drains from saturated sediment owing to the attraction of gravity to the total volume of sediment. The laboratory grain size analyses were used to derive values for specific yield and effective porosity (Fetter, 1994).

Based on grain size analyses (Tables 5 and 8), effective porosity measurements in the study area range from about:

- 3.5 to 21.0% (average = 15.3%) in the upper residuum;
- 10.5 to 32.0% (average = 23.4%) in the deep residuum;
- 23.5% to 30.5% (average = 27.0%) in the partially weathered rock;
- the effective porosity can be expected to range from about 5% to 10% for fractured crystalline bedrock (average = 7.5%) according to Kruseman and deRidder (1989).

3.5.5.4 Groundwater Flow Velocity

The velocity of groundwater movement (V) is a function of existing hydraulic gradient (i), the hydraulic conductivity (K), and the effective porosity (n_e), in the equation $V = Ki/n_e$ in the deep residuum, partially weathered rock, and bedrock. Based on these parameters and the data provided above, the horizontal movement of groundwater across Phase 3 and 4, summarized on Table 7, is approximately:

- 0.068 to 0.74 feet/day in the deep residual soil zone,
- 0.011 to 0.070 feet/day in the partially weathered rock zone, and
- 0.024 to 0.99 feet/day in the bedrock zone.

3.5.6 Vertical Flow Gradients

Vertical flow gradients were evaluated at four locations in the Phase 3 and 4 areas. Based on groundwater level measurements on February 14, 2008 from the piezometers and wells, the following vertical gradients were observed:

PIEZOMETER PAIR	LOCATION DESCRIPTION	RECHARGE GRADIENT	DISCHARGE GRADIENT
MW-5A/MW-5D	Topographically low area directly downgradient of the temporary sediment pond in Proposed Phase 4.	X	
PZ-7S/PZ-7D	Topographically low area along the drainage feature in Proposed Phase 4 (downgradient of MW-5A/MW-5D).		X

The vertical gradients observed at the site are typical for unconfined aquifers in this portion of the Blue Ridge. Groundwater recharge occurs in the upland areas in Phases 3 and 4. Discharge occurs to drainage feature in the central portion of Phase 3 and the drainage feature south of Phase 4, which both flow towards the Pigeon River north of the site. Vertical flow gradients are summarized on Table 9.

3.6 GEOTECHNICAL CONSIDERATIONS

An evaluation of the potential impact from faults, seismic zones and unstable areas, as required by 15A NCAC13B.1622 subsections (4), (5), and (6), was previously prepared by others for the current landfill site and documented as part of prior SHR and DHR projects (Section 1.0). These items were briefly reviewed to provide a background for our geotechnical evaluation. The results of our update to these items are provided below.

3.6.1 Fault Areas

No Holocene faults are located within 200 feet of the subject site (Horton and Zullo, 1991).

3.6.2 Seismic Impact Zones

According to the definition of seismic impact zones in 15A NCAC 13B.1622 (5), this site is in a seismic impact zone. The maximum horizontal acceleration expressed as a percentage of the earth's gravity (g) in rock is 0.176g with a 2% probability of being exceeded in 50 years (equal to 10% probability in 250 years; USGS, 2006). The design of the landfill considered the seismic condition. BLE has performed a seismic stability analysis for the design of Phases 3 and 4. The results of the analysis are provided in Appendix I and indicate the landfill is stable under both static and seismic conditions.

3.6.3 Unstable Areas

An unstable area according to 15A NCAC 13B.1622 (6) is defined as a location that is susceptible to natural or human induced events or forces capable of impairing the integrity of some or all of the

landfill structural components responsible for preventing releases from a landfill. Unstable areas could include poor foundation conditions, areas susceptible to mass movements, and karst terrains. Site and subsurface data obtained was evaluated to determine if unstable site areas exist. The site is not in a karst area. No unstable conditions were present. BLE evaluated specific subgrade settlement and slope stability conditions for Phases 3 and 4. The analyses results are provided in Appendix I. The resulting settlements will be well within tolerable limits. Slope stability analysis indicates the planned subgrade, structural fill slopes, waste mound, and cap are stable.

3.6.4 Permeability of Potential On-Site Soils for Liner and Cover Construction

The permeability of selected potential on-site borrow soils were determined as indicated in Section 3.4.3 titled Laboratory Testing Results. Three bag samples of soil were collected (two of the upper residuum and one of the deeper residuum). The samples were compacted at varying percents of the Standard Proctor maximum dry density, and at varying moisture contents of the Standard Proctor optimum moisture content. Hydraulic conductivity values of the upper residuum were 4.8×10^{-7} and 8.8×10^{-8} cm/sec.

The near surface soils at the site consist of three general soil types based on topographic position. The near surface soils in the higher elevation areas, including the upper portions of the hill side-slopes, consist of reddish-brown silty clay and clayey silt. These soils generally transition to light brown clayey silt along the lower elevations of the hill side-slopes.

The red-brown silty clay and clayey silts along the higher portions of the site present the most favorable materials for use as compacted clay liner, soil liner, or closure cap soils. The plasticity of these soils fall generally well below the "A" line. The clayey soils are found immediately below the topsoil to depths of 2 to 4 feet in limited quantity. Soils that could be used as compacted soil liner can be found over a limited portion of the site. During site clearing and stripping activities, these soils should be carefully delineated and stockpiled for later use.

The *in situ* moistures of the silty clay will vary based on recent rainfall; however, they should be found at moisture contents within a few points of the standard Proctor optimum moisture content. Some modification of moisture will be required during soil liner or cap construction.

3.6.5 Excavation

Excavation of the residual soils can be accomplished using conventional earth moving equipment. Historical excavation of the site has typically employed track excavators, dozers, and trucks. Some excavation has been performed using tractor scrapers. An estimated bedrock elevation (auger refusal) contour map was developed as Figure 5 which is based on auger refusal depths in the soil borings drilled at this site. Materials sufficiently hard to cause refusal to the mechanical drill augers may result from continuous bedrock, boulders, lenses, ledges, or layers of relatively hard rock or residual soil. Coring was performed at four locations in the Phases 3 and 4 areas where refusal to augering occurred. Continuous rock was found with varying recovery and Rock Quality Designation (RQD) as discussed above in Section 3.4.1.3. Due to its typically varying surface, the actual occurrence of hard rock during site grading may vary somewhat from that presented in Figure 5.

There is usually no sharp distinction between soil and rock in residual soil areas as at this site. Typically, the degree of weathering simply decreases with greater depth until solid rock is eventually reached. The partially weathered rock, as well as the soil above, may also contain boulders, lenses or ledges of hard rock. The mechanical auger used in this exploration could penetrate some of the partially weathered rock of the transitional zone. The ease of excavation will depend on the geologic structure of the material itself, such as the direction of bedding, planes or weakness and spacing between discontinuities. Weathered rock or rock that cannot be penetrated by the mechanical drill auger will likely require heavy excavating equipment with ripping tools or other methods for removal, if desired.

3.6.6 Engineered Fill

The residual soils that will be excavated from the cell areas to achieve the design subgrade elevations are suitable for use as structural fill. Some moisture modification (wetting or drying) may be required depending on the particular area of excavation. The existing fill soils near BLE-3, which form an apparent existing storm water control feature and potential surface sediment deposits in the central lower areas in Phase No. 3, should be evaluated for reuse as fill at the time of excavation by the geotechnical engineer. Conventional compaction equipment and methods should be appropriate.

Fill used for raising site grades should be uniformly compacted to at least 95 percent of the standard Proctor maximum dry density (ASTM D 698). Prior to fill placement, the areas to receive structural fill should be stripped of topsoil and vegetation and proofrolled using a loaded dump truck or similar equipment. The proofrolling should be observed by the geotechnical/CQA engineer or his representative. Any areas which undergo rutting or excessive degradation should be excavated to firm soils.

Partially weathered rock may be mixed with the soil borrow materials provided it can be broken down by the excavation and compaction equipment into particles with a maximum dimension of 6 inches. Larger boulders or rock pieces may be used in the lower portions of the deeper fills if the boulders are placed individually and soil compacted around and over each boulder. Sufficient quantities of soil should be mixed with the partially weathered rock so that voids do not result between the pieces of partially weathered rock and the fill meets the compaction requirements.

Before filling operations begin, representative samples of each proposed fill materials should be collected and tested to determine the compaction and classification characteristics. The maximum dry density and optimum moisture content should be determined. Once compaction begins, a sufficient number of density tests should be performed to measure the degree of compaction being obtained.

Earthwork cut or fill slopes can be constructed as steep as 2H:1V (horizontal:vertical). Structural fill slopes at the 2H:1V inclination should initially be constructed at two to three feet beyond the design slope due to difficulty of compacting the edge of slopes, then trimmed to final grade leaving the exposed face well compacted. Slopes of 3H:1V or flatter, can be compacted in place without overfilling. Cut and fill slope surfaces outside the cell area should be protected from erosion by grassing or other means. Where the cell embankment is to be constructed on natural slopes steeper than 4H:1V, we recommend that the fill soils be keyed into the slopes using horizontal benches

(stair-step fashion) to facilitate placement and compaction of structural fill and to prevent formation of a potential slip surface.

The surface of compacted subgrade soils can deteriorate and lose its support capabilities when exposed to environmental changes and construction activity. Deterioration can occur in the form of freezing, formation of erosion gullies, extreme drying, exposure for a long period of time, or rutting by construction traffic. We recommend that if the fill soils within the cell become deteriorated or softened, they be proofrolled, scarified and recompacted (and additional fill placed, if necessary) prior to construction of the compacted soil liner. Additionally, any excavations through the cell embankments (such as leachate collection line trenches) should be properly backfilled in compacted lifts. Recompaction of subgrade surfaces and compaction of backfill should be checked with a sufficient number of density tests to determine if adequate compaction is being achieved.

-oOo-

4.0 CONCLUSIONS

The proposed Phase 3 cell location is along a northeast trending drainage feature west of existing Phase 1. The proposed Phase 4 cell location is on a hill west of proposed Phase 3. The Phase 3 and 4 areas' subsurface geology and hydrogeology are typical of Blue Ridge terrain in this vicinity of North Carolina with deeply weathered biotite gneiss. No unusual or unexpected geologic features were observed in the Phase 3 and 4 areas.

Groundwater flow beneath the Phase 3 and 4 areas is predominantly to the north towards the Pigeon River. There is also a southwestward component of flow on the southern side of Phase 3. Groundwater flow is through the soil matrix, the weathered fracture openings, and the bedrock fractures. Recharge to the unconfined aquifer occurs at the higher elevations. Groundwater discharge is to the northeastward trending drainage features on the northern side of Phases 3 and 4, and to the northwestward trending drainage feature located south of Phase 3. Other than these natural features, there are no groundwater receptors to this landfill phase.

The site is favorable for landfill development considering geotechnical aspects. The site is in a seismic impact zone, but the landfill structural components have been designed, using conventional construction, to resist the seismic magnitude. The existing residuum and the planned structural fill will form a stable foundation for the landfill. Anticipated subgrade total and differential settlements of the completed waste cells are expected to be well within acceptable limits of the structural components and leachate collection system of a MSW landfill. The on-site residual soils are suitable for use as structural fill. The residual soils and the planned new engineered fill will form stable slopes and provide acceptable interface friction with the base and cap liner systems. The planned structural fill and waste mound slopes will be stable under static and seismic conditions. Low permeability surficial soils that could be used to construct a base clay liner ($K \leq 1.0 \times 10^{-7}$ cm/sec) or final cover cap ($K \leq 1.0 \times 10^{-5}$ cm/sec) are present on site in limited quantities. Careful selection and use of these clayey soils will be required during waste cell development.

This Design Hydrogeologic Report was prepared to satisfy the requirements specified in the North Carolina Title 15A NCAC 13B .1623 (b). Based on the results of field and laboratory testing, it is our opinion that the study area is geologically, hydrogeologically, and geotechnically suitable for municipal solid waste landfill cell development. This Design Hydrogeologic Report, while specifically addressing Phases 3 and 4, also considers the potential expanded landfill footprint and grades shown in the Facility Plan.

-oOo-

5.0 ANNOTATED BIBLIOGRAPHY

Bouwer, H. and Rice, R.C., 1976, "A slug test method for determining hydraulic conductivity of unconfined aquifers with completely or partially penetrating wells," Water Resources Research, Vol. 12, No. 3, pp. 423-428.
- Slug testing data reduction procedures.

Brown, M.B., and others (compilers), 1985, *Geologic Map of North Carolina*: NCDNRCD, scale 1:500,000.
- General geologic setting and fault locations.

Carter, M.W., and Weiner, L.S., 1999, Bedrock Geologic *Map of the Fines Creek 7.5-Minute Quadrangle*, North Carolina, North Carolina Geological Survey, Geologic Map Series 8.

Fetter, C.W., 1994, *Applied Hydrogeology*: Merrill Publishing Company, Columbus, Ohio.
- Basic hydrogeologic principles and estimates of effective porosity in soils.

Hadley, J.B., and Goldsmith, R.E., 1983, *Geology of the Eastern Great Smoky Mountains, North Carolina-Tennessee*: United States Geological Survey Professional Paper 349-B.

Horton, J.W. and Zullo, V.A., 1991, *The Geology of the Carolinas: Carolina Geological Society fifteenth anniversary volume*: The University of Tennessee Press, Knoxville, TN.
- General geologic setting.

Kruseman, G.P., and deRidder, N.A., 1989, *Analysis and Evaluation of Pumping Test Data*: *Publication 47*, International Institute for Land Reclamation and Improvement, Wageningen, The Netherlands.
- Estimates of effective porosity in fractured bedrock.

United States Geologic Survey (USGS), Earthquake Hazards Program, International Building Code (IBC), 2006.
- Seismic impact zones.

-oOo-

TABLES

TABLE 1

MONITORING WELL, PIEZOMETER, AND BORING SURVEY INFORMATION

White Oak MSW Landfill - Phase 3 & 4 DHR

Haywood County, North Carolina

BLE Project Number J07-1957-02

Well/ Piezometer	Ground Elevation	TOC Elevation	Northing	Easting	Status of Well/Piezometer
BLE-1	**2574.23**	**2577.77**	**720937.6102**	**811220.4171**	**Present**
BLE-2	**2525.68**	**2529.57**	**721195.5520**	**811425.0105**	**Present**
BLE-3	**2519.77**	**2523.43**	**721364.1500**	**811475.5286**	**Present**
BLE-4 (boring)	**2560.09**	**NA**	**721347.2616**	**811709.1865**	**Abandoned**
BLE-5	**2497.10**	**2500.99**	**721592.0538**	**811514.7738**	**Present**
BLE-6	**2532.96**	**2536.67**	**721667.9455**	**811741.4725**	**Present**
BLE-7S	**2492.12**	**2495.30**	**721759.8035**	**811585.9715**	**Present**
BLE-7D	**2491.92**	**2495.70**	**721766.2970**	**811589.4921**	**Present**
BLE-8 (boring)	**2473.09**	**NA**	**721934.7910**	**811656.4570**	**Abandoned**
BLE-9	**2552.54**	**2556.63**	**721775.5467**	**811375.3773**	**Present**
BLE-10	**2612.97**	**2615.73**	**721574.7601**	**810881.4408**	**Present**
BLE-11	**2630.61**	**2634.27**	**721450.3759**	**810649.4778**	**Present**
BLE-12	**2620.95**	**2624.50**	**721285.4999**	**810817.1273**	**Present**
BLE-13	**2609.39**	**2612.66**	**721419.1687**	**811109.9420**	**Present**
BLE-14	**2610.41**	**2613.65**	**721222.6091**	**811099.9933**	**Present**
BLE-15	**2584.11**	**2587.90**	**720930.9031**	**811053.8980**	**Present**
BLE-16	**2614.70**	**2618.50**	**721398.3928**	**810908.9271**	**Present**
BLE-17	**2611.46**	**2615.91**	**721159.4128**	**810931.6189**	**Present**
MW-1A	2517.97	2520.02	721096.3047	812481.4745	Present
MW-2	2494.43	2496.71	721460.7647	812309.4391	Present
MW-2D	2494.69	2496.89	721456.0050	812311.8744	Present
MW-3	2435.06	2437.28	721947.2608	812058.3839	Present
MW-3D	2434.17	2436.94	721956.0474	812071.8689	Present
MW-4A	2496.19	2498.54	721692.8083	811976.7333	Present
MW-5A	**2502.29**	**2503.58**	**721496.6325**	**811628.8222**	**Present**
MW-5D	**2502.18**	**2502.90**	**721503.8890**	**811631.0644**	**Present**
MW-8	2474.84	2477.33	721704.5021	812155.0344	Present
MW-9	UK	2430.15	UK	UK	Present
MW-11S	UK	2674.58	719905.8752	811642.8913	Present
MW-11D	2672.01	2674.89	719909.3380	811651.5544	Present
MW-12	**2526.93**	**2529.63**	**721082.9594**	**811524.1854**	**Present**
MW-13S	**2529.67**	**2532.20**	**721079.1672**	**811454.9494**	**Present**
MW-13D	**2528.11**	**2530.86**	**721088.3729**	**811454.4229**	**Present**
MW-14	UK	2711.69	UK	UK	Present
MW-15	UK	2547.41	UK	UK	Present
P-4	**2571.25**	**2573.14**	**721895.9954**	**811433.5246**	**Present**
P-5	**2485.02**	**2487.78**	**721882.4117**	**811171.8164**	**Present**
P-6	**2594.13**	**2597.74**	**721486.7978**	**811249.7675**	**Present**

Notes:

1. **Bold** borings represent those in the Phase 3 and 4 Cell area.
2. Measurements are in feet; elevations are relative to mean sea level.
3. TOC = *Top Of Casing*
4. NA = *Not Applicable*
5. UK = *Unknown*
6. Surveying was performed by McGill Associates.
7. Source of elevation data for MW-9, MW-14 and MW-15 cannot be confirmed.

TABLE 2

MONITORING WELL AND PIEZOMETER CONSTRUCTION DETAILS
White Oak MSW Landfill - Phase 3 & 4 DHR
Haywood County, North Carolina
BLE Project Number J07-1957-02

Well/ Piezometer	Ground Elev.	TOC Elev.	Auger Refusal Depth	Auger Refusal Elev.	Bedrock Drilling Depth	Screened Interval Depth	Screened Interval Elevation	Zone Screened	Status of Well/Piezometer
BLE-1	**2574.23**	**2577.77**	**66.0**	**2508.2**	**NA**	**55.0 - 65.0**	**2519.2 - 2509.2**	**Deep Residuum/PWR**	**Present**
BLE-2	**2525.68**	**2529.57**	**>40.0**	**<2485.7**	**NA**	**29.0 - 39.0**	**2496.7 - 2486.7**	**Deep Residuum**	**Present**
BLE-3	**2519.77**	**2523.43**	**>50.0**	**<2469.8**	**NA**	**38.0 - 48.0**	**2481.8 - 2471.8**	**Deep Residuum**	**Present**
BLE-4 (boring)	**2560.09**	**NA**	**2.5**	**2557.6**	**NA**	**NA**	**NA**	**-**	**Abandoned**
BLE-5	**2497.10**	**2500.99**	**26.0**	**2471.1**	**NA**	**15.0 - 25.0**	**2482.1 - 2472.1**	**Deep Residuum/PWR**	**Present**
BLE-6	**2532.96**	**2536.67**	**46.0**	**2487.0**	**NA**	**36.0 - 46.0**	**2497.0 - 2487.0**	**Deep Residuum**	**Present**
BLE-7S	**2492.12**	**2495.30**	**26.0**	**2466.1**	**NA**	**15.1 - 25.1**	**2477.1 - 2467.1**	**Deep Residuum**	**Present**
BLE-7D	**2491.92**	**2495.70**	**32.0**	**2459.9**	**32.0 - 60.0**	**49.6 - 59.6**	**2442.3 - 2432.3**	**Bedrock**	**Present**
BLE-8 (boring)	**2473.09**	**NA**	**3.0**	**2470.1**	**NA**	**NA**	**NA**	**-**	**Abandoned**
BLE-9	**2552.54**	**2556.63**	**25.0**	**2527.5**	**25.0 - 49.0**	**37.7 - 47.7**	**2514.8 - 2504.8**	**Bedrock**	**Present**
BLE-10	**2612.97**	**2615.73**	**>78.9**	**<2534.1**	**NA**	**68.7 - 78.7**	**2544.3 - 2534.3**	**Deep Residuum**	**Present**
BLE-11	**2630.61**	**2634.27**	**>103.0**	**<2527.6**	**NA**	**92.6 - 102.6**	**2538.0 - 2528.0**	**Deep Residuum**	**Present**
BLE-12	**2620.95**	**2624.50**	**>90.2**	**<2530.8**	**NA**	**80.0 - 90.0**	**2541.0 - 2531.0**	**Deep Residuum**	**Present**
BLE-13	**2609.39**	**2612.66**	**86.0**	**2523.4**	**NA**	**71.4 - 81.4**	**2538.0 - 2528.0**	**PWR**	**Present**
BLE-14	**2610.41**	**2613.65**	**73.5**	**2536.9**	**NA**	**63.0 - 73.0**	**2547.4 - 2537.4**	**Deep Residuum/PWR**	**Present**
BLE-15	**2584.11**	**2587.90**	**>75.0**	**<2509.1**	**NA**	**64.1 - 74.1**	**2520.0 - 2510.0**	**Deep Residuum/PWR**	**Present**
BLE-16	**2614.70**	**2618.50**	**>80.0**	**<2534.7**	**NA**	**68.2 - 78.2**	**2546.5 - 2536.5**	**Deep Residuum**	**Present**
BLE-17	**2611.46**	**2615.91**	**101.0**	**2510.5**	**NA**	**89.7 - 99.7**	**2521.8 - 2511.8**	**Deep/PWR**	**Present**
MW-1A	2517.97	2520.02	26.0	2492.0	NA	10.4 - 25.4	2507.6 - 2492.6	Deep Residuum	Present
MW-2	2494.43	2496.71	35.5	2458.9	NA	19.9 - 34.9	2474.5 - 2459.5	Deep Residuum/PWR	Present
MW-2D	2494.69	2496.89	36.9	2457.8	36.9 - 55.1	44.6 - 54.6	2450.1 - 2440.1	Bedrock	Present
MW-3	2435.06	2437.28	21.2	2413.9	NA	5.6 - 20.6	2429.5 - 2414.5	Deep Residuum	Present
MW-3D	2434.17	2436.94	21.4	2412.8	21.4 - 37.0	26.5 - 36.5	2407.7 - 2397.7	Bedrock	Present
MW-4A	2496.19	2498.54	27.9	2468.3	27.9 - 100.3	85.2 - 100.2	2411.0 - 2396.0	Bedrock	Present
MW-5A	**2502.29**	**2503.58**	**20.1**	**2482.2**	**NA**	**4.5 - 19.5**	**2497.8 - 2482.8**	**Deep Residuum**	**Present**
MW-5D	**2502.18**	**2502.90**	**20.0**	**2482.2**	**20.0 - 36.2**	**25.7 - 35.7**	**2476.5 - 2466.5**	**Bedrock**	**Present**
MW-8	2474.84	2477.33	>42.8	<2432.0	NA	31.0 - 41.0	2443.8 - 2433.8	Deep Residuum	Present
MW-9	UK	2430.15	11	UK	UK	4.5 - 9.5	UK	Fill	Present
MW-11S	UK	2674.58	UK	UK	UK	UK	UK	UK	Present
MW-11D	2672.01	2674.89	97.0	2575.0	97.0 - 128.0	118.0 - 127.6	2554.0 - 2544.4	Bedrock	Present
MW-12	**2526.93**	**2529.63**	**UK**	**UK**	**UK**	**UK**	**UK**	**UK**	**Present**
MW-13S	**2529.67**	**2532.20**	**UK**	**UK**	**UK**	**UK**	**UK**	**UK**	**Present**
MW-13D	**2528.11**	**2530.86**	**UK**	**UK**	**UK**	**UK**	**UK**	**UK**	**Present**
MW-14	UK	2711.69	UK	UK	UK	UK	UK	UK	Present
MW-15	UK	2547.41	UK	UK	UK	UK	UK	UK	Present
P-4	**2571.25**	**2573.14**	**59.0**	**2512.3**	**59.0 - 81.0**	**71.0 - 81.0**	**2500.3 - 2490.3**	**Bedrock**	**Present**
P-5	**2485.02**	**2487.78**	**20.0**	**2465.0**	**20.0 - 52.3**	**42.3 - 52.3**	**2442.7 - 2432.7**	**Bedrock**	**Present**
P-6	**2594.13**	**2597.74**	**58.0**	**2536.1**	**58.0 - 67.5**	**57.5 - 67.5**	**2536.6 - 2526.6**	**Bedrock**	**Present**

Notes:
1. **Bold** borings represent those in the Phase 3 and 4 Cell area.
2. Measurements are in feet; elevations are relative to mean sea level.
3. TOC = *Top Of Casing*
4. NA = *Not Available*
5. UK = *Unknown*
6. PWR = *Partially Weathered Rock*
7. Surveying was performed by McGill Associates.
8. Source of elevation data for MW-9, MW-14 and MW-15 cannot be confirmed.

TABLE 3

GROUNDWATER DEPTH ELEVATION MEASUREMENTS
White Oak MSW Landfill - Phase 3 & 4 DHR
Haywood County, North Carolina
BLE Project Number J07-1957-02

			GROUNDWATER ELEVATION MEASUREMENTS																			Sept '07 to Feb '08	Data from 1998 to 2008			Estimated Long-Term Seasonal High		
					1998					2004	2005		2006		2007					2008		Seasonal High	Maximum	Minimum	Difference	AVG Difference	LTSHWT	Data
WELL	GROUND ELEV.	TOC ELEV.	TOB	24-Hr	6/9/98	7/7/98	8/17/98	9/25/98	10/27/98	10/21/04	4/18/05	10/13/05	4/25/06	10/20/06	4/26/07	9/20/07	10/25/07	11/30/07	12/14/07	1/16/08	2/14/08	Elev.	Elev.	Elev.	Feet	Feet	Feet	Source
BLE-1	2574.23	2577.77	2526.23	2531.73	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	**2531.12**	2530.75	2530.36	2530.22	2529.85	2529.64	2531.12	2531.12	2529.64	1.48	-	2534.73	Calculation
BLE-2	2525.68	2529.57	2508.58	2513.23	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	2512.97	2513.07	2513.04	2513.10	2513.42	**2513.76**	2513.76	2513.76	2512.97	0.79	-	2517.37	Calculation
BLE-3	2519.77	2523.43	2500.27	2501.33	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	2500.95	2501.17	2501.25	2501.34	2501.58	**2501.87**	2501.87	2501.87	2500.95	0.92	-	2505.48	Calculation
BLE-5	2497.10	2500.99	2485.80	2492.50	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	2491.98	2492.64	2492.48	2492.81	2493.11	**2493.33**	2493.33	2493.33	2491.98	1.35	-	2496.94	Calculation
BLE-6	2532.96	2536.67	2488.31	2488.25	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	2488.24	2488.16	2488.47	2488.54	2488.77	**2488.93**	2488.93	2488.93	2488.16	0.77	-	2492.54	Calculation
BLE-7S	2492.12	2495.30	2481.82	2484.32	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	2483.72	2483.31	2483.76	2483.99	2484.69	**2484.83**	2484.83	2484.83	2483.31	1.52	-	2488.44	Calculation
BLE-7D	2491.92	2495.70	2483.62	2483.52	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	2484.41	2484.73	2484.47	2484.65	2485.05	**2485.24**	2485.24	2485.24	2484.41	0.83	-	2488.85	Calculation
BLE-9	2552.54	2556.63	2509.84	2509.54	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	**2509.28**	2506.28	2505.73	2505.60	2505.39	2505.11	2509.28	2509.28	2505.11	4.17	-	2512.89	Calculation
BLE-10	2612.97	2615.73	2551.47	NM	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	**2551.22**	2551.03	2550.45	2544.28	2543.80	2543.41	2551.22	2551.22	2543.41	7.81	-	2554.83	Calculation
BLE-11	2630.61	2634.27	2540.91	2546.01	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	**2540.95**	2540.75	2540.17	2540.12	2539.57	2539.21	2540.95	2540.95	2539.21	1.74	-	2544.56	Calculation
BLE-12	2620.95	2624.50	2545.05	2545.05	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	**2545.19**	2544.94	2544.35	2544.27	2543.73	2543.30	2545.19	2545.19	2543.30	1.89	-	2548.80	Calculation
BLE-13	2609.39	2612.66	2540.39	2541.89	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	**2542.44**	2542.40	2542.07	2541.98	2541.60	2541.19	2542.44	2542.44	2541.19	1.25	-	2546.05	Calculation
BLE-14	2610.41	2613.65	2551.31	2551.21	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	**2551.21**	2551.10	2550.60	2550.49	2549.97	2549.46	2551.21	2551.21	2549.46	1.75	-	2554.82	Calculation
BLE-15	2584.11	2587.90	2526.36	2527.01	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	**2527.18**	2526.87	2526.49	2526.43	2526.24	2526.53	2527.18	2527.18	2526.24	0.94	-	2530.79	Calculation
BLE-16	2614.70	2618.50	2546.20	2552.49	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	**2555.63**	2555.25	2554.55	2554.42	2553.80	2553.34	2555.63	2555.63	2553.34	2.29	-	2559.24	Calculation
BLE-17	2611.46	2615.91	2523.86	2538.05	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	2521.72	**2537.59**	2537.00	2536.94	2536.32	2535.88	2537.59	2537.59	2521.72	15.87	-	2541.20	Calculation
MW-1A	2517.97	2520.02	UK	UK	**2503.77**	2503.33	2502.69	2502.39	2502.14	2502.30	2502.97	2501.58	2502.47	2500.81	2500.65	2496.12	2495.46	2495.06	2494.94	2495.33	2496.07	2496.12	2503.77	2494.94	8.83	7.65	2503.77	Max 6/98-2/08
MW-2	2494.43	2496.71	UK	UK	2467.35	2466.91	2466.14	2465.61	2465.53	2466.65	**2467.78**	**2466.00**	2467.47	2465.84	**2466.68**	2465.36	2465.26	2465.15	2465.20	2465.44	2466.10	2466.10	2467.78	2465.15	2.63	1.68	2467.78	Max 6/98-2/08
MW-2D	2494.69	2496.89	UK	UK	NM	NM	NM	NM	NM	2466.89	**2468.06**	2466.26	2467.71	2466.03	2466.89	2465.55	2465.39	2465.35	2465.34	2465.64	2466.25	2466.25	2468.06	2465.34	2.72	1.81	2468.06	Max 6/98-2/08
MW-3	2435.06	2437.28	UK	UK	2429.72	2429.20	2428.03	2426.93	2426.51	2428.99	2430.58	2428.38	**2430.60**	2428.07	2428.93	2427.02	2426.70	2426.39	2426.51	2427.17	2428.01	2428.01	2430.60	2426.39	4.21	2.59	2430.60	Max 6/98-2/08
MW-3D	2434.17	2436.94	UK	UK	NM	NM	NM	NM	NM	2420.62	**2421.37**	2420.13	2421.17	2420.23	2420.24	2419.58	2419.45	2419.30	2419.31	2419.57	2419.89	2419.89	2421.37	2419.30	2.07	1.48	2421.37	Max 6/98-2/08
MW-4A	2496.19	2498.54	UK	UK	2459.44	**2463.46**	2462.80	2456.35	2460.26	2451.96	2451.41	2450.77	2448.97	2447.77	2447.46	2448.14	2448.14	2448.27	2448.19	2448.07	2448.08	2448.27	2463.46	2447.46	16.00	15.19	2463.46	Max 6/98-2/08
MW-5A	2502.29	2503.58	UK	UK	2497.22	2496.56	2496.28	2495.95	2495.88	2497.43	2498.48	2497.49	**2499.28**	NM	2498.08	2496.80	2497.12	2497.06	2497.14	2497.34	2497.59	2497.59	2499.28	2495.88	3.40	1.69	2499.28	Max 6/98-2/08
MW-5D	2502.18	2502.90	UK	UK	2496.24	2495.85	2495.69	2495.52	2495.50	2496.25	2496.92	2496.30	**2497.58**	NM	2496.72	2495.82	2496.14	2496.31	2496.38	2496.55	2496.75	2496.75	2497.58	2495.50	2.08	0.83	2497.58	Max 6/98-2/08
MW-8	2474.84	2477.33	UK	UK	NM	NM	NM	NM	NM	2446.80	**2447.63**	2446.30	2447.37	2445.96	2446.59	2445.30	2445.00	2444.77	2444.79	2445.05	2445.63	2445.63	2447.63	2444.77	2.86	2.00	2447.63	Max 6/98-2/08
MW-9	UK	2430.15	UK	UK	NM	NM	NM	NM	NM	2420.90	2421.02	2420.83	2420.99	**2421.09**	2420.87	NM	NM	NM	NM	NM	NM	-	2421.09	2420.83	0.26	-	2421.09	Max 6/98-2/08
MW-11S	UK	2674.58	UK	UK	NM	NM	NM	NM	NM	2590.86	2592.08	2593.90	2594.94	**2595.11**	2593.96	NM	NM	NM	NM	NM	NM	-	2595.11	2590.86	4.25	-	2595.11	Max 6/98-2/08
MW-11D	2672.01	2674.89	UK	UK	NM	NM	NM	NM	NM	2590.52	2591.74	2593.52	2594.30	**2594.57**	2593.35	NM	NM	NM	NM	NM	NM	-	2594.57	2590.52	4.05	-	2594.57	Max 6/98-2/08
MW-12	2526.93	2529.63	UK	UK	NM	NM	NM	NM	NM	2517.33	2518.09	2517.43	**2518.63**	2517.51	2517.73	2517.03	2516.86	2516.89	2516.93	2517.20	2517.40	2517.40	2518.63	2516.86	1.77	1.23	2518.63	Max 6/98-2/08
MW-13S	2529.67	2532.20	UK	UK	NM	NM	NM	NM	NM	2519.53	2520.35	2519.88	**2520.50**	2519.41	2519.82	2518.68	2518.44	2518.36	2518.34	2518.57	2518.84	2518.84	2520.50	2518.34	2.16	1.66	2520.50	Max 6/98-2/08
MW-13D	2528.11	2530.86	UK	UK	NM	NM	NM	NM	NM	2518.22	2519.03	2518.55	**2519.10**	2518.23	2518.50	2517.64	2517.46	2517.34	2517.29	2517.53	2517.76	2517.76	2519.10	2517.29	1.81	1.34	2519.10	Max 6/98-2/08
MW-14	UK	2711.69	UK	UK	NM	NM	NM	NM	NM	2612.36	2613.19	**2613.51**	2612.41	2611.74	2610.50	NM	NM	NM	NM	NM	NM	-	2613.51	2610.50	3.01	-	2613.51	Max 6/98-2/08
MW-15	UK	2547.41	UK	UK	NM	NM	NM	NM	NM	2538.49	2538.70	2538.39	**2538.71**	2538.33	2538.33	NM	NM	NM	NM	NM	NM	-	2538.71	2538.33	0.38	-	2538.71	Max 6/98-2/08
P-4	2571.25	2573.14	UK	UK	**2503.85**	**2504.56**	2504.34	**2504.73**	2503.73	NM	NM	NM	NM	NM	NM	2496.95	2496.69	2496.44	2496.33	2496.06	2495.85	2496.95	2504.73	2495.85	8.88	7.78	2504.73	Max 6/98-2/08
P-5	2485.02	2487.78	UK	UK	**2462.73**	2461.36	2460.35	2459.62	2459.15	NM	NM	NM	NM	NM	NM	2456.34	2455.93	2455.73	2455.67	2456.55	2458.26	2458.26	2462.73	2455.67	7.06	4.47	2462.73	Max 6/98-2/08
P-6	2594.13	2597.74	UK	UK	2538.68	**2538.83**	2538.71	2538.57	2538.23	NM	NM	NM	NM	NM	NM	2536.05	2535.87	2535.59	2535.50	2535.27	2535.05	2536.05	2538.83	2535.05	3.78	2.78	2538.83	Max 6/98-2/08
																									AVG (Avg Diff)	3.61		

			DEPTH TO WATER BELOW GROUND SURFACE																		
					1998					2004	2005		2006		2007					2008	
WELL	GROUND ELEV.	TOC ELEV.	TOB	24-Hr	6/9/98	7/7/98	8/17/98	9/25/98	10/27/98	10/21/04	4/18/05	10/13/05	4/25/06	10/20/06	4/26/07	9/20/07	10/25/07	11/30/07	12/14/07	1/16/08	2/14/08
BLE-1	2574.23	2577.77	48.00	42.50	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	43.11	43.48	43.87	44.01	44.38	44.59
BLE-2	2525.68	2529.57	17.10	12.45	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	12.71	12.61	12.64	12.58	12.26	11.92
BLE-3	2519.77	2523.43	19.50	18.44	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	18.82	18.60	18.52	18.43	18.19	17.90
BLE-5	2497.10	2500.99	11.30	4.60	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	5.12	4.46	4.62	4.29	3.99	3.77
BLE-6	2532.96	2536.67	44.65	44.71	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	44.72	44.80	44.49	44.42	44.19	44.03
BLE-7S	2492.12	2495.30	10.30	7.80	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	8.40	8.81	8.36	8.13	7.43	7.29
BLE-7D	2491.92	2495.70	8.30	8.40	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	7.51	7.19	7.45	7.27	6.87	6.68
BLE-9	2552.54	2556.63	42.70	43.00	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	43.26	46.26	46.81	46.94	47.15	47.43
BLE-10	2612.97	2615.73	61.50	NM	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	61.75	61.94	62.52	68.69	69.17	69.56
BLE-11	2630.61	2634.27	89.70	84.60	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	89.66	89.86	90.44	90.49	91.04	91.40
BLE-12	2620.95	2624.50	75.90	75.90	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	75.76	76.01	76.60	76.68	77.22	77.65
BLE-13	2609.39	2612.66	69.00	67.50	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	66.95	66.99	67.32	67.41	67.79	68.20
BLE-14	2610.41	2613.65	59.10	59.20	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	59.20	59.31	59.81	59.92	60.44	60.95
BLE-15	2584.11	2587.90	57.75	57.10	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	56.93	57.24	57.62	57.68	57.87	57.58
BLE-16	2614.70	2618.50	68.50	62.21	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	59.07	59.45	60.15	60.28	60.90	61.36
BLE-17	2611.46	2615.91	87.60	73.41	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	89.74	73.87	74.46	74.52	75.14	75.58
MW-1A	2517.97	2520.02	UK	UK	14.20	14.64	15.28	15.58	15.83	15.67	15.00	16.39	15.50	17.16	17.32	21.85	22.51	22.91	23.03	22.64	21.90
MW-2	2494.43	2496.71	UK	UK	27.08	27.52	28.29	28.82	28.90	27.78	26.65	28.43	26.96	28.59	27.75	29.07	29.17	29.28	29.23	28.99	28.33
MW-2D	2494.69	2496.89	UK	UK	NM	NM	NM	NM	NM	27.80	26.63	28.43	26.98	28.66	27.80	29.14	29.30	29.34	29.35	29.05	28.44
MW-3	2435.06	2437.28	UK	UK	Dry	Dry	Dry	Dry	Dry	Dry	Dry	Dry	Dry	Dry	Dry	Dry	Dry	Dry	Dry	Dry	Dry
MW-3D	2434.17	2436.94	UK	UK	NM	NM	NM	NM	NM	13.55	12.80	14.04	13.00	13.94	13.93	14.59	14.72	14.87	14.86	14.60	14.28
MW-4A	2496.19	2498.54	UK	UK	36.75	32.73	33.39	39.84	35.93	44.23	44.78	45.42	47.22	48.42	48.73	48.05	48.05	47.92	48.00	48.12	48.11
MW-5A	2502.29	2503.58	UK	UK	5.07	5.73	6.01	6.34	6.41	4.86	3.81	4.80	3.01	NM	4.21	5.49	5.17	5.23	5.15	4.95	4.70
MW-5D	2502.18	2502.90	UK	UK	5.94	6.33	6.49	6.66	6.68	5.93	5.26	5.88	4.60	NM	5.46	6.36	6.04	5.87	5.80	5.63	5.43
MW-8	2474.84	2477.33	UK	UK	NM	NM	NM	NM	NM	28.04	27.21	28.54	27.47	28.88	28.25	29.54	29.84	30.07	30.05	29.79	29.21
MW-9	UK	2430.15	UK	UK	NM	NM	NM	NM	NM	UK	UK	UK	UK	UK	UK	NM	NM	NM	NM	NM	NM
MW-11S	UK	2674.58	UK	UK	NM	NM	NM	NM	NM	UK	UK	UK	UK	UK	UK	NM	NM	NM	NM	NM	NM
MW-11D	2672.01	2674.89	UK	UK	NM	NM	NM	NM	NM	81.49	80.27	78.49	77.71	77.44	78.66	NM	NM	NM	NM	NM	NM
MW-12	2526.93	2529.63	UK	UK	NM	NM	NM	NM	NM	9.60	8.84	9.50	8.30	9.42	9.20	9.90	10.07	10.04	10.00	9.73	9.53
MW-13S	2529.67	2532.20	UK	UK	NM	NM	NM	NM	NM	10.14	9.32	9.79	9.17	10.26	9.85	10.99	11.23	11.31	11.33	11.10	10.83
MW-13D	2528.11	2530.86	UK	UK	NM	NM	NM	NM	NM	9.89	9.08	9.56	9.01	9.88	9.61	10.47	10.65	10.77	10.82	10.58	10.35
MW-14	UK	2711.69	UK	UK	NM	NM	NM	NM	NM	UK	UK	UK	UK	UK	UK	NM	NM	NM	NM	NM	NM
MW-15	UK	2547.41	UK	UK	NM	NM	NM	NM	NM	UK	UK	UK	UK	UK	UK	NM	NM	NM	NM	NM	NM
P-4	2571.25	2573.14	UK	UK	67.40	66.69	66.91	66.52	67.52	NM	NM	NM	NM	NM	NM	74.30	74.56	74.81	74.92	75.19	75.40
P-5	2485.02	2487.78	UK	UK	22.29	23.66	24.67	25.40	25.87	NM	NM	NM	NM	NM	NM	28.68	29.09	29.29	29.35	28.47	26.76
P-6	2594.13	2597.74	UK	UK	55.45	55.30	55.42	55.56	55.90	NM	NM	NM	NM	NM	NM	58.08	58.26	58.54	58.63	58.86	59.08

Notes:

1. TOB = *Time Of Boring*
2. TOC = *Top Of Casing*
3. NP = *Not Present* at time of measurement
4. NM = *Not Measured*
5. UK= *unknown*
6. Measurements are in feet; elevations are relative to mean sea level.
7. Bold elevations represent highest observed elevations between 6/9/98 to 2/14/08.

Prepared By: IAI
Checked By: AWA

TABLE 4

SUMMARY OF IN-SITU HYDRAULIC CONDUCTIVITY TESTING -SLUG TEST RESULTS
White Oak MSW Landfill - Phase 3 & 4 DHR
Haywood County, North Carolina
BLE Project Number J07-1957-02

				Hydraulic Conductivity (K)		
Well	**Method**	**Data Type**	**Aquifer Unit**	**ft/min**	**cm/sec**	**ft/day**
BLE-3	Bouwer-Rice	Falling Head	Deep Residuum	9.2E-04	4.7E-04	1.3
BLE-7S	Bouwer-Rice	Falling Head	Deep Residuum	1.7E-04	8.6E-05	0.24
BLE-7D	Bouwer-Rice	Falling Head	Bedrock	3.9E-04	2.0E-04	0.56
BLE-9	Bouwer-Rice	Rising Head	Bedrock	3.7E-06	1.9E-06	0.0053
BLE-11	Bouwer-Rice	Falling Head	Deep Residuum	2.2E-05	1.1E-05	0.032
BLE-14	Bouwer-Rice	Falling Head	Partially Weathered Rock	5.2E-05	2.6E-05	0.074
Deep Residuum	Maximum Hydraulic Conductivity			9.2E-04	4.7E-04	1.3
	Geometric Mean Hydraulic Conductivity			1.5E-04	7.6E-05	0.22
	Minimum Hydraulic Conductivity			2.2E-05	1.1E-05	0.032
Partially Weathered Rock	Hydraulic Conductivity			5.2E-05	2.6E-05	0.074
Bedrock	Maximum Hydraulic Conductivity			3.9E-04	2.0E-04	0.56
	Geometric Mean Hydraulic Conductivity			3.8E-05	1.9E-05	0.054
	Minimum Hydraulic Conductivity			3.7E-06	1.9E-06	0.0053
All Units	Maximum Hydraulic Conductivity			9.2E-04	4.7E-04	1.3
	Geometric Mean Hydraulic Conductivity			7.9E-05	4.0E-05	0.11
	Minimum Hydraulic Conductivity			3.7E-06	1.9E-06	0.0053

Notes:
1. K = Hydraulic Conductivity
2. The data was reduced and the hydraulic conductivities calculated using SuperSlug (version 3.0)

TABLE 5

SUMMARY OF LABORATORY RESULTS - SPLIT SPOON & SHELBY TUBE SAMPLES
White Oak MSW Landfill - Phase 3 & 4 DHR
Haywood County, North Carolina
BLE Project Number J07-1957-02

						Triaxial Shear				Consolidation												
	Split-Spoon	Shelby Tube		Hydraulic Cond.	Nat. Moisture	Cohesion (ksf)		Φ (degree)		Precon. Press.	Virgin Slope	Void Ratio	Effective	Total	Atterberg Limits			Grain Size (% by wt)				
Boring	Depth (ft)	Depth (ft)	Soil Unit	(cm/sec)	Content (%)	Total	Effective	Total	Effective	Pc (ksf)	at 16ksf Cc	(eo)	Porosity (%)	Porosity (%)	LL	PL	PI	Gravel	Sand	Silt	Clay	USCS
BLE-1	-	3.5 - 5.5	upper residuum	2.6E-04	32.1%	-	-	-	-	-	-	-	20.2%	47.9%	59	46	13	0.0%	36.6%	57.2%	6.2%	MH
BLE-1	63.5 - 65.0	-	PWR	-	12.6%	-	-	-	-	-	-	-	30.5%	*49.0%*	29	26	3	0.8%	70.8%	26.8%	1.6%	SM
BLE-2	23.5 - 25.0	-	deep residuum	-	24.8%	-	-	-	-	-	-	-	32.0%	*47.0%*	42	38	4	24.2%	54.7%	19.0%	2.1%	SM
BLE-3	-	6.0 - 8.0	deep residuum	1.8E-04	20.4%	-	-	-	-	-	-	-	10.5%	39.4%	42	29	13	4.6%	46.1%	27.7%	21.6%	SM
BLE-3	8.5 -10.0	-	deep residuum	-	15.4%	-	-	-	-	-	-	-	18.5%	*47.5%*	46	34	12	2.9%	60.8%	23.4%	12.9%	SM
BLE-3	-	23.5 - 25.0	deep residuum	3.5E-05	31.6%	-	-	-	-	-	-	-	24.0%	46.4%	44	35	9	0.0%	55.2%	38.2%	6.6%	SM
BLE-6	6.0 - 7.5	-	deep residuum	-	14.4%	-	-	-	-	-	-	-	26.0%	*47.0%*	34	29	5	15.5%	56.9%	20.7%	6.9%	SM
BLE-7	-	1.0 - 3.0	upper residuum	1.1E-05	35.4%	-	-	-	-	-	-	-	16.5%	50.8%	56	43	13	0.0%	43.8%	42.0%	14.2%	MH
BLE-7	13.5 - 15.0	-	deep residuum	-	27.4%	-	-	-	-	-	-	-	28.5%	*49.5%*	42	36	6	0.1%	67.8%	28.8%	3.3%	SM
BLE-9	-	13.5 - 15.5	deep residuum	2.2E-04	23.8%	-	-	-	-	-	-	-	25.2%	50.2%	37	33	4	0.0%	60.4%	33.0%	6.6%	SM
BLE-10	-	1.0 - 3.0	deep residuum	5.4E-05	20.3%	-	-	-	-	8.06	0.12	0.760	27.5%	45.7%	55	49	6	0.0%	65.6%	30.3%	4.1%	SM
BLE-10	-	9.5 - 11.5	deep residuum	2.4E-05	24.2%	-	-	-	-	-	-	-	21.0%	46.4%	45	38	7	0.0%	42.3%	51.3%	6.4%	ML
BLE-11	6.0 - 7.5	-	upper residuum	-	20.2%	-	-	-	-	-	-	-	21.0%	*52.5%*	52	38	14	0.0%	47.8%	43.6%	8.6%	MH
BLE-13	-	23.5 - 25.0	deep residuum	6.9E-05	21.2%	-	-	-	-	-	-	-	22.0%	44.9%	42	35	7	0.0%	41.2%	55.8%	3.0%	ML
BLE-13	43.5 - 45.0	-	deep residuum	-	15.5%	-	-	-	-	-	-	-	23.0%	*48.0%*	45	34	11	9.2%	54.9%	26.4%	9.5%	SM
BLE-15	8.5 - 10.0	-	upper residuum	-	27.9%	-	-	-	-	-	-	-	3.5%	*51.0%*	52	34	18	0.4%	26.6%	35.8%	37.2%	MH
BLE-16	73.5 - 75.0	-	deep residuum	-	22.2%	-	-	-	-	-	-	-	22.5%	*52.5%*	37	32	5	0.4%	51.3%	41.6%	6.7%	SM
BLE-17	98.5 - 100.0	-	PWR	-	13.7%	-	-	-	-	-	-	-	23.5%	*49.5%*	30	26	4	1.3%	58.8%	31.8%	8.1%	SM
BLE-9/-10	-	13.5-15.0/9.5-11.5	deep residuum	-	-	0.063	0.064	18.80	36.73	-	-	-	-	-	-	-	-	-	-	-	-	SM

Notes:
1. Effective Porosity (Specific Yield) is based on grain size analyses and Figure 4.11 (Fetter, 1994)
2. Total Porosity values in *italic case* are based on grain size analyses.
3. USCS = Unified Soil Classification System. Refer to Appendix C for a description of the abbreviations.

TABLE 6

SUMMARY OF LABORATORY RESULTS - REMOLDED BAG SAMPLES

White Oak MSW Landfill - Phase 3 & 4 DHR
Haywood County, North Carolina
BLE Project Number J07-1957-02

				Standard Proctor		Remolded Permeability Conditions						Atterberg Limits			Grain Size (% by wt)				
Boring	Bag Sample Depth (ft)	Soil Unit	Natual Moisure	Opt. Moisture Content (%)	Max. Dry Density (pcf)	Effective Stress(PSI)	Moisture Content (%)	% Wet of Opt.	Dry Density (pcf)	% of MDD	Hydraulic Cond. (cm/sec)	LL	PL	PI	Gravel	Sand	Silt	Clay	USCS
BLE-11	15.5 - 18.0	deep residuum	-	22.4%	97.9	15	28.0%	5.6%	93.0	95.0%	2.9E-07	59	37	22	0.4%	32.9%	37.5%	29.2%	MH
BLE-14	16.0 - 18.0	upper residuum	-	23.8%	94.7	15	31.0%	7.2%	90.1	95.1%	4.8E-07	63	40	23	0.0%	24.0%	46.7%	29.3%	MH
BLE-15	1.0 - 8.0	upper residuum	-	25.7%	94.3	15	31.1%	5.4%	89.6	95.0%	8.8E-08	63	35	28	0.5%	15.5%	25.6%	58.4%	MH

Notes:

1. USCS = Unified Soil Classification System. Refer to Appendix C for a description of the abbreviations.

TABLE 7

INTERSTITIAL GROUNDWATER FLOW VELOCITY CALCULATIONS
White Oak MSW Landfill - Phase 3 & 4 DHR
Haywood County, North Carolina
BLE Project Number J07-1957-02

Geologic Unit	Velocity Calculation	Hydraulic Conductivity (K) (feet per day)	Hydraulic Gradient (i) (unitless)	Effective Porosity (n_e) (unitless)	Groundwater Flow Velocity (V) (feet per day)
Deep Residuum	Max K, Max n_e, & Min i	1.3	0.0435	0.320	**0.18**
	Geometric Mean K, and Average n_e & i	0.22	0.133	0.234	**0.12**
	Max K, and Average n_e & i	1.3	0.133	0.234	**0.74**
	Min K, Min n_e, & Max i	0.032	0.222	0.105	**0.068**
Partially Weathered Rock	K, Average n_e & i	0.074	0.133	0.270	**0.036**
	K, Max n_e, & Min i	0.074	0.0435	0.305	**0.011**
	K, Min n_e, & Max i	0.074	0.222	0.235	**0.070**
Bedrock	Max K, Max n_e, & Min i	0.56	0.0435	0.100	**0.24**
	Geometric Mean K, and Average n_e & i	0.054	0.133	0.075	**0.096**
	Max K, and Average n_e & i	0.56	0.133	0.075	**0.99**
	Min K, Min n_e, & Max i	0.0053	0.222	0.050	**0.024**

Notes:

1. Groundwater velocity derived from $V = Ki/n_e$ where:
   K = hydraulic conductivity, i = hydraulic gradient, and n_e = effective porosity.
2. The hydraulic conductivity values in the Deep Residuum, Partially Weathered Rock, and Bedrock are from slug tests (Table 4).
3. Effective porosity values in the Deep Residuum and Partially Weathered Rock are from soil laboratory tests (Table 5).
4. Effective porosity values in the Bedrock are from published values (5 to 10 percent) (Kruseman & deRidder, 1989).
5. Hydraulic gradient information is from the February 14, 2008 Water Table Contour Map (Figure 6).
6. The high velocity hydraulic gradient (0.222 ft/ft) is in the northern portion of Phase 4. (maximum calculated hydraulic gradient of 0.222 [180 feet between the 2490 and 2530 contours]).
7. The low velocity hydraulic gradient (0.0435 ft/ft) is in the central portion of Phase 3. (minimum calculated hydraulic gradient of 0.0435 [230 feet between the 2490 and 2500 contours]).
8. Upper Residuum is typically above the water table, and is therefore not used in the calculations on this Table.

TABLE 8

SUMMARY OF HYDROGEOLOGIC CHARACTERISTICS OF GEOLOGIC UNITS

White Oak MSW Landfill - Phase 3 & 4 DHR
Haywood County, North Carolina
BLE Project Number J07-1957-02

Geologic Unit	USCS	Grain Size				Total Porosity				Effective Porosity				Hydraulic Conductivity (cm/sec)		
		gravel	sand	silt	clay	max	min	average	geomean	max	min	average	geomean	max	min	geomean
Upper Residual Soil	CL, ML, MH	0.1%	38.7%	44.7%	16.6%	52.5%	47.9%	50.5%	50.5%	21.0%	3.5%	15.3%	12.5%	2.6E-04	1.1E-05	5.3E-05
Deep Residual Soil	SM, ML	4.7%	54.8%	33.0%	7.5%	52.5%	39.4%	47.0%	46.9%	32.0%	10.5%	23.4%	22.7%	4.7E-04	1.1E-05	7.6E-05
Partially Weathered Rock	SM	1.1%	64.8%	29.3%	4.9%	49.5%	49.0%	49.3%	49.2%	30.5%	23.5%	27.0%	26.8%	2.6E-05	-	-
Bedrock	Biotite-Quartz-Feldspar Gneiss	-	-	-	-	10.0%	5.0%	7.5%	7.1%	10.0%	5.0%	7.5%	7.1%	2.0E-04	1.9E-06	1.9E-05

Notes:

1. Values are summarized from Table 4 (Summary of Slug Test Results) and Table 5 (Summary of Laboratory Results).
   The hydraulic conductivity values for the Deep Residuum, Partially Weathered Rock, and Bedrock are from slug testing, and from soil laboratory testing in the Upper Residuum.
2. Grain size values are averages.
3. "geomean" is the geometric mean.
4. Values of porosity in Bedrock are from published values (Kruseman & deRidder, 1989).

TABLE 9

VERTICAL HYDRAULIC GRADIENTS AND FLOW RATES
White Oak MSW Landfill - Phase 3 & 4 DHR
Haywood County, North Carolina
BLE Project Number J07-1957-02

Well Pairs	Ground Elev. (ft)	TOC Elev. (ft)	Ground Elevation Difference (ft)	Horizontal Distance Between Wells (ft)	Midpoint Screen Elev. (ft)	Vertical Separation Between Screens Midpoints (ft)	2/14/2008		Vertical Hydraulic Gradient (i)	Geometric Mean Hydraulic K(ft/day)	Geometric Mean Effective Porosity (n)	Vertical Flow Velocity (ft/day)	Direction
							Water Elev. (ft)	Head Difference (ft)					
MW-5A	2502.29	2503.58	0.11	7.6	2490.30	18.80	2497.59	0.84	0.045	0.1144	0.1159	0.044	Recharge
MW-5D	2502.18	2502.90			2471.50		2496.75						
BLE-7S	2492.12	2495.30	0.20	7.4	2475.23	37.93	2484.86	-0.40	-0.011	0.1144	0.1159	-0.010	Discharge
BLE-7D	2491.92	2495.70			2437.30		2485.26						

Notes:
1. Water level elevations measured on 2/14/2008.
2. Hydraulic conductivity values are from Table 4 and effective porosity values are estimated from averages or similar soil types on Table 8.
3. Negitive (-) gradients and velocities indicate an upward flow direction.
4. Positive (+) gradients and velocities indicate a downward flow direction.

FIGURES



REFERENCE:
USGS TOPOGRAPHIC MAP, 7.5 MINUTE SERIES,
COVE CREEK GAP AND FINES CREEK, N.C. QUADRANGLES, 1967.

DRAWN: AEH	DATE: 07-11-08	BLE inc. BUNNELL-LAMMONS ENGINEERING, INC. 6004 PONDERS COURT GREENVILLE, SOUTH CAROLINA 29615 PHONE: (864)288-1265 FAX: (864)288-4430	FIGURE 1
CHECKED: MSP	CAD: HCWOLF-02 SLM		
APPROVED:	JOB NO: J07-1957-02		

SITE LOCATION MAP
WHITE OAK LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA

GENERALIZED GEOLOGIC MAP OF NORTH CAROLINA



Sedimentary and Metamorphic Rocks

Late Proterozoic to Early Paleozoic

- Sedimentary rocks - sandstone, dolomite, shale and siltstone.
- Metasedimentary and metavolcanic rocks of the Kings Mountain belt - schist, phyllite, marble, metavolcanic rock, quartzite and gneiss.
- Metamorphic rocks of the Inner Piedmont, Milton belt and Raleigh belt - gneiss, schist and amphibolite.
- Metavolcanic rocks of the Carolina slate belt and eastern slate belt - felsic metavolcanic rock with mafic and intermediate volcanic rock.
- Metasedimentary rocks of the Carolina slate belt and eastern slate belt - metamudstone, argillite and epiclastic rock.

Late Proterozoic

- Clastic and carbonate metasedimentary rocks of the Murphy belt - schist, phyllite, quartzite, marble, slate and metasiltstone.
- Brevard fault zone - schist, marble and phyllonite.
- Clastic metasedimentary and metavolcanic rocks of the Ocoee Supergroup, Grandfather Mountain Formation, Mount Rogers Formation and quartzite of the Sauratown Mountains anticlinorium - slate, metasiltstone, schist, metagraywacke, calc-silicate granofels, quartzite and felsic metavolcanic rock.
- Clastic metasedimentary rock and mafic and felsic metavolcanic rock of the Ashe Metamorphic Suite, Tallulah Falls Formation and Alligator Back Formation - gneiss, schist, metagraywacke, amphibolite and calc-silicate granofels.

Middle Proterozoic

- Felsic gneiss derived from sedimentary and igneous rocks in the northern outcrop area; biotite gneiss in the southern outcrop area; locally migmatitic and mylonitic. Locally and variably interlayered with amphibolite, calc-silicate granofels and rare marble. Intruded by Late Proterozoic mafic and felsic plutons.

Intrusive Rocks

Middle Paleozoic to Late Paleozoic

- Granitic rocks - unfoliated to weakly foliated.
- Syenite - Concord ring dike.

Late Proterozoic to Middle Paleozoic

- Metamorphosed gabbro and diorite - foliated to weakly foliated.
- Metamorphosed granitic rocks - foliated to weakly foliated; locally migmatitic.
- Henderson Gneiss - uneven-grained monzonitic to granodioritic.
- Meta-ultramafic rocks.

Sedimentary Rocks

Quaternary

- Surficial deposits, undivided - sand, clay and gravel. (Shown only below 25 feet of elevation.)

Tertiary

- Pinehurst Formation - unconsolidated sand.
- Terrace deposits and upland sediment - gravel, clayey sand and sand.
- Waccamaw Formation - fossiliferous sand with silt and clay.
- Yorktown Formation and Duplin Formation, undivided -
  Yorktown Formation- fossiliferous clay and sand.
  Duplin Formation- shelly sand, sandy marl and limestone.
- Belgrade Formation, undivided -
  Pollocksville Member- oyster-shell mounds in sand matrix.
  Haywood Landing Member- fossiliferous clayey sand.
- River Bend Formation - sandy, molluscan-mold limestone.
- Castle Hayne Formation -
  Spring Garden Member- molluscan-mold limestone.
- Comfort Member and New Hanover Member, undivided -
  Comfort Member - limestone with bryozoan and echinoid skeletons.
  New Hanover Member - phosphate-pebble conglomerate.
- Beaufort Formation, undivided -
  Unnamed upper member - glauconitic, fossiliferous sand and silty clay.
  Jericho Run Member - siliceous mudstone with sandstone lenses.

Cretaceous

- Peedee Formation - marine sand, clayey sand and clay.
- Black Creek Formation - lignitic sand and clay.
- Middendorf Formation - sand, sandstone and clay.
- Cape Fear Formation - sandstone and sandy mudstone.

Triassic

- Dan River Group, undivided -
  Stoneville Formation - conglomerate, sandstone and mudstone.
  Cow Branch Formation - mudstone.
  Pine Hall Formation - sandstone, mudstone and conglomerate.
- Chatham Group, undivided -
  Sanford Formation - conglomerate, sandstone and mudstone.
  Cumnock Formation - sandstone and mudstone.
  Pekin Formation - conglomerate, sandstone and mudstone.

50 Miles

GEOLOGICAL SURVEY N.C. 1823

1991

Reprinted, 1996

FIGURE 2

Physiography

North Carolina can be divided into three physiographic provinces, the Coastal Plain, the Piedmont and the Blue Ridge. Each province is characterized by particular types of landforms.

The Coastal Plain is characterized by flat land to gently rolling hills and valleys. Elevations range from sea level near the coast to about 600 feet in the Sand Hills of the southern Inner Coastal Plain.

The Piedmont Province lies between the Coastal Plain and the Blue Ridge Mountains. The Piedmont occupies about 45 percent of the area of the state. Along the border between the Piedmont and the Coastal Plain, elevations range from 300 to 600 feet above sea level. To the west, elevations gradually rise to about 1,500 feet above sea level at the foot of the Blue Ridge. The Piedmont is characterized by gently rolling, well rounded hills and long low ridges with a few hundred feet of elevation difference between the hills and valleys. The Piedmont includes some relatively low mountains including the South Mountains and the Uwharrie Mountains.

The Blue Ridge is a deeply dissected mountainous area of numerous steep mountain ridges, intermontane basins and trench valleys that intersect at all angles and give the area its rugged mountain character. The Blue Ridge contains the highest elevations and the most rugged topography in the Appalachian Mountain system of eastern North America. The North Carolina portion of the Blue Ridge is about 200 hundred miles long and ranges from 15 to 55 miles wide. It contains an area of about 6,000 square miles, or about 10 percent of the area of the state.

Within North Carolina, 43 peaks exceed 6,000 feet in elevation and 82 peaks are between 5,000 and 6,000 feet. On the west, the Great Smoky Mountains is the dominant range with several peaks that reach more than 6000 feet. On the eastern side of the North Carolina Blue Ridge, the highest range is the Black Mountains which extend for some 15 miles and contain a dozen peaks that exceed 6,000 feet in elevation. This group includes Mount Mitchell. At an elevation of 6,684 feet, it is the highest peak of eastern North America. Other prominent ranges from northeast to southwest are the Pisgah Mountains, Newfound Mountains, Balsam Mountains, Cowee Mountains, Nantahala Mountains, Snowbird Mountains and the Valley River Mountains.

Geology

Three major classes of rocks common to North Carolina are igneous, metamorphic and sedimentary. North Carolina has a long and complex geologic history. Although much remains to be learned, detailed geologic studies provide a general understanding of regional geological relationships. The state is best described in terms of geological belts; that is, areas with similar rock types and geologic history.

Blue Ridge Belt: This mountainous region is composed of rocks from over one billion to about one-half billion years old. This complex mixture of igneous, sedimentary and metamorphic rock has repeatedly been squeezed, fractured, faulted and twisted into folds. The Blue Ridge belt is well known for its deposits of feldspar, mica and quartz–basic materials used in the ceramic, paint and electronic industries. Olivine is mined for use as refractory material and foundry molding sand.

Inner Piedmont Belt: The Inner Piedmont belt is the most intensely deformed and metamorphosed segment of the Piedmont. The metamorphic rocks range from 500 to 750 million years in age. They include gneiss and schist that have been intruded by younger granitic rocks. The northeast-trending Brevard fault zone forms much of the boundary between the Blue Ridge and Inner Piedmont belts. Although this zone of strongly deformed rocks is one of the major structural features in the southern Appalachians, its origin is poorly understood. Crushed stone for road aggregate and building construction is the principal commodity produced.

Kings Mountain Belt: The belt consists of moderately deformed and metamorphosed volcanic and sedimentary rocks. The rocks are about 400-500 million yearls old. Lithium deposits here provide raw materials for chemical compounds, ceramics, glass, greases, batteries and TV glass.

Milton Belt: This belt consists of gneiss, schist and metamorphosed intrusive rocks. The principal mineral resource is crushed stone for road aggregate and for building construction.

Charlotte Belt: The belt consists mostly of igneous rocks such as granite, diorite and gabbro. These are 300-500 million years old. The igneous rocks are good sources for crushed and dimension stone for road aggregate and buildings.

Carolina Slate Belt: This belt consists of heated and deformed volcanic and sedimentary rocks. It was the site of a series of oceanic volcanic islands about 550-650 million years ago. This belt is known for its numerous abandoned gold mines and prospects. North Carolina led the nation in gold production before the California Gold Rush of 1849. In recent decades, only minor gold mining has taken place, but mining companies continue to show interest in the area. Mineral production is crushed stone for road aggregate and pyrophyllite for refractories, ceramics, filler, paint and insecticide carriers.

Triassic Basins: The basins are filled with sedimentary rocks that formed about 200-190 million years ago. Streams carried mud, silt, sand and gravel from adjacent highlands into rift valleys similar to those of Africa today. The mudstones are mined and processed to make brick, sewer pipe, structural tile and drain tile.

Raleigh Belt: The Raleigh belt contains granite, gneiss and schist. In the 19th century, there were a number of small building stone quarries in this region, but today the main mineral product is crushed stone for construction and road aggregate.

Eastern Slate Belt: This belt contains slightly metamorphosed volcanic and sedimentary rocks similar to those of the Carolina slate belt. The rocks are poorly exposed and partially covered by Coastal Plain sediments. The metamorphic rocks, 500-600 million years old, are intruded by younger, approximately 300 million year old, granitic bodies. Gold was once mined in the belt, and small occurrences of molybdenite, an ore of molybdenum, have been prospected here. Crushed stone, clay, sand and gravel are currently mined in this belt.

Coastal Plain: The Coastal Plain is a wedge of mostly marine sedimentary rocks that gradually thickens to the east. The Coastal Plain is the largest geologic belt in the state, covering about 45 percent of the land area. The most common sediment types are sand and clay, although a significant amount of limestone occurs in the southern part of the Coastal Plain. In the Coastal Plain, geology is best understood from studying data gathered from well drilling. The state's most important mineral resource in terms of dollar value is phosphate, an important fertilizer component, mined near Aurora, Beaufort County. Industrial sand for making container and flat glass and ferrosilicon and used for filtration and sandblasting is mined in the Sand Hills area.

Mineral Industry

North Carolina has important deposits of many minerals and annually leads the nation in the production of feldspar, lithium minerals, scrap mica, olivine and pyrophyllite. The state ranks second in phosphate rock production and ranks in the top five in clay and crushed granite production. North Carolina does not produce significant quantities of metallic minerals.



GEOLOGIC TIME SCALE FOR NORTH CAROLINA

EON	ERA	PERIOD	EPOCH	GEOLOGIC EVENTS IN NORTH CAROLINA	AGE*
PHANEROZOIC	CENOZOIC	Quaternary	Recent	Deposition of sediments in Coastal Plain. Erosion of Piedmont and Appalachian Mountains to their present rugged features.	
			Pleistocene		1.7
		Tertiary	Pliocene		5
			Miocene	Phosphate deposited in eastern North Carolina (Beaufort and Pamlico Counties).	24
			Oligocene	Limestone deposited in Coastal Plain. Weathering and erosion continue in Piedmont and Mountains.	
			Eocene		
			Paleocene		66
	MESOZOIC	Cretaceous	Late	Deposition of estuarine and marine sediments in the Coastal Plain. Continued erosion of the Piedmont and Mountains.	
			Early	Sediments deposited in northern half of the Coastal Plain. Cape Fear Arch begins to develop. Piedmont and Mountains eroded.	138
		Jurassic	Late	Marine sediments deposited on outer continental shelf. Piedmont and mountains eroded.	
			Middle	Weathering and erosion of the Blue Ridge and the Piedmont areas. Emplacement of diabase dikes and sheets.	
			Early		205
		Triassic	Late	Faulting and rifting create Deep River, Dan River, and Davie County basins. Basins fill with continental clastic sediments known as "red beds".	
			Middle	Formation of the Atlantic Ocean as North America and Africa drifted apart. Weathering and erosion of Piedmont and Mountains.	
			Early		240
	PALEOZOIC	Permian		Final collision of North America and Africa. Thrust faulting in west; deformation in eastern Piedmont.	290
		Pennsylvanian		Time of uplift and erosion.	330
		Mississippian		Time of uplift and erosion.	360
		Devonian		Emplacement of lithium, mica, and feldspar-rich pegmatites, primarily in the Kings Mountain and Spruce Pine districts. Metamorphism of Carolina slate belt. Period of erosion.	410
		Silurian		Period of uplift and erosion.	435
		Ordovician		Continental collision and beginning of mountain building process--faulting, folding, and metamorphism of pre-existing rocks.	500
		Cambrian		Sandstone, shale, and limestone deposited in the mountain area. Continued deposition of Carolina slate belt rocks. Gold deposits of the slate belt form.	570
PROTEROZOIC		Late		Sedimentary and volcanic rocks deposited in the mountains and Piedmont. Local intrusions of igneous rocks.	900
		Middle		Sedimentary, volcanic, and igneous rocks formed in the Blue Ridge and metamorphosed to gneisses and schists.	1600
		Early		Oldest dated rock in North Carolina is 1,800 million years old.	2500
				Oldest known rock in U.S.- 3,600 million years old. Oldest known rocks in world- 3,850 million years old. Formation of the Earth- about 4,500 million years ago.	

Emplacement of igneous intrusions

* Estimated age in millions of years.

Commercial Gem- and Mineral-Collecting Sites

Garnet, moonstone, ruby and sapphire - Cowee Valley mines; 8 miles north of Franklin, Macon Co., on NC 28. Panners Creek Gem Lines; southwest of Raleigh off Old Apex Road (gems are from western N.C.)

Emerald, aquamarine and amethyst - mines in the Spruce Pine-Little Switzerland area, Mitchell County.

Emerald, hiddenite, rutile and quartz - mines at Hiddenite, Alexander Co., 15 miles northwest of Statesville off NC 90.

Gold - Reed Gold Mine State Historic Site; off NC 200, 6 miles southeast of Concord, Cabarrus County. Cotton Patch Gold Mine; off US 52, 2 miles southeast of New London.

Sapphire - Pressley Mine; off Interstate 40, near Canton, west of Asheville, Haywood Co.

The State Precious Stone - Emerald

The General Assembly of 1973 designated the emerald as the official State precious stone. Emerald is found in North Carolina near Hiddenite in Alexander County and southwest of Spruce Pine in Mitchell County. The largest single emerald crystal found in North America was found at the Rist Mine at Hiddenite in 1969. This crystal weighed 1,438 carats. The *Carolina Emerald*, a 13.14 carat, emerald-cut gem, was also found at the Rist Mine.

The State Rock - Granite

The General Assembly of 1979 designated granite as the official State rock. North Carolina is blessed with an abundance of granite. When granite is crushed, it is used as an aggregate for road and building construction. If granite has the right physical properties, it can be cut into blocks and used for monuments, curb stone and stone for building facings. The largest open-face granite quarry in the world is located at Mount Airy, North Carolina.

STATE OF NORTH CAROLINA
James B. Hunt, Jr., Governor

Department of Environment, Health and Natural Resources
Jonathan B. Howes, Secretary

Division of Land Resources
Charles H. Gardner
Director and State Geologist

North Carolina Geological Survey
P.O. Box 27687, Raleigh, N.C. 27611-7687
Telephone (919)733-2423; FAX (919)733-0900
e-mail: jeff_reid@mail.ehnr.state.nc.us
http://www.ehnr.state.nc.us/EHNR/DLR/JEFF/rock1.htm

PRINCIPAL MINERAL-PRODUCING AREAS



SYMBOLS

Clay		Li-	lithium
CS-	crushed stone	Mi-	mica
DGr-	dimension granite	Ol-	olivine
DSl-	dimenion slate	Phosphate	
Fel-	feldspar	Peat	
Gems-	gemstones	Pyr-	pyrophyllite
Kao-	kaolin	SG-	sand & gravel



LEGEND

- EXISTING GROUNDWATER MONITORING WELL
- EXISTING PIEZOMETER – APPROXIMATE LOCATIONS FROM PREVIOUS SITE PLANS
- EXISTING PIEZOMETER – SURVEYED BY McGILL ASSOCIATES IN 2007
- EXISTING PIEZOMETER AND OR BORING INSTALLED BY BUNNELL-LAMMONS ENGINEERING IN 2007
- CONTROL POINT
- EXISTING LANDFILL GAS MONITORING PROBE
- SURFACE WATER SAMPLING LOCATION

DRAWING TITLED "CONCEPTUAL SITE PLAN, OPTION 1 & 2" BY McGILL ASSOCIATES DATED JUNE 2007.

REVISIONS		
No.	DESCRIPTION	BY

DRAWN:	AEH
CHECKED:	AWA
APPROVED:	

DATE:	07-11-08
CAD FILE:	HCWOLF-02 BLP
JOB NO:	J07-1957-02

BLE INC.
BUNNELL-LAMMONS ENGINEERING, INC.
8044 POINDEXTER COURT
GREENVILLE, SOUTH CAROLINA 29615
PHONE: (864)288-1265 FAX: (864)288-6490

BORING LOCATION MAP
WHITE OAK MSW LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA

FIGURE NO. 3



LEGEND

- POTENTIOMETRIC SURFACE
- 2510 — EQUIPOTENTIAL LINES
- GROUNDWATER FLOW DIRECTION
- SCREENED INTERVAL OF PIEZOMETER OR WELL
- 2484.83 — GROUNDWATER ELEVATION (MSL) ON 02-14-08
- BT — BORING TERMINATED
- AR — AUGER REFUSAL
- FILL
- UPPER RESIDUAL SOIL; SILTY CLAY AND CLAYEY SILT (ML-CL, ML, MH)
- DEEPER RESIDUAL SOIL, SAND SILT AND SILTY SAND (ML, SM)
- PARTIALLY WEATHERED ROCK
- GRANITIC GNEISS BEDROCK
- 20 Feet / 1 Inch — 1 Inch / 100 Feet — SCALE — VERTICAL EXAGGERATION = 5X

NOTE:
TOPSOIL IS PRESENT OVER PORTIONS OF THE STUDY AREA BUT IS NOT SHOWN ON THE PROFILES.

NORTH CAROLINA LICENSED GEOLOGIST SEAL 1043 MARK S. PRESSLY
4/4/08





PROFILE LOCATION PLAN

300 150 0 300 600
APPROXIMATE SCALE IN FEET

REVISIONS		
No.	DESCRIPTION	BY

DRAWN:	IAI
CHECKED:	AWA/MSP
APPROVED:	

DATE:	07-11-08
CAD FILE:	HCWOLF-02 PROFILES
JOB NO:	J07-1957-02

BLE INC.
BUNNELL-LAMMONS ENGINEERING, INC.
6004 PONDERS COURT
GREENVILLE, SOUTH CAROLINA 29615
PHONE: (864)288-1565 FAX: (864)288-4430

GEOLOGIC PROFILES: CROSS-SECTION A-A' AND B-B'
WHITE OAK MSW LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA

FIGURE NO. 4



NORTH CAROLINA LICENSED SEAL 1043 GEOLOGIST MARK S. PRESNY

7/11/08

LEGEND

- EXISTING GROUNDWATER MONITORING WELL
- EXISTING PIEZOMETER – APPROXIMATE LOCATIONS FROM PREVIOUS SITE PLANS
- EXISTING PIEZOMETER – SURVEYED BY McGILL ASSOCIATES IN 2007
- EXISTING PIEZOMETER AND OR BORING INSTALLED BY BUNNELL-LAMMONS ENGINEERING IN 2007
- SURFACE WATER SAMPLING LOCATION
- 2414.2 — BEDROCK ELEVATION (IN FEET)
- 2420 — BEDROCK ELEVATION CONTOUR, CONTOUR INTERVAL = 10 FEET (DASHED WHERE INFERRED)

NOTE:
THIS MAP REPRESENTS THE APPROXIMATE BEDROCK SURFACE (AUGER REFUSAL). AUGER REFUSAL DEPTHS MAY REPRESENT COMPETENT BEDROCK OR POSSIBLY BOULDERS OF HARD ROCK WITHIN THE RESIDUAL SOIL AND PARTIALLY WEATHERED ROCK UNITS. THE DEPTH TO AUGER REFUSAL CAN VARY EVEN OVER SHORT HORIZONTAL DISTANCES DUE TO FRACTURES, JOINTS AND THE PRESENCE OF LESS RESISTANT ROCK TYPES. THEREFORE, THE ACTUAL DEPTH TO CONTINUOUS BEDROCK WILL VARY SOMEWHAT FROM THAT PRESENTED ON THIS FIGURE AND MAY ACTUALLY BE DEEPER THAN INDICATED.

REFERENCE:
DRAWING TITLED "CONCEPTUAL SITE PLAN, OPTION 1 & 2" BY McGILL ASSOCIATES DATED JUNE 2007.

REVISIONS		
No.	DESCRIPTION	BY

DRAWN:	IAI
CHECKED:	AWA/MSP
APPROVED:	

DATE:	07-11-08
CAD FILE:	HCWOLF-02 BEDROCK
JOB NO:	J07-1957-02

BLE INC.
BUNNELL-LAMMONS ENGINEERING, INC.
8004 POINDERS COURT
GREENVILLE, SOUTH CAROLINA 29615
PHONE: (864)288-1265 FAX: (864)288-4430

BEDROCK ELEVATION CONTOUR MAP
WHITE OAK MSW LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA

FIGURE NO. 5



NORTH CAROLINA LICENSED SEAL 1043 GEOLOGIST MARK S. PRIDDY 7/14/08

LEGEND

- EXISTING GROUNDWATER MONITORING WELL
- EXISTING PIEZOMETER – APPROXIMATE LOCATIONS FROM PREVIOUS SITE PLANS
- EXISTING PIEZOMETER – SURVEYED BY McGILL ASSOCIATES IN 2007
- EXISTING PIEZOMETER AND OR BORING INSTALLED BY BUNNELL-LAMMONS ENGINEERING IN 2007
- SURFACE WATER SAMPLING LOCATION
- 2421.33 GROUNDWATER ELEVATION (IN FEET)
- 2500 GROUNDWATER ELEVATION CONTOUR CONTOUR INTERVAL = 10 FEET
- GROUNDWATER FLOW DIRECTION

REFERENCE:
DRAWING TITLED "CONCEPTUAL SITE PLAN, OPTION 1 & 2" BY McGILL ASSOCIATES DATED JUNE 2007.

REVISIONS		
No.	DESCRIPTION	BY

DRAWN: IAI
CHECKED: AWA/MSP
APPROVED:

DATE: 07-11-08
CAD FILE: HCWOLF-02 WTM021408
JOB NO: J07-1957-02

BLE INC.
BUNNELL-LAMMONS ENGINEERING, INC.
6004 PONDERS COURT
GREENVILLE, SOUTH CAROLINA 29615
PHONE (864)288-1265 FAX (864)288-5430

WATER TABLE MAP – 2/14/2008
WHITE OAK MSW LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA

FIGURE NO. 6

PIGEON RIVER

PHASE 4

PHASE 3

EXISTING PHASE 1

EXISTING PHASE 2

EXISTING LCID

LEACHATE LAGOON

MAINTENANCE BUILDING

SCALE HOUSE AND SCALES

NORTH CAROLINA LICENSED SEAL 1043 GEOLOGIST MARK S. PRESNO 7/11/08

LEGEND

- EXISTING GROUNDWATER MONITORING WELL
- EXISTING PIEZOMETER – APPROXIMATE LOCATIONS FROM PREVIOUS SITE PLANS
- EXISTING PIEZOMETER – SURVEYED BY McGILL ASSOCIATES IN 2007
- EXISTING PIEZOMETER AND OR BORING INSTALLED BY BUNNELL-LAMMONS ENGINEERING IN 2007
- SURFACE WATER SAMPLING LOCATION
- 2496.41 GROUNDWATER ELEVATION (IN FEET)
- 2480 GROUNDWATER ELEVATION CONTOUR CONTOUR INTERVAL = 10 FEET

REFERENCE:
DRAWING TITLED "CONCEPTUAL SITE PLAN, OPTION 1 & 2" BY McGILL ASSOCIATES DATED JUNE 2007.

100 50 0 100 200
APPROXIMATE SCALE IN FEET

REVISIONS		
No.	DESCRIPTION	BY

DRAWN:	IAI
CHECKED:	AWA/MSP
APPROVED:	

DATE:	07-11-08
CAD FILE:	HCWOLF-02 SHWTM
JOB NO:	J07-1957-02

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.
6004 PONDERS COURT
GREENVILLE, SOUTH CAROLINA 29615
PHONE: (864)288-1265 FAX: (864)288-5430

SEASONAL HIGH WATER TABLE MAP – (9/20/07 – 2/14/08)

WHITE OAK MSW LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA

FIGURE NO. 7

PHASE 4

PHASE 3

EXISTING
PHASE 1

EXISTING
PHASE 2

EXISTING
LCID

LEACHATE LAGOON

MAINTENANCE BUILDING

SCALE HOUSE AND SCALES

PIGEON RIVER

NORTH CAROLINA LICENSED SEAL 1043 GEOLOGIST MARK S. PREDDY

4/4/08

BLE-10 2554.65
BLE-11 2544.36
BLE-12 2548.80
BLE-13 2546.05
BLE-14 2554.82
BLE-15 2530.79
BLE-16 2559.24
BLE-17 2541.20
BLE-1 2534.73
BLE-2 2517.37
BLE-3 2505.48
BLE-4 (BORING)
BLE-5 2496.94
BLE-6 2492.54
BLE-7S 2488.85
BLE-75 2488.44
BLE-8 (BORING)
BLE-9 2512.89
P-1 2504.73
P-2 2538.83
P-3
P-4
P-5 2462.73
P-6S
P-6D
P-7
P-8
P-9
P-10
P-11
P-12
P-13
P-14
P-15
P-16
P-17
P-18
P-1S
P-3S
P-3D
PZ-9 (DISTURBED)
PZ-4S
MW-1A 2503.77
MW-1S 2595.11
MW-1D 2594.57
MW-2 2467.78
MW-2D 2468.08
MW-3 2430.60
MW-3D 2421.37
MW-4A 2499.28
MW-4S 2463.46
MW-5 2497.58
MW-5A 2499.28
MW-8 2447.63
MW-12 2518.63
MW-13D 2519.10
MW-13S 2520.50
MW-15 2538.71
SW-1
SW-2
SW-5

2430 2440 2450 2460 2470 2480 2490 2500 2510 2520 2530 2540 2550

100 50 0 100 200
APPROXIMATE SCALE IN FEET

LEGEND

- EXISTING GROUNDWATER MONITORING WELL
- EXISTING PIEZOMETER – APPROXIMATE LOCATIONS FROM PREVIOUS SITE PLANS
- EXISTING PIEZOMETER – SURVEYED BY McGILL ASSOCIATES IN 2007
- EXISTING PIEZOMETER AND OR BORING INSTALLED BY BUNNELL-LAMMONS ENGINEERING IN 2007
- SURFACE WATER SAMPLING LOCATION
- 2421.33 GROUNDWATER ELEVATION (IN FEET) (REFER TO TABLE 3 FOR THE DATA SOURCES)
- 2440 GROUNDWATER ELEVATION CONTOUR CONTOUR INTERVAL = 10 FEET

REFERENCE:
DRAWING TITLED "CONCEPTUAL SITE PLAN, OPTION 1 & 2" BY McGILL ASSOCIATES DATED JUNE 2007.

REVISIONS		
No.	DESCRIPTION	BY

DRAWN:	IAI
CHECKED:	AWA/MSP
APPROVED:	

DATE:	07-11-08
CAD FILE:	HCWOLF-02 LTSHWTM
JOB NO:	J07-1957-02

BLE INC.
BUNNELL-LAMMONS ENGINEERING, INC.
6004 PONDERS COURT
GREENVILLE, SOUTH CAROLINA 29615
PHONE: (864)288-2365 FAX: (864)288-4430

ESTIMATION OF LONG-TERM SEASONAL HIGH WATER TABLE ELEVATION CONTOUR MAP

WHITE OAK MSW LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA

FIGURE NO. 8

APPENDICES

APPENDIX A

DRILLING AND SAMPLING PROCEDURES

APPENDIX A

DRILLING AND SAMPLING PROCEDURES

SOIL TEST BORINGS

Soil test borings were advanced by mechanically twisting a continuous flight steel auger into the soil. Soil sampling and penetration testing were performed in general accordance with ASTM D 1586. At regular intervals, soil samples were obtained with a standard 1.4-inch ID, 2-inch OD, split-tube sampler. The sampler was first seated 6 inches to penetrate any loose cuttings, and then driven an additional 12 inches with blows of a 140-pound hammer falling 30 inches. The number of hammer blows required to drive the sampler the final 12 inches was recorded and designated the "penetration resistance."

CORE DRILLING

Core drilling procedures were required to determine the character and vertical continuity of refusal materials. Refusal to soil drilling equipment may result from hard cemented soil, soft weathered rock, coarse gravel or boulders, thin rock seams, or the upper surface of solid continuous rock.

Prior to coring, a 4-inch diameter PVC pipe was seated in the refusal material and grouted into place with a cement-bentonite mixture. Refusal materials were then cored according to the ASTM D 2113 using a diamond-studded bit fastened to the end of a hollow, double-tube core barrel. The NQ and HQ sizes designate bits that obtain rock cores 1-7/8 and 2-1/2 inches in diameter. Upon completion of each drill run, the core inner barrel was brought to the surface, the core recovered was measured, and the core samples were removed and placed in boxes for storage.

The core samples were returned to our laboratory where the refusal material was identified and the percent core recovery and rock quality designation (RQD) was determined by a geologist. The percent core recovery is the ratio of the core length obtained to the length cored, expressed as a percent. The RQD is obtained by summing only those pieces of recovered core which are 4 inches or longer and are at least moderately hard, and dividing by the total length cored. The percent core recovery and the RQD are related to soundness and continuity of the refusal material. Refusal-material descriptions, recoveries and the bit size are shown on a Test Boring Record (see Appendix C).

APPENDIX B

FIELD LOGS OF BORINGS

TEST BORING REPORT

BORING NO. BLE-1

PROJECT: White Oak Landfill
CLIENT: McGill Associates
CONTRACTOR: Landprobe
EQUIPMENT USED: CME 750 with 4-1/4 inch hollow stem auger

BLE JOB NO. J07-1957-02
PAGE NO. 1 of
LOCATION:
ELEVATION:
DATE START: 7/18/07
DATE FINISH: 7/18/07
DRILLER: T. Gradwell
PREPARED BY: T. Livingston

GROUND WATER		DEPTH TO:		
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE
	TOB	48		
	24	42.5		

	CASING	SAMPLER	CORE BARREL
TYPE			
SIZE ID/OD			
HAMMER WT	XXX		XXX
HAMMER FALL	XXX		XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS
		2	SS-1		6" TOPSOIL
		5			STIFF, LT BR, YELLOW, F. SA, SILT
		6			
			UD		BR, MIC, F. SA, SI, CLAY
5					
		4	SS-2		V. STIFF, GRAY, F. SA, SI, CLAY
		10			
		10			
		4	SS-3		V. STIFF, GRAY, BR, F. SA, SILT
		7			
10		9			
		4	SS-4		V. STIFF, BR, MIC, F. SA, SILT
		12			
15		13			
		4	SS-5		V. STIFF, BR, GRAY, WHITE, MIC, F-M SA, SILT W/ROCK FRAGMENTS
		11			
20		11			

WELL: 2" PVC; GROUT

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SAMPLE ID	
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION
STICKUP =
TOP SAND = 52.8
TOP BENT. = 50.6
SCREEN = 55-65
SCREEN LENGTH = 10
END CAP = 65.0
WELL TD = 65.2

TEST BORING REPORT

White Oak Landfill — J07-1957-02 — **BORING NO.** RLE-1 0 — PAGE 2 OF

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
		9	SS-6		V. STIFF, GRAY, BR, MIC, F-M SA, SILT	2" PVC
-25		13				
		13				
		9	SS-7			GROUT
-30		13				
		14				
		9	SS-8		V. STIFF, LT BR, WHITE, MIC, F-M SA, SILT	
-35		14				
		15				
		12	SS-9		HARD TO V. STIFF, BR, BLK, MIC, F-M SA, SILT	
-40		16				
		22				
		5	SS-10			
-45		10				
		19				

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

White Oak Landfill | **J07-1957-02** | **BORING NO.** BLE-1 0 | **PAGE** 3 OF 3

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
						GROUT, 2" PVC
50		5 9 12				BENT. 50.0
						52.8
55		6 8 15				55.0
					PWR - BR & WHITE ROCK FRAGMENTS	SAND
60		7 10 12				
		50/3"			PWR - GREY & WHITE, MIC, SI, F-M SAND	65.0
65		—				65.2
					AUGER REFUSAL @ 66' BGS. GW @ 48.0' @ TOB AND 42.5' AFTER 24 HRS	66.0
70						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-2

PROJECT: White Oak Landfill
CLIENT: McGill Associates
CONTRACTOR: Landprobe
EQUIPMENT USED: CME 750 with 4-1/4 inch hollow stem auger

BLE JOB NO. J07-1957-02
PAGE NO. 1 of 2
LOCATION:
ELEVATION:
DATE START: 7/13/07
DATE FINISH: 7/13/07
DRILLER: T. Gradwell
PREPARED BY: T. Livingston

GROUND WATER		DEPTH TO:				CASING	SAMPLER	CORE BARREL
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE	TYPE			
	TOB	12.1			SIZE ID/OD			
	24 HR	12.45			HAMMER WT	XXX		XXX
					HAMMER FALL	XXX		XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
					6" TOPSOIL	
		2	SS-1		SOFT, BR, F-M SA, SI, CLAY	
		2				
		2				
		2				
- 5		2	SS-2		SOFT, YELLOW, BR, MIC, F-M SA, SILT	GROUT
		2				2" PVC
		4				
		5	SS-3		FIRM, BLK, BR, MOI, MIC, SI, F-M SAND	
		6				
		3	SS-4			
		6				
- 10		11				
		2	SS-5		SOFT, TAN, GRAY, WHITE, MOI, MIC, F-M SA, SILT	
		1				
- 15		2				
		2				
		1	SS-6		SOFT, GRAY, BR, MIC, WET, F. SA, SILT	
- 20		2				

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION
STICKUP =
TOP SAND = 26.8
TOP BENT. = 24.4
SCREEN = 29.0 - 39.0
SCREEN LENGTH = 10
END CAP = 0.2
WELL TD = 39.2

TEST BORING REPORT

White Oak Landfill — J07-1957-02 — BORING NO. BLE-2 0 — PAGE 2 OF 7

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
						GROUT
		7	SS-7		V. FIRM, BR, BLK, GRAY, MIC, SL F-M SAND	2" PVC
		7				
-25		14				BENT.
						24.4
						26.8
		2	SS-8		LOOSE, GRAY, BR, MIC, SL, F-M SAND	29.0
		2				
-30		4				
		5	SS-9		V. FIRM, MIC, GRAY, BROWN, SL, F-M SAND	SAND
		11				
-35		15				
		7	SS-10		V. FIRM, GRAY, BR, SL, F-M SAND	39.0
		12				39.2
-40		18				40.0
					BORING TERM. @ 40.0' BGS. GW @ 17.1' BTOB AND 12.45 24HR	
-45						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS: SAND = | BENTONITE = | GROUT = | WELL O.D. = | WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-3

PROJECT: White Oak Landfill
CLIENT: McGill Associates
CONTRACTOR: Landprobe
EQUIPMENT USED: CME 750 with 4-1/4 inch hollow stem auger

BLE JOB NO. J07-1957-02
PAGE NO. 1 of 2
LOCATION:
ELEVATION:
DATE START: 7/12/07
DATE FINISH: 7/12/07
DRILLER: T. Gradwell
PREPARED BY: T. Livingston

GROUND WATER		DEPTH TO:				CASING	SAMPLER	CORE BARREL
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE	TYPE			
	TOB	19.5			SIZE ID/OD			
	24	18.44			HAMMER WT	XXX		XXX
					HAMMER FALL	XXX		XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS
		2	SS-1		6" TOPSOIL FIRM, BR, SI, F-M SAND (FILL)
		2			
		4			
		2	SS-2		SOFT, LT BR, MIC, F. SA, SILT (FILL)
5		2			
		2			
		UD	UD		BR, F. SA, SI, CLAY
		2	SS-3		STIFF, BR, F-M SA, SI, CLAY
10		4			
		5			
		2	SS-4		V. FIRM, BR, BLK, MIC, SI, F-C SAND
15		10			
		15			
		3	SS-5		STIFF, RED, BR, WET, SI, F-C SAND
		4			
20		5			

WELL: Grout, 2" PVC

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION
STICKUP =
TOP SAND = 36.0
TOP BENT. = 33.0
SCREEN = 38.0 - 48.0
SCREEN LENGTH = 10
END CAP = 0.2
WELL TD = 48.2

TEST BORING REPORT

BORING NO. BLE-3 0

White Oak Landfill — J07-1957-02 — PAGE 2 OF 3

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
25			UD		LT BR, GRAY, MIC, F-M SA, SILT	
		6				
30		8			V. STIFF, GRAY, BR, WET, MIC, F-M SA, SILT	
		18				
		12				
		19				
35		19			DENSE, GRAY, WHITE, BLK, MIC, SI, F-M SAND	
		9				
		12				
40		12			V. FIRM, DK BR, MIC, F-M SAND W/ ROCK FRAGMENTS	
		13				
		19				
45		28			DENSE, GRAY, MIC, SI, F-M SAND W/ROCK FRAGMENTS	



BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

White Oak Landfill — J07-1957-02

BORING NO. BLE-3 0

PAGE 3 OF 3

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
						SAND 48.10 48.12
		12			PWR - Vr DENSE, WHITE, BR, BLK, MIC, F-M SAND	
-50		26				
		31				50.0
					BORING TERM @ 50' BGS. GW @ 19.5' @ TOB AND 18.44' AFTER 24 HRS.	
-55						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-4

PROJECT: WHITE OAK LF - HAYWOOD CO
CLIENT: MCGILL ASSO.
CONTRACTOR:
EQUIPMENT USED:

BLE JOB NO. J07-1957-07
PAGE NO. 1 of 1
LOCATION:
ELEVATION:
DATE START: 9/6/07
DATE FINISH:
DRILLER: TG-BE
PREPARED BY: T. LIVINGSTON

GROUND WATER		DEPTH TO:		
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE

	CASING	SAMPLER	CORE BARREL
TYPE	HSA	Split Spoon	XXX
SIZE ID/OD	8.25" OD	2" ID	XXX
HAMMER WT	XXX	140 lb	XXX
HAMMER FALL	XXX	30 "	XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
					TOPSOIL	
			SS-1		No Samples	
					Boring Term. @ 2.5	
			SS-2			
5						
			SS-3			
			SS-4			
10						
			SS-5			
15						
			SS-6			
20						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SAMPLE ID	
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION
STICKUP =
TOP SAND =
TOP BENT. =
SCREEN =
SCREEN LENGTH =
END CAP =
WELL TD =

TEST BORING REPORT

BORING NO. BLE-5

PROJECT:	White Oak Landfill
CLIENT:	McGill Associates
CONTRACTOR:	Landprobe
EQUIPMENT USED:	CME 750 with 4-1/4 inch hollow stem auger
BLE JOB NO.	J07-1957-02
PAGE NO.	1 of 2
LOCATION:	
ELEVATION:	
DATE START:	7/16/07
DATE FINISH:	7/16/07
DRILLER:	T. Gradwell
PREPARED BY:	T. Livingston

GROUND WATER		DEPTH TO:				CASING	SAMPLER	CORE BARREL
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE	TYPE			
	TOB	11.3			SIZE ID/OD			
	24	4.6			HAMMER WT	XXX		XXX
					HAMMER FALL	XXX		XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS
					6" TOPSOIL
		1	SS-1		FIRM, BR, SILTY, CLAY
		2			
		3			
		3	SS-2		FIRM, BR, BLK, GRAY, MOI, MIC, F. SA, CL, SILT
5		2			
		3			
		1	SS-3		FIRM, BR, MOI, MIC, F-M SA, SILT
		2			
		3			
		5	SS-4		V. FIRM, LT BR, BLK, MOI, SI, F-C SAND
10		18			
		12			
		5	SS-5		FIRM, GRAY, BR, WET, MIC, SI, F. SAND
		7			
15		8			
		50/4"	SS-6		PWR - GRAY, BR, , SI, F-M SAND W/ ROCK FRAGMENTS
20		–			
		–			

WELL: GRAVEL 2" PVC; BENT. 10.6; SAND 12.9

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION	
STICKUP =	
TOP SAND =	12.9
TOP BENT. =	10.6
SCREEN =	15-25
SCREEN LENGTH =	10
END CAP =	0.2
WELL TD =	25.2

TEST BORING REPORT

White Oak Landfill — J07-1957-02

BORING NO. BLE-5 0

PAGE 2 OF 2

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
		9			PWR – BLK & BR, MIC, SI, F-M SAND W/ROCK FRAGMENTS	SAND
-25		29				
		18				25.0
						25.2
						26.0
-30						
-35						
-40						
-45						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-6

PROJECT: WHITE OAK LF
CLIENT:
CONTRACTOR:
EQUIPMENT USED: 4 1/2" HSA

BLE JOB NO. 1957-02
PAGE NO. 1 of 3
LOCATION:
ELEVATION:
DATE START:
DATE FINISH:
DRILLER: TG-BE
PREPARED BY: TL

GROUND WATER		DEPTH TO:		
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE
	TOB	44.65	BGS	
	24	44.70	BGS	

	CASING	SAMPLER	CORE BARREL
TYPE	HSA	Split Spoon	XXX
SIZE ID/OD	8.25" OD	2" ID	XXX
HAMMER WT	XXX	140 lb	XXX
HAMMER FALL	XXX	30"	XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS
					TOPSOIL
		3 3 4	SS-1	MH	FIRM TO STIFF, BR, RED, SOME CLAYEY, F. SANDY SILT
5		4 5 6e	SS-2	SM	FIRM TO V. FIRM, BR, RED, BLK, SILTY, F-M SAND
		5 6e 6e	SS-3	SM	
10		6 8 10	SS-4	SM	
15		4 8 10	SS-5	SM	
20		5 7 8	SS-6	SM	FIRM TO V. FIRM, BR, BLK, GRAY, SILTY, F-M SAND

WELL: GROUT, 2" PVC

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SAMPLE ID	
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION
STICKUP = 3.9
TOP SAND = 33.4
TOP BENT. = 27.0
SCREEN = 46.0 - 36.0
SCREEN LENGTH = 10
END CAP = 0.2
WELL TD = 46.2

TEST BORING REPORT

BORING NO. BLE-6

PAGE 2 OF 3

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
25		5 9 13	SS-7	SM		GROUT
30		5 9 10	SS-8	SM	FIRM, GRY, BR, MIC, SILTY, FINE SAND	BENTONITE
35		5 6 9	SS-9	ML	STIFF, GRY, BLK, MIC, F. SDY SILT	SAND
40		5 7 10	SS-10	ML	V. STIFF, BR, MIC, F. SANDY SILT	
45		6 8 11	SS-11	ML	V. STIFF, GRY, BR, MIC, SL. MOIST, F. SANDY SILT	

2" PVC

36.1

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-6

PAGE 3 OF 3

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
			GS-1	PWR	GNEISS ROCK FRAGMENTS	46.0 46.2
					BORING TERM @ 46.0 AUGER REFUSAL	
			SS-12			
50						
			SS-13			
55						
			SS-14			
60						
			SS-15			
65						
			SS-16			
70						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-7

PROJECT: White Oak Landfill
CLIENT: McGill Associates
CONTRACTOR: Landprobe
EQUIPMENT USED: CME 750 with 4-1/4 inch hollow stem auger

BLE JOB NO. J07-1957-02
PAGE NO. 1 of 2
LOCATION:
ELEVATION:
DATE START: 7/17/07
DATE FINISH: 7/17/07
DRILLER: T. Gradwell
PREPARED BY: T. Livingston

GROUND WATER		DEPTH TO:		
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE
	TOB	10.3		
	24 Hr	7.8		

	CASING	SAMPLER	CORE BARREL
TYPE			
SIZE ID/OD			
HAMMER WT	XXX		XXX
HAMMER FALL	XXX		XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS
					6" TOPSOIL
		3	SS-1		FIRM, BR, SI, CLAY
		3			
		5			
		2			
5		3	SS-2		FIRM, LT. BR, CL, SILT
		3			
		2			
		4	SS-3		LOOSE, LT. BR, BLK, GRAY, SI, F-M SAND
		5			
		2	SS-4		FIRM, LT BR, WHITE, WET, SI, F-C SAND
10		5			
		7			
		2	SS-5		FIRM, GRAY, BR, WET, MIC, SI, F-M SAND
		2			
15		3			
		4	SS-6		STIFF, DK BR, GRAY, WET, MIC, SI F-M SAND
		5			
20		6			

WELL: GRANT; 2" PVC; BENT.; SAND; 10.8; 13.0; 15.0

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION
STICKUP =
TOP SAND =
TOP BENT. =
SCREEN =
SCREEN LENGTH =
END CAP =
WELL TD =

TEST BORING REPORT

White Oak Landfill — J07-1957-02

BORING NO. BLE-7 0

PAGE 2 OF 2

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
						SAND
		2	SS-7		STIFF, GRAY, BR MIC, SILTY, F-M SAND	
25		5				25.0'
		6				25.2'
					AUGER REFUSAL @ 26' BGS, GW @ 10.3' @ TOB AND 7.8' AFTER 24 HRS.	
30						
35						
40						
45						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-7D

PROJECT: White Oak LF - Haywood Co
CLIENT:
CONTRACTOR:
EQUIPMENT USED:

BLE JOB NO. J07-1957-02
PAGE NO. 1 of 3
LOCATION:
ELEVATION:
DATE START: 9/11/07
DATE FINISH: 9/12/07
DRILLER: TG - BE
PREPARED BY: T. LIVINGSTON

GROUND WATER		DEPTH TO:		
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE
	TOR	8.3		
	24	8.3		

	CASING	SAMPLER	CORE BARREL
TYPE	HSA	Split Spoon	XXX
SIZE ID/OD	8.25" OD	2" ID	XXX
HAMMER WT	XXX	140 lb	XXX
HAMMER FALL	XXX	30 "	XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
				6"	TOPSOIL	
			SS-1		SEE BORING LOG FOR BLE-7	
5			SS-2			
			SS-3			
			SS-4			
10						
			SS-5			
15						
			SS-6			
20						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION
STICKUP = 3,5
TOP SAND = 46.9
TOP BENT. = 30.2
SCREEN = 59.6 - 49.6
SCREEN LENGTH = 10
END CAP = 0.2
WELL TD = 59.8

TEST BORING REPORT

BORING NO. BLE-7D

PAGE 2 OF 3

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
25			SS-7			GROUT; 2" PVC
30			SS-8			
35			SS-9		AUGER REFUSAL @ 32.0 CHANGE OVER TO AIR HAMMER SEE CORING REPORT	BENTONITE
40			SS-10			
45			SS-11			

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SAMPLE ID	
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-7D

PAGE 3 OF 3

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
50			SS-12		SAND	46.9 49.6
55			SS-13			
60			SS-14			59.6 59.8 60.0
65			SS-15		BORING TERMINATED @ 60.0	
70			SS-16			

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

CORE BORING REPORT

BORING NO. BLE-7D

PROJECT: WHITE OAK LF
CLIENT: McGILL ASSO.
CONTRACTOR:
EQUIPMENT USED:

BLE JOB NO. J07-1957-02
PAGE NO. 1 of 2
LOCATION:
ELEVATION:
DATE START:
DATE FINISH:
DRILLER:
PREPARED BY: TL

GROUND WATER		DEPTH TO:			ORIENTATION		CORE BARREL	
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE	X	VERTICAL	TYPE	NQ
						HORIZONTAL	TYPE	
						INCLINED	Bit (ft)	
						BEARING	Barrel (ft)	
						ANG. FROM VERT.	Total (ft)	

DEPTH IN FEET	DRILL RATE MIN/FT	CORE NO. DEPTH RANGE	SAMPLE NUMBER	RECOVERY FT	RECOVERY %	RQD	FIELD CLASSIFICATION AND REMARKS	WELL
30		32.0					AUGER REFUSAL 32.0'	32
35		35.0	R-1	15"	42	(9") 25	HARD, SLI WEATHERED, BR, DRK GRY, WHITE, COARSE GRAINED QUARTZ FELDSPAR BIOTITE GNEISS; W/ THICK FOLIATION, V. CLOSE STAINED FRACTURES	33
40		40.0	R-2	60"	100	(59") 98	V. HARD, FRESH, BR, DRK GRY, WHITE, FINE TO COARSE GRAINED QTZ-FELDSPAR BIOTITE GNEISS; MOD. FOLIATION, THIN, FOLIATION, AND CLOSE TO V. CLOSE SPACED STAINED FRACTURES	
45		45.0	R-3	60"	100	(54") 90		

FIELD HARDNESS		BEDDING		ATTITUDE AND ANGLE	JOINTS / SHEAR / FRACTURE		WEATHERING
V. HARD	- KNIFE CANT SCRATCH	V. THIN	<2"	HORIZONTAL (0-5)	V. CLOSE	<2"	FRESH
HARD	- SCRATCHES DIFFICULTLY	THIN	2"-12"	SHALLOW OR LOW ANGLE (5-35)	CLOSE	2"-12"	V. SLIGHT
MOD. HARD	- SCRATCHES EASILY	MEDIUM	12"-36"	MODERATELY DIPPING (35-55)	MOD CLOSE	12"-36"	SLIGHT
SOFT	- GROVES	THICK	36"-120"	STEEP OR HIGH ANGLE (55-85)	WIDE	36"-120"	MODERATE
V. SOFT	- CARVES	V. THICK	>120"	VERTICAL (85-90)	V. WIDE	>120"	MOD. SEVERE
							V. SEVERE
							COMPLETE

ORDER FOR CORE DESCRIPTION: FIELD HARDNESS, WEATHERING, COLOR, GRAIN SIZE/TEXTURE, LITHOLOGY, FRACTURE CHARACTERISTICS, BEDDING AND FOLIATION, COMMENTS

Changes
Rod on
GS to TOR
Depth to bit
Run

WELL DESCRIPTION	
SCREEN DEPTH =	STICKUP =
SCREEN LENGTH =	TOP SAND =
END CAP =	TOP BENT. =
WELL TD =	BOT. CASING =

CORE BORING REPORT

BORING NO. BLE-7D

PAGE 2 OF 2

DEPTH IN FEET	DRILL RATE MIN/FT	CORE NO. DEPTH RANGE	SAMPLE NUMBER	RECOVERY FT	RECOVERY %	RQD	FIELD CLASSIFICATION AND REMARKS	WELL
			R-4	54"	90	(50") 83		
50		50.0						
			R-5	58"	97	(30") 50		
55		55.0						
			R-6	60"	100	(43") 72		
60		60.0						60.0
							WELL SET	

FIELD HARDNESS		BEDDING		ATTITUDE AND ANGLE	JOINTS / SHEAR / FRACTURE		WEATHERING
V. HARD	- KNIFE CANT SCRATCH	V. THIN	<2"	HORIZONTAL (0-5)	V. CLOSE	<2"	FRESH
HARD	- SCRATCHES DIFFICULTLY	THIN	2"-12"	SHALLOW OR LOW ANGLE (5-35)	CLOSE	2"-12"	V. SLIGHT
MOD. HARD	- SCRATCHES EASILY	MEDIUM	12"-36"	MODERATELY DIPPING (35-55)	MOD CLOSE	12"-36"	SLIGHT
SOFT	- GROVES	THICK	36"-120"	STEEP OR HIGH ANGLE (55-85)	WIDE	36"-120"	MODERATE
V. SOFT	- CARVES	V. THICK	>120"	VERTICAL (85-90)	V. WIDE	>120"	MOD. SEVERE
							V. SEVERE
							COMPLETE

ORDER FOR CORE DESCRIPTION: FIELD HARDNESS, WEATHERING, COLOR, GRAIN SIZE/TEXTURE, LITHOLOGY, FRACTURE CHARACTERISTICS, BEDDING AND FOLIATION, COMMENTS

Changes
Rod on
GS to TOR
Depth to bit
Run

WELL MATERIALS	
SAND =	GROUT =
	WELL O.D. =
BENTONITE =	CASING O.D. =
	WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-8

PROJECT: Haywood County White Oak DHR
CLIENT: McGill Associates
CONTRACTOR: Landprobe
EQUIPMENT USED: CME 750 with 4-1/4 inch hollow stem auger

BLE JOB NO. 1957-02
PAGE NO. 1 of 1
LOCATION:
ELEVATION:
DATE START: 7-18-07
DATE FINISH: 7-18-07
DRILLER: T. Gradwell
PREPARED BY: T. Livingston

GROUND WATER		DEPTH TO:				CASING	SAMPLER	CORE BARREL
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE	TYPE			
					SIZE ID/OD			
					HAMMER WT	XXX		XXX
					HAMMER FALL	XXX		XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
					6-inches Topsoil	
					Auger refusal at 3 ft. No groundwater at time of drilling.	
5						
10						
15						
20						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SAMPLE ID	
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION
STICKUP =
TOP SAND =
TOP BENT. =
SCREEN =
SCREEN LENGTH =
END CAP =
WELL TD =

TEST BORING REPORT

BORING NO. BLE-9

PROJECT: WHITE OAK LF - HAYWOOD CO
CLIENT:
CONTRACTOR:
EQUIPMENT USED:

BLE JOB NO. J07-1957-02
PAGE NO. 1 of 3
LOCATION:
ELEVATION:
DATE START: 9/6/07
DATE FINISH: 9/7/07
DRILLER: FG
PREPARED BY: TL

GROUND WATER DATE	HRS AFT COMP	DEPTH TO: WATER	BOT. OF CASING	BOT. OF HOLE
	TOB	42.7		
	24	43.0		

	CASING	SAMPLER	CORE BARREL
TYPE	HSA	Split Spoon	XXX
SIZE ID/OD	8.25" OD	2" ID	XXX
HAMMER WT	XXX	140 lb	XXX
HAMMER FALL	XXX	30 "	XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
					TOPSOIL	
		3			FIRM TO STIFF, BR + GRAY, F. SAND,	
		4	SS-1	ML	CLAYEY, MIC., SILT	
		4				
		4				
		5	SS-2	ML		
5		5				
					STIFF TO V. STIFF, BR, GRAY, BL,	
		5			MIC., F. SANDY, SILT	
		5	SS-3	ML		
		6				
		5				
		6	SS-4	ML		
10		7				
			SS-5 UD	ML		
15						
		5				
		7	SS-6	ML		
20		8				

GROUT

2" PVC

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION	
STICKUP =	3.8
TOP SAND =	35.4
TOP BENT. =	23.6
SCREEN =	47.7-37.7
SCREEN LENGTH =	10
END CAP =	0.2
WELL TD =	47.9

TEST BORING REPORT

BORING NO. BLE-9

PAGE 2 OF 3

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
		50/3"	SS-7	SM	PWR, GRAY, WHITE, SILTY SAND W/ ROCK FRAGMENTS	23.0
25					AUGER REFUSAL @ 25.0	
					CHANGE OVER TO AIR HAMMER	
						2" PVC
			SS-8			
30						BENTONITE
			SS-9		SEE CORING REPORT	
35						35.0
						37.7
			SS-10			SAND
40						
			SS-11			
45						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

BORING NO. BLB-9

PAGE 3 OF 3

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
						SAND 47.7 47.9
			SS-12		BORING TERM. @ 49.0	
50						
			SS-13			
55						
			SS-14			
60						
			SS-15			
65						
			SS-16			
70						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

CORE BORING REPORT

BORING NO. BLE-9

PROJECT: White Oak LF
CLIENT:
CONTRACTOR:
EQUIPMENT USED:

BLE JOB NO. J07-1957-02
PAGE NO. 1 of 2
LOCATION:
ELEVATION:
DATE START: 9/6/07
DATE FINISH: 9/7/07
DRILLER: TG
PREPARED BY: TL

GROUND WATER		DEPTH TO:			ORIENTATION		CORE BARREL	
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE	X	VERTICAL	TYPE	NQ
						HORIZONTAL	TYPE	
						INCLINED	Bit (ft)	
						BEARING	Barrel (ft)	
						ANG. FROM VERT.	Total (ft)	

DEPTH IN FEET	DRILL RATE MIN/FT	CORE NO. DEPTH RANGE	SAMPLE NUMBER	RECOVERY FT	RECOVERY %	RQD	FIELD CLASSIFICATION AND REMARKS	WELL
25		25.0					AUGER REFUSAL	25
30		30.0	R-1	48"	80	(30") 50	MOD. HARD, SLI WEATHERED, BRN, DK GRAY, WHITE, F. TO COARSE GRAINED, QTZ-FELDSPAR-BIOTITE GNEISS; W/ MOD. DEVELOPED, V. THIN, SHALLOW DIPPING FOLIATION, AND CLOSE TO V. CLOSE SPACED, SHALLOW AND STEEPLY DIPPING, IRON STAINED FRACTURES	
35		35.0	R-2	45"	75	(37") 62		
40		40.0	R-3	55"	92	(41") 68		

FIELD HARDNESS		BEDDING		ATTITUDE AND ANGLE	JOINTS / SHEAR / FRACTURE		WEATHERING
V. HARD	- KNIFE CANT SCRATCH	V. THIN	<2"	HORIZONTAL (0-5)	V. CLOSE	<2"	FRESH
HARD	- SCRATCHES DIFFICULTLY	THIN	2"-12"	SHALLOW OR LOW ANGLE (5-35)	CLOSE	2"-12"	V. SLIGHT
MOD. HARD	- SCRATCHES EASILY	MEDIUM	12"-36"	MODERATELY DIPPING (35-55).	MOD CLOSE	12"-36"	SLIGHT
SOFT	- GROVES	THICK	36"-120"	STEEP OR HIGH ANGLE (55-85)	WIDE	36"-120"	MODERATE
V. SOFT	- CARVES	V. THICK	>120"	VERTICAL (85-90)	V. WIDE	>120"	MOD. SEVERE
							V. SEVERE
							COMPLETE

ORDER FOR CORE DESCRIPTION: FIELD HARDNESS, WEATHERING, COLOR, GRAIN SIZE/TEXTURE, LITHOLOGY, FRACTURE CHARACTERISTICS, BEDDING AND FOLIATION, COMMENTS

Changes
Rod on
GS to TOR
Depth to bit
Run

WELL DESCRIPTION	
SCREEN DEPTH =	STICKUP =
SCREEN LENGTH =	TOP SAND =
END CAP =	TOP BENT. =
WELL TD =	BOT. CASING =

CORE BORING REPORT

BORING NO. BLE-9
PAGE 2 OF 2

DEPTH IN FEET	DRILL RATE MIN/FT	CORE NO. DEPTH RANGE	SAMPLE NUMBER	RECOVERY FT	RECOVERY %	RQD	FIELD CLASSIFICATION AND REMARKS	WELL
			R-4	58"	97	(52") 87		
45		45.0					SOFT, MOD. WEATHERED, BRN, GRN, F. GRAINED BIOTITE SCHIST; W/ WELL DEVELOPED, V. THIN, SHALLOW DIPPING FOLIATION, SHALLOW DIPPING, IRON STAINED FRACTURE.	44.0 45.0
			R-5					
49		49.0					HARD, V. SLI. WEATHERED, BRN, DK GRAY, WHITE, F. TO COARSE GRAINED, QTZ-FELDSPAR-BIOTITE GNEISS; MOD. DEVELOPED FOLIATION, V. CLOSE SPACED FRACTURES	49.0
							WELL SET	

FIELD HARDNESS		BEDDING		ATTITUDE AND ANGLE	JOINTS / SHEAR / FRACTURE		WEATHERING
V. HARD	- KNIFE CANT SCRATCH	V. THIN	<2"	HORIZONTAL (0-5)	V. CLOSE	<2"	FRESH
HARD	- SCRATCHES DIFFICULTLY	THIN	2"-12"	SHALLOW OR LOW ANGLE (5-35)	CLOSE	2"-12"	V. SLIGHT
MOD. HARD	- SCRATCHES EASILY	MEDIUM	12"-36"	MODERATELY DIPPING (35-55)	MOD CLOSE	12"-36"	SLIGHT
SOFT	- GROVES	THICK	36"-120"	STEEP OR HIGH ANGLE (55-85)	WIDE	36"-120"	MODERATE
V. SOFT	- CARVES	V. THICK	>120"	VERTICAL (85-90)	V. WIDE	>120"	MOD. SEVERE
							V. SEVERE
							COMPLETE

ORDER FOR CORE DESCRIPTION: FIELD HARDNESS, WEATHERING, COLOR, GRAIN SIZE/TEXTURE, LITHOLOGY, FRACTURE CHARACTERISTICS, BEDDING AND FOLIATION, COMMENTS

Changes
Rod on
GS to TOR
Depth to bit
Run

WELL MATERIALS	
SAND =	GROUT =
	WELL O.D. =
BENTONITE =	CASING O.D. =
	WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-10

PROJECT: WHITE OAK LP
CLIENT:
CONTRACTOR:
EQUIPMENT USED: 4 1/2" HSA

BLE JOB NO. 1957-02
PAGE NO. 1 of 4
LOCATION:
ELEVATION:
DATE START: 7/24/07
DATE FINISH: 7/26/07
DRILLER:
PREPARED BY: TL

GROUND WATER		DEPTH TO:				CASING	SAMPLER	CORE BARREL
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE	TYPE	HSA	Split Spoon	XXX
	TOB	61.5			SIZE ID/OD	8.25" OD	2" ID	XXX
					HAMMER WT	XXX	140 lb	XXX
					HAMMER FALL	XXX	30 "	XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
		4	SS-1	ML	STIFF, DK RED, LT. BR, F. SANDY SILT	
		6				
		6				
		6	SS-2	SM	V. FIRM, LT. BR, SI, F-M SAND	
5		10				
		15				
		6	SS-3	MH	V. STIFF, DK. RED, LT BR, FINE SANDY, CLAYEY SILT	
		11				
		14				
		6	SS-4	MH		
		12				
10		13				
		10	SS-5	MH		
		12				
15		15				
		8	SS-6	MH		
		13				
20		16				

GROUT

2" PVC

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SAMPLE ID	
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION
STICKUP = 3.0
TOP SAND = 66.7
TOP BENT. = 62.7
SCREEN = 68.7 - 78.7
SCREEN LENGTH = 10
END CAP = 0.2
WELL TD = 78.9

TEST BORING REPORT

BORING NO. BLE-10

PAGE 2 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
25		11 16 15	SS-7	MH		2" PVC
30		11 15 13	SS-8	SM	V. FIRM, RED, BR, GRAY, SI F-M SAND	
35		9 16 20	SS-9	ML	HARD, RED, BR, GRAY, F. SANDY SILT	
40		11 20 37	SS-10	MLS	V. HARD TO HARD LT BR, GRAY, BLK, F-M SANDY SILT	
45		13 26 26	SS-11	MLS		

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-10
PAGE 3 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
50		11 20 21	SS-12	MLS		GROUT
55		10 12 20	SS-13	MLS		2" PVC
60		6 14 27	SS-14	ML	V. STIFF, BR, WH, GRAY, F. SANDY SILT	
65		14 28 30	SS-15	ML	V. HARD, GRAY, BRN, WH., F. SANDY SILT	BENTONITE 62.7
70		13 21 25	SS-16	ML	HARD TO V. HARD, GRAY, BR, MICACEOUS, MOIST, F. SANDY SILT	SAND 66.7 68.7

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-10

PAGE 4 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
75		11 20 50	SS-17	ML		78.7 78.9
80			SS-18		BORING TERM. @ 78.9	
85			SS-19			
90			SS-20			
95			SS-21			

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SAMPLE ID	
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-11

PROJECT: WHITE OAK LF
CLIENT:
CONTRACTOR:
EQUIPMENT USED: 4½" HSA

BLE JOB NO. 1957-02
PAGE NO. 1 of 5
LOCATION:
ELEVATION:
DATE START: 8/3/07
DATE FINISH:
DRILLER: K. THOMAS
PREPARED BY: TL

GROUND WATER		DEPTH TO:		
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE
	TOP	89.7		
	24	84.6		

	CASING	SAMPLER	CORE BARREL
TYPE	HSA	Split Spoon	XXX
SIZE ID/OD	8.25" OD	2" ID	XXX
HAMMER WT	XXX	140 lb	XXX
HAMMER FALL	XXX	30 "	XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS
		3 4 7	SS-1	ML	STIFF TO V. STIFF, DK. RED, LT. BR, F. SANDY SILT
		3 6 9	SS-2	ML	
5		4 6 8	SS-3	ML	
		4 9 10	SS-4	ML	
10					
		3 5 7	SS-5	ML	STIFF, DK RED, LT. BR, F. SANDY SILT
15					
		4 5 9	SS-6	ML	
20					

WELL: GROUT, 2" PVC

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SAMPLE ID	
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION	
STICKUP =	2.6
TOP SAND =	90.1
TOP BENT. =	71.0
SCREEN =	92.6-102.6
SCREEN LENGTH =	10
END CAP =	0.2
WELL TD =	102.8

TEST BORING REPORT

BORING NO. BLE-11

PAGE 2 OF 5

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
25		3 5 8	SS-7	ML		GROUT 2" PVC
30		5 7 10	SS-8	ML	STIFF TO V. STIFF, RED, LT. BR, BLK, F. SANDY SILT	
35		4 5 9	SS-9	ML		
40		7 9 12	SS-10	ML		
45		8 11 14	SS-11	ML	V. STIFF, RED, BR, GRAY, MIC., FINE SANDY SILT	

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-11

PAGE 3 OF 5

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
50		3 9 12	SS-12	ML		
55		5 10 10	SS-13	ML	V. STIFF, WHITE, LT. BR, FINE SANDY SILT	
60		16 22 24	SS-14	MH	HARD TO V. STIFF, RED, BR, CLAYEY, F. SANDY SILT	2" PVC GROUT
65		6 10 14	SS-15	MH		
70		2 5 11	SS-16	ML	V. STIFF, GRAY, BR, FI SANDY, SILT	

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SAMPLE ID	
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-11

PAGE 4 OF 5

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
						71.0
		8				
		10	SS-17	ML		
75		12				
						BENTONITE
		10				
		14	SS-18	ML	V. STIFF, GRAY, LT. BR, MOIST, FINE SANDY SILT	
80		16				
		10				
		18	SS-19	MH	V. HARD, RED, GRY, LT BR, CLAYEY, F. SDY SILT	
85		20				
		14				
		16	SS-20	ML	V. STIFF TO HARD, GRY, BR, BLK, MOIST, F. SANDY SILT	
90		18				90.1
						SAND
		8				
		10	SS-21	ML		
95		12				

BLOWS/FT	DENSITY	BLOWS/FT	CONSISTANCY	SAMPLE ID		WELL MATERIALS
0-4	VERY LOOSE	0-2	VERY SOFT	SS	SPLIT SPOON	SAND =
5-10	LOOSE	3-4	SOFT	HP	HYDROPUNCH	
11-20	FIRM	5-8	FIRM	UD	UNDISTURBED TUBE	BENTONITE =
21-30	VERY FIRM	9-15	STIFF	G	GRAB	
31-50	DENSE	16-30	VERY STIFF	C	COMPOSITE	GROUT =
51+	VERY DENSE	31-50	HARD	B	BAG	WELL O.D. =
		51+	VERY HARD	NR	NO RECOVERY	WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-11
PAGE 5 OF 5

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
100			SS-22	ML	SAND	102.4 / 102.8
105			SS-23		BORING TERM. @ 103.0	
110			SS-24			
115			SS-25			
120			SS-26			

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-12

PROJECT: White Oak LF - Haywood Co.
CLIENT:
CONTRACTOR:
EQUIPMENT USED:

BLE JOB NO. J07-1957-02
PAGE NO. 1 of 4
LOCATION:
ELEVATION:
DATE START:
DATE FINISH:
DRILLER: TG-BE
PREPARED BY: TL

GROUND WATER		DEPTH TO:		
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE
	TOB	75.9		
	24	75.9		

	CASING	SAMPLER	CORE BARREL
TYPE	HSA	Split Spoon	XXX
SIZE ID/OD	8.25" OD	2" ID	XXX
HAMMER WT	XXX	140 lb	XXX
HAMMER FALL	XXX	30 "	XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS
		3 4 5	SS-1	MH	STIFF, RED, CLAYEY, SILT
		4 4 6	SS-2	MH	
5					
		4 5 6	SS-3	ML	STIFF TO V. STIFF, RED, BRN, F. SANDY, SILT
		5 7 9	SS-4	ML	
10					
		5 7 8	SS-5	ML	
15					
		5 8 8	SS-6	ML	V. STIFF, RED & LT. BR, F. SANDY, SILT W/SOME CLAY
20					

WELL: GROUT, 2" PVC

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION
STICKUP = 2.2
TOP SAND = 77.8
TOP BENT. = 68.3
SCREEN = 90.0 - 80.0
SCREEN LENGTH = 10
END CAP = 0.2
WELL TD = 90.2

TEST BORING REPORT

BORING NO. BLB-12

PAGE 2 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
25		4 8 11	SS-7	ML		
30		4 8 11	SS-8	ML	V. STIF LT. BR + RED, F. SANDY, SILT	GROUT 2" PVC
35		5 8 11	SS-9	ML	V. STIFF, BR, RED, BLK, MIC., FINE SANDY, SILT	
40		10 10 16	SS-10	ML		
45		5 8 14	SS-11	ML	V. STIFF, BRN, GRAY, MIC., F. SANDY, SILT	

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-12

PAGE 3 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
50		4 8 12	SS-12	ML		GROUT 2" PVC
55		4 5 9	SS-13	ML	FIRM TO DENSE, BRN, RED, BLK, SILTY, FINE SAND	
60		6 10 23	SS-14	ML		
65		9 14 18	SS-15	ML	HARD, GRAY, BRN, BLK, MICA, F. SANDY, SILT	
70		16 22 29	SS-16	ML		68.3

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-12

PAGE 4 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
75		10 16 20	SS-17	ML		BENTONITE 2" PVC
80		10 20 22	SS-18	ML		77.9 80.0
85		8 12 26	SS-19	ML	HARD, GRAY, BR, MIC, F SANDY SILT	SAND
90		10 14 22	SS-20	ML		90.0 90.2
95			SS-21		BORING TERM. @ 90.2	

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-13

PROJECT: White Oak Landfill
CLIENT: McGill Associates
CONTRACTOR: Landprobe
EQUIPMENT USED: CME 750 with 4-1/4 inch hollow stem auger

BLE JOB NO. J07-1957-02
PAGE NO. 1 of
LOCATION:
ELEVATION:
DATE START: 7/22/07
DATE FINISH: 7/22/07
DRILLER: T. Gradwell
PREPARED BY: T. Livingston

GROUND WATER DATE	HRS AFT COMP	DEPTH TO: WATER	BOT. OF CASING	BOT. OF HOLE
	TOB	69.0		
	24 HR	67.5		

	CASING	SAMPLER	CORE BARREL
TYPE			
SIZE ID/OD			
HAMMER WT	XXX		XXX
HAMMER FALL	XXX		XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS
		7			STIFF, DK RED & BR, SI, CLAY
		7	SS-1		
		7			
		13			PWR, WH, PINK, QUARTZ ROCK
		13	SS-2		
5		13			
		5			V. STIFF, DK RED, BR, MIC, F-M SA, SILT
		7	SS-3		
		9			
		9			
		14	SS-4		
10		15			
		7			V. STIFF, DK RED, MIC, CL, F-M SA, SILT
		10	SS-5		
15		15			
		7			
		10	SS-6		
20		15			

WELL: GROUT, 2" PVC

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION
STICKUP =
TOP SAND = 69.4
TOP BENT. = 66.8
SCREEN = 71.4 - 81.4
SCREEN LENGTH = 10
END CAP = 0.2
WELL TD = 81.6

TEST BORING REPORT

BORING NO. BLE-B 0

White Oak Landfill J07-1957-02 PAGE 2 OF

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
25			UD			
30		8 16 20	SS-7		HARD, DK RED, BR, MIC, F-M SA, SILT	GROUT 2" PVC
35		17 20 24	SS-8			
40		12 18 23	SS-9		HARD, BLK, BR, RED, MIC, SI, F-M SAND	
45		8 15 20	SS-10		HARD, DK BR, MIC, F. SA, SILT	

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

White Oak Landfill — **J07-1957-02** — **BORING NO.** BLE-13 0 — PAGE 3 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
		8				
-50		16 26	SS-11		HARD, BR + LT BR, MIC, F. SA, SILT	
		13				
-55		22 22	SS-12		HARD TO V. HARD, BLK, BR, GRAY, MOI, F. SA, SILT	
		15				
-60		20 23	SS-13			
		28				
-65		30 33	SS-14			
		23				
-70		32 48	SS-15			

WELL: GROUT 2" PVC; BENT; 66.5; 69.4

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS: SAND = ; BENTONITE = ; GROUT = ; WELL O.D. = ; WELL TYPE =

TEST BORING REPORT

White Oak Landfill — J07-1957-02 — BORING NO. BLE-13 0 — PAGE 4 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
						71.4
		26	SS-16		PWR - GRAY + WHITE, SI, F-M SAND	
-75		45				
		50/3"				
						SAND
-80						81.4
						81.6
		50/3"	SS-17			
-85		-				
						86.1
					AUGER REFUSAL @ 86.0' BGS, GW AT 69.0' @ TOB AND 67.5' AFTER 24 HRS.	
-90						
-95						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS: SAND = ; BENTONITE = ; GROUT = ; WELL O.D. = ; WELL TYPE =

TEST BORING REPORT

BORING NO. BLB-14

PROJECT: WHITE OAK LF - HAYWOOD CO.
CLIENT:
CONTRACTOR:
EQUIPMENT USED:

BLE JOB NO. J07-1957-02
PAGE NO. 1 of 4
LOCATION:
ELEVATION:
DATE START: 9/4/07
DATE FINISH:
DRILLER: TG-BE
PREPARED BY: T. LIVINGSTON

GROUND WATER		DEPTH TO:				CASING	SAMPLER	CORE BARREL
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE	TYPE	HSA	Split Spoon	XXX
	TOB	59.1			SIZE ID/OD	8.25" OD	2" ID	XXX
	24	59.2			HAMMER WT	XXX	140 lb	XXX
					HAMMER FALL	XXX	30 "	XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
					STIFF TO V. STIFF RED, LT BRN, F. SANDY SILT W/ SOME CLAY	GROUT, 2" PVC
		3 4 6	SS-1	ML		
		4 5 7	SS-2	ML		
5		4 4 7	SS-3	ML		
		4 6 8	SS-4	ML		
10						
		4 7 9	SS-5	ML		
15						
		6 9 11	SS-6	MH	V. STIFF, RED, BRN, BLK, MIC., FINE SANDY, CLAYEY, SILT	
20						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SAMPLE ID	
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION	
STICKUP =	4.0
TOP SAND =	60.3
TOP BENT. =	45.7
SCREEN =	73.3-63.3
SCREEN LENGTH =	10
END CAP =	0.2
WELL TD =	73.5

TEST BORING REPORT

BORING NO. BLB-14

PAGE 2 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
25		5 9 12	SS-7	MH		GROUT 2" PVC
30		6 8 12	SS-8	MH		
35		11 21 30	SS-9	ML	V. HARD TO STIFF, GRAY, BRN, MIC., F. SANDY, SILT	
40		17 28 33	SS-10	ML		
45		11 16 21	SS-11	ML		

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-14

PAGE 3 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
50		9 12 14	SS-12	ML		45.7 BENTONITE
55		12 13 16	SS-13	ML	V. STIFF TO HARD, BR, GRAY, MIC., MOIST, F. SANDY, SILT	2" PVC
60		14 15 18	SS-14	ML		60.3
65		13 14 17	SS-15	ML		63.3 SAND
70		50/1"	SS-16	ML	V. HARD, GRY, BLK, WHITE, SILTY, F-M SAND	

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

TEST BORING REPORT

BORING NO. 2LE-14

PAGE 4 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
					SAND	73.5
					BORING TERM @ 73.5	73,5
75			SS-17		AUGER REFUSAL	
80			SS-18			
85			SS-19			
90			SS-20			
95			SS-21			

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS
SAND =
BENTONITE =
GROUT =
WELL O.D. =
WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-15

PROJECT:	White Oak Landfill
CLIENT:	McGill Associates
CONTRACTOR:	Landprobe
EQUIPMENT USED:	CME 750 with 4-1/4 inch hollow stem auger
BLE JOB NO.	J07-1957-02
PAGE NO.	1 of 4
LOCATION:	
ELEVATION:	
DATE START:	7/19/07
DATE FINISH:	7/20/07
DRILLER:	T. Gradwell
PREPARED BY:	T. Livingston

GROUND WATER		DEPTH TO:				CASING	SAMPLER	CORE BARREL
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE	TYPE			
	TOB	57.75			SIZE ID/OD			
	24 HR	57.1			HAMMER WT	XXX		XXX
					HAMMER FALL	XXX		XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
					6" TOPSOIL	
		5	SS-1		STIFF TO V. STIFF, DK RED, SI, CLAY	
		6				
		8				
		3	SS-2			
		5				
5		8				
		5	SS-3			
		9				
		10				
		3	SS-4			
		4				
10		6				
		5	SS-5		V. STIFF TO HARD, BR & PURPLE, MIC, F. SA, CL, SILT	
		12				
15		15				
		9	SS-6			
		15				
20		18				

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION	
STICKUP =	
TOP SAND =	62.1
TOP BENT. =	59.7
SCREEN =	64.13-74.13
SCREEN LENGTH =	10
END CAP =	0.2
WELL TD =	74.33

TEST BORING REPORT

BORING NO. BLE-15 0

White Oak Landfill — **J07-1957-02** — PAGE 2 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
		9	SS-7		HARD, BR, F. SA, CL, SILT	
-25		15				
		19				
		5	SS-8		V. STIFF, RED + BR, SI, CLAY	
		6				
-30		11				
		4	SS-9		STIFF, LT. BR, F. SA, SILT	
		6				
-35		6				
		7	SS-10		V. STIFF, GRAY + BR, MIC, F. SA, SILT	
		8				
-40		9				
		7	SS-11			
		9				
-45		19				

Grout, 2" PVC

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

SAMPLE ID

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-15 0

White Oak Landfill — **J07-1957-02** — **PAGE** 3 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
						Grout
		7				
		9	SS-12			
-50		11				
		7				
		8	SS-13		V. STIFF, BR + GRAY, MIC, F. SA, SILT W/ROCK FRAGMENTS	
-55		13				
		5				
		9	SS-14			
-60		15				59.7
						62.1
		9				
		12	SS-15		V. FIRM, WHITE + LT. BR, MOIST, SI, F-M SAND	64.1
-65		14				
		15				
		22	SS-16		V. DENSE, GRAY + BR, SI, F-M SAND	
-78		50/6"				

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

TEST BORING REPORT

White Oak Landfill — J07-1957-02 — BORING NO. BLE-15 0 — PAGE 4 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
						SAND
		14			V. DENSE, OR, BR, SI, F-M SAND	74.1
75		26 50/4"	SS-17		W/ROCK FRAGMENTS	74.3 75.1
					BORING TERM. @ 75' BGS. GW ENCOUNTERED @ 57.75' @ TOB AND @ 57.1' AFTER 24 HOURS.	
80						
85						
90						
95						

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS: SAND = | BENTONITE = | GROUT = | WELL O.D. = | WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-10

PROJECT: WHITE OAK NSW CF
CLIENT: MCGILL ASSOC.
CONTRACTOR:
EQUIPMENT USED: 4 1/2" HSA

BLE JOB NO. J07-1957-02
PAGE NO. 1 of 4
LOCATION:
ELEVATION:
DATE START: 7/29/07
DATE FINISH:
DRILLER:
PREPARED BY: TL

GROUND WATER		DEPTH TO:		
DATE	HRS AFT COMP	WATER	BOT. OF CASING	BOT. OF HOLE
	TOB	68.5		

	CASING	SAMPLER	CORE BARREL
TYPE	HSA	Split Spoon	XXX
SIZE ID/OD	8.25" OD	2" ID	XXX
HAMMER WT	XXX	140 lb	XXX
HAMMER FALL	XXX	30 "	XXX

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
					V. FIRM WHITE, LT BR SILTY F-M SAND	
		14 12 15	SS-1	SM		
		6 10 11	SS-2	SM		
5					V. STIF LT. BR, RED, WH FINE SANDY SILT	
		7 7 9	SS-3	ML		
		9 10 11	SS-4	ML		
10						
		8 12 15	SS-5	ML		
15					RED, DK RED, BLK FINE SANDY SILT V. STIFF TO HARD	
		7 14 15	SS-6	ML		
20						

WELL: GROUT, 2" PVC

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

SAMPLE ID	
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL DESCRIPTION	
STICKUP =	4.0
TOP SAND =	67.6
TOP BENT. =	64.7
SCREEN =	68.2 — 78.2
SCREEN LENGTH =	10
END CAP =	0.2
WELL TD =	78.4

TEST BORING REPORT

BORING NO. BLE-16

PAGE 2 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
					SAME AS ABOVE	GROUT 2" PVC
		8				
		10	SS-7	ML		
25		14				
		9				
		11	SS-8	ML		
30		18				
		10				
		17	SS-9	ML		
35		19				
		10				
		12	SS-10	ML		
40		27				
		12			LT RED, LT BR, BLK SILTY FINE SAND	
		20	SS-11	SM		
45		27				

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

TEST BORING REPORT

BORING NO. BLE-11

PAGE 3 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
					V. DENSE	
		12			LT. BR, GRAY SI F-M SAND	
		25	SS-12	SM		
50		30				
					V. DENSE BR, GRY, RED SI	
		12			F-M SAND	
		15	SS-13	SM		
55		25				
		9			HARD, BR, GRAY FINE SANDY	
		16	SS-14	ML	SILT	
60		24				
		10				
		12	SS-15	ML		
65		20				
		10				
		14	SS-16	ML		
70		20				

GROUT

2" PVC

BENTONITE

SAND

61.7

67.4

68.2

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

TEST BORING REPORT

BORING NO. B-16

PAGE 4 OF 4

DEPTH IN FEET	CASING BLOWS PER FT	SAMPLER BLOWS PER 6"	SAMPLE NUMBER	USCS	FIELD CLASSIFICATION AND REMARKS	WELL
75		12 24 25	SS-17	SM	DENSE, GRAY, LT. BROWN, F-M SILTY SAND	SAND
80		8 18 32	SS-18	ML	HARD, GRAY, BRN, F. SANDY SILT	78.2 78.4 80.0
85			SS-19		BORING TERM. @ 80.0	
90			SS-20			
95			SS-21			

BLOWS/FT	DENSITY
0-4	VERY LOOSE
5-10	LOOSE
11-20	FIRM
21-30	VERY FIRM
31-50	DENSE
51+	VERY DENSE

BLOWS/FT	CONSISTANCY
0-2	VERY SOFT
3-4	SOFT
5-8	FIRM
9-15	STIFF
16-30	VERY STIFF
31-50	HARD
51+	VERY HARD

	SAMPLE ID
SS	SPLIT SPOON
HP	HYDROPUNCH
UD	UNDISTURBED TUBE
G	GRAB
C	COMPOSITE
B	BAG
NR	NO RECOVERY

WELL MATERIALS

SAND =

BENTONITE =

GROUT =

WELL O.D. =

WELL TYPE =

APPENDIX C

SOIL AND ROCK BORING RECORDS AND WELL DIAGRAMS

APPENDIX C

SOIL AND ROCK BORINGS RECORDS AND WELL DIAGRAMS

Piezometers and monitoring wells have been installed at the site since 1990. The piezometers were installed as part of Site Hydrogeologic and Design Hydrogeologic investigations performed at the site in the past. The monitoring wells were installed as part of the water quality monitoring system for the constructed landfill cells.

KEY TO SOIL CLASSIFICATIONS AND CONSISTENCY DESCRIPTIONS

BUNNELL-LAMMONS ENGINEERING, INC.
GREENVILLE, SOUTH CAROLINA

Penetration Resistance* Blows per Foot	Relative Density
SANDS	
0 to 4	Very Loose
5 to 10	Loose
11 to 20	Firm
21 to 30	Very Firm
31 to 50	Dense
over 50	Very Dense

Penetration Resistance* Blows per Foot	Consistency
SILTS and CLAYS	
0 to 2	Very Soft
3 to 4	Soft
5 to 8	Firm
9 to 15	Stiff
16 to 30	Very Stiff
31 to 50	Hard
over 50	Very Hard

*ASTM D 1586

Particle Size Identification

Boulder: Greater than 300 mm
Cobble: 75 to 300 mm
Gravel:
Coarse - 19 to 75 mm
Fine - 4.75 to 19 mm
Sand:
Coarse - 2 to 4.75 mm
Medium - 0.425 to 2 mm
Fine - 0.075 to 0.425 mm
Silt & Clay: Less than 0.075 mm

KEY TO DRILLING SYMBOLS


Grab Sample


Split Spoon Sample


Undistrurbed Sample

NR = No reaction to HCL

NA = Not applicable

NS = No sample


Groundwater Table at Time of Drilling


Groundwater Table 24 Hours after Completion of Drilling

KEY TO SOIL CLASSIFICATIONS


Well-graded Gravel
GW


Low Plasticity Clay
CL


Clayey Silt
MH


Silty Sand
SM


Poorly-graded Gravel
GP


Sandy Clay
CLS


Sandy Silt
MLS


Topsoil
TOPSOIL


Partially Weathered Rock
BLDRCBBL


Silty Clay
CL-ML


Sand
SW


Trash
MUCKPEAT


High Plasticity Clay
CH


Silt
ML


Clayey Sand
SC


Fill
FILL

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-1

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-18-07 END: 7-18-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2574.23

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 48 AFTER 24 HOURS: ▼ 42.5 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)
	6-inches of TOPSOIL			
2	Stiff, light brownish-yellow, fine sandy SILT - (residuum)		2 5 6	
2570 4	Brown, micaceous, slightly clayey, sandy SILT		UD	
6	Very stiff, grayish-brown, fine sandy SILT		4 10 10	
8			4 7 9	
2565 10				
12				
2560 14	Very stiff, brown, micaceous, fine sandy SILT		4 12 13	
16				
18				
2555 20	Very stiff, brown and gray and white, micaceous, fine to medium sandy SILT with rock fragments		4 11 11	
22				
2550 24	Very stiff, grayish-brown, micaceous, fine to medium sandy SILT		9 13 13	
26				
28				
2545 30			9 13 14	
32				
2540 34	Very stiff, light brownish-white, micaceous, fine to medium sandy SILT		9 14 15	
36				
38				
2535	Hard to very stiff, brown and black, micaceous, fine to medium sandy SILT		12 16 22	

MONITOR WELL INSTALLATION DETAILS

SURFACE COMPLETION
3.57-foot stick-up

Neat cement grout, 0 to 50.6 feet

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-1

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-18-07 END: 7-18-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2574.23

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 48 AFTER 24 HOURS: ▼ 42.5 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
42	Hard to very stiff, brown and black, micaceous, fine to medium sandy SILT				
2530 / 44			5, 10, 19		
46					
48 ▽					
2525 / 50			5, 9, 12		
52					Bentonite seal, 50.6 to 52.8 feet
2520 / 54			6, 8, 15		Filter pack, sand 52.8 to 66 feet
56					
58					
2515 / 60			7, 10, 12		2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 55 to 65 feet
62					
2510 / 64	PARTIALLY WEATHERED ROCK which sampled as gray and white, micaceous, silty, fine to medium SAND		50/3"	50/3"	
66	Auger refusal at 66 feet. Groundwater encountered at 48.0 feet at time of drilling and at 42.5 feet after 24 hours.				Pipe cap
					Total well depth, 65.2 feet
2505 / 68					
70					
2500 / 72					
74					
76					
2495 / 78					

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-2

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-13-07 END: 7-13-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2525.68

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 17.1 AFTER 24 HOURS: ▼ 12.45 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)
2525 / 0	6-inches of TOPSOIL			
2	Soft, brown, fine to medium sandy, silty CLAY - (residuum)			2 2 2
4	Soft, yellowish-brown, micaceous, fine to medium sandy SILT			2 2 2
2520 / 6	Firm, blackish-brown, moist, micaceous, silty, fine SAND			4 5 6
8				3 6 11
10 / 2515				
12 ▼				
14	Soft, tan, gray and white, moist, micaceous, fine to medium sandy SILT			2 1 2
2510 / 16				
▽ 18				
20	Soft, grayish-brown, micaceous, wet, fine sandy SILT			2 1 2
2505 / 22				
24	Very firm, brown, black and gray, micaceous, silty, fine to medium SAND - saprolite			7 7 19
2500 / 26				
28				
30	Loose, gray and brown, micaceous, silt, fine to medium SAND			2 2 4
2495 / 32				
34	Very firm, micaceous, gray and brown, silty, fine to medium SAND - saprolite			5 11 15
2490 / 36				
38				
	Very firm, gray and brown, silty, fine to medium SAND			7 12 18

MONITOR WELL INSTALLATION DETAILS

SURFACE COMPLETION
3.91-foot stick-up

Neat cement, 0 to 24.4 feet

Bentonite seal, 24.4 to 26.8 feet

Filter pack, sand 26.8 to 40 feet

2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 29 to 39 feet

Pipe cap

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-2

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-13-07 END: 7-13-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2525.68

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 17.1 AFTER 24 HOURS: ▼ 12.45 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2485 – 42 – 44 – 2480 – 46 – 48 – 50 – 2475 – 52 – 54 – 2470 – 56 – 58 – 60 – 2465 – 62 – 64 – 2460 – 66 – 68 – 70 – 2455 – 72 – 74 – 2450 – 76 – 78	Boring terminated at 40 feet. Groundwater encountered at 17.1 feet at time of drilling and at 12.45 feet after 24 hours.				Total well depth, 39.2 feet

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-3

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-12-07 END: 7-12-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2519.77

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 19.5 AFTER 24 HOURS: ▼ 18.44 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)
2515 / 2	6-inches of TOPSOIL Firm, brown, silty, fine to medium SAND - (fill)			2 2 4
4	Soft, light brown, micaceous, fine sandy SILT - (fill)			2 2 2
2515 / 6	Loose, brown, silty, fine to coarse SAND - (residuum)			UD
8				2 4 5
2510 / 10				
12				
14	Very firm, brown and black, micaceous, silty, fine to coarse SAND			7 10 15
2505 / 16				
18 ▼				
▽	Loose, light gray and white, silty, fine to medium SAND			3 4 5
2500 / 20				
22				
24	Light gray and white, silty, fine to medium SAND			UD
2495 / 26				
28				
30	Very stiff, gray and brown, wet, micaceous, fine to medium sandy SILT			6 8 10
2490 / 32				
34	Dense, gray, white and black, micaceous, silty, fine to medium SAND			12 19 19
2485 / 36				
38				
2480	Very firm, dark brown, micaceous, silty, fine to medium SAND with rock fragments			9 12 12

MONITOR WELL INSTALLATION DETAILS

SURFACE COMPLETION
3.68-foot stick-up

Neat cement, 0 to 33 feet

Bentonite seal, 33 to 36 feet

Filter pack, sand 36 to 50 feet

2-inch diameter, 0.010-inch slotted Schedule 40 PVC well

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-3

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-12-07 END: 7-12-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2519.77

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 19.5 AFTER 24 HOURS: ▼ 18.44 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
42	Very firm, dark brown, micaceous, silty, fine to medium SAND with rock fragments				screen, 38 to 48 feet
44	Dense, gray, micaceous, silty, fine to medium SAND with rock fragments			13 19 28	2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 38 to 48 feet
2475					
46					
48	Very dense, white and brown, micaceous, silty, fine to medium SAND			12 26 31	Pipe cap
2470 50					Total well depth, 48.2 feet
52	Boring terminated at 50 feet. Groundwater encountered at 19.5 feet at time of drilling and at 18.44 feet after 24 hours.				
54					
2465					
56					
58					
2460					
60					
62					
64					
2455					
66					
68					
2450					
70					
72					
74					
2445					
76					
78					
2440					

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

SOIL TEST BORING NO. BLE-4

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 9-6-07 END: 9-6-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2560.09

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ _____ AFTER 24 HOURS: ▼ _____ CAVING> _____

ELEVATION/ DEPTH (FT)	SOIL DESCRIPTION	SOIL TYPE
2555 / 2	6-inches of TOPSOIL	
	No sample	
4	Auger refusal at 2.5 feet on fill boulders. Four test pits advanced to depths of 10 to 11 feet below ground surface were performed by McGill Associates on 6-4-08. The test pits encountered fill soil with numerous boulders which were found to be responsible for the auger refusal in BLE-4. Bedrock was not encountered in any test pit. No ground water encountered at time of drilling.	
6		
8		
2550 / 10		
12		
14		
2545 / 16		
18		
2540 / 20		
22		
24		
2535 / 26		
28		
2530 / 30		
32		
34		
2525 / 36		
38		

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-5

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-16-07 END: 7-16-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2497.10

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 11.3 AFTER 24 HOURS: ▼ 4.6 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)
2495 / 2	6-inches of TOPSOIL Firm, brown, silty CLAY - (residuum)		1 2 3	
4	Firm, brown, black and gray, moist, micaceous, fine sandy, clayey SILT		3 2 3	
2490 / 6	Firm, brown, moist, micaceous, fine to medium sandy SILT		1 2 3	
8	Very firm, light brown/black, moist, silty, fine to coarse SAND		5 10 12	
2485 / 10				
12				
14	Firm, gray and brown, wet, micaceous, silty, fine SAND		5 7 8	
2480 / 16				
18	PARTIALLY WEATHERED ROCK which sampled as gray and brown, silty SAND with rock fragments		50/4"	50/4"
2475 / 20				
22				
24	Dense, black and brown, micaceous, silty SAND with rock fragments		9 29 10	
2470 / 26	Auger refusal at 26 feet. Groundwater encountered at 11.3 feet at time of drilling and at 4.6 feet after 24 hours.			
28				
2465 / 30				
32				
34				
2460 / 36				
38				

MONITOR WELL INSTALLATION DETAILS

SURFACE COMPLETION
3.91-foot stick-up

Neat cement, 0 to 10.6 feet

Bentonite seal, 10.6 to 12.9 feet

Filter pack, sand 12.9 to 25.2 feet

2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 15 to 25 feet

Pipe cap

Total well depth, 25.2 feet

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-6

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 9-6-07 END: 9-6-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2532.96

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 44.65 AFTER 24 HOURS: ▼ 44.70 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2530 / 2	6-inches of TOPSOIL Firm to stiff, brown and red, slightly clayey, fine sandy SILT - (residuum)		3 3 4		SURFACE COMPLETION 3.74-foot stick-up
4	Firm to very firm, brown, red and black, silty, fine to medium SAND		4 5 6		
6			5 6 6		
2525 / 8			6 8 10		
10					
12					
2520 / 14			4 8 10		Neat cement, 0 to 27 feet
16					
2515 / 18	Firm to very firm, brown, black and gray, silty, fine to medium SAND		5 7 8		
20					
22					
2510 / 24			5 9 13		
26					
2505 / 28	Firm, gray and brown, micaceous, silty, fine SAND		5 9 10		Bentonite seal, 27 to 33.4 feet
30					
32					
2500 / 34	Stiff, gray and black, micaceous, fine sandy SILT		5 6 9		Filter pack, sand 33.4 to 46.2 feet
36					
2495 / 38	Very stiff, brown, micaceous, fine sandy SILT		5 7 10		2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 36 to 46 feet

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-6

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 9-6-07 END: 9-6-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2532.96

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 44.65 AFTER 24 HOURS: ▼ 44.70 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
42	Very stiff, brown, micaceous, fine sandy SILT				
2490	Very stiff, gray and brown, micaceous, slightly moist, fine sandy SILT			6 8 11	2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 36 to 46 feet
44 ▼					
46	GNEISS rock fragments				Pipe cap
	Auger refusal at 46 feet. Groundwater encountered at 44.65 feet at time of drilling and at 44.70 feet after 24 hours.				Total well depth, 46.2 feet
2485 48					
50					
52					
2480 54					
56					
2475 58					
60					
62					
2470 64					
66					
2465 68					
70					
72					
2460 74					
76					
2455 78					

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-7S

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-17-07 END: 7-17-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2492.12

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 10.3 AFTER 24 HOURS: ▼ 7.8 CAVING> ▨



GEOT_WELL 1957-02.GPJ 7/11/08

GROUNDWATER MONITORING WELL NO. BLE-7S

Sheet 1 of 1

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-7D

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02
CLIENT: McGill Associates — START: 9-11-07 END: 9-12-07
LOCATION: Haywood County, North Carolina — ELEVATION: 2491.92
DRILLER: Landprobe, T. Gradwell/BF — LOGGED BY: T. Livingston
DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger and NQ rock coring
DEPTH TO - WATER> INITIAL: ▽ 8.3 AFTER 24 HOURS: ▼ 8.3 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)
2490 / 2	6-inches of TOPSOIL Firm, light brown, very sandy, clayey SILT - (residuum)			3 3 5
4				2 3 3
6 / 2485	Loose, light brown, black and gray, silty SAND			2 4 5
8				
10	Firm, light brown and white, wet, silty, fine to coarse SAND			2 5 7
2480 / 12				
14	Loose, gray and brown, wet, micaceous, silty, fine to medium SAND			2 2 3
16 / 2475				
18				
20	Firm, dark brown and gray, wet, micaceous, silty, fine to medium SAND			4 5 6
2470 / 22				
24	Firm, gray and brown, micaceous, silty, fine to medium SAND			3 5 6
26 / 2465				
28				
30				
2460 / 32	Auger refusal at 32 feet. Changed over to rock coring.			R-1
34	Hard, slightly weathered, brown, dark gray and white, coarse grained QUARTZ FELDSPAR BIOTITE GNEISS; with thick foliation, very close stained fractures R-1 recovery = 42%, RQD = 25%			
36 / 2455	Very hard, fresh, brown, dark gray and white, fine to coarse grained QUARTZ FELDSPAR BIOTITE GNEISS; moderate foliation, thin foliation and close to very closely spaced stained fragments R-2 recovery = 100%, RQD = 98% R-3 recovery = 100%, RQD = 90%			R-2
38				

MONITOR WELL INSTALLATION DETAILS

SURFACE COMPLETION
3.8-foot stick-up

Neat cement, 0 to 30.2 feet

Bentonite seal, 30.2 to 46.9 feet

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-7D

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 9-11-07 END: 9-12-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2491.92

DRILLER: Landprobe, T. Gradwell/BF — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger and NQ rock coring

DEPTH TO - WATER> INITIAL: ▽ 8.3 AFTER 24 HOURS: ▼ 8.3 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2450 – 42	R-4 recovery = 90%, RQD = 83% R-5 recovery = 97%, RQD = 50% R-6 recovery = 100%, RQD = 72%		R-3		Bentonite seal, 30.2 to 46.9 feet
44					
46			R-4		
2445 – 48					Filter pack, sand 46.9 to 60 feet
50			R-5		
2440 – 52					
54					
56			R-6		2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 49.6 to 59.6 feet
2435 – 58					
60	Boring terminated at 60 feet. Groundwater encountered at 8.3 feet at time of drilling and at 8.3 feet after 24 hours.				Pipe cap
2430 – 62					Total well depth, 59.8 feet
64					
66					
2425 – 68					
70					
2420 – 72					
74					
76					
2415 – 78					

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

SOIL TEST BORING NO. BLE-8

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-18-07 END: 7-18-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2473.09

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ _____ AFTER 24 HOURS: ▼ _____ CAVING> _____

ELEVATION/ DEPTH (FT)	SOIL DESCRIPTION	SOIL TYPE
0	6-inches of TOPSOIL	
2470 / 4	Auger refusal at 3 feet. No groundwater encountered at time of drilling.	
6		
2465 / 8		
10		
12		
2460 / 14		
16		
2455 / 18		
20		
22		
2450 / 24		
26		
2445 / 28		
30		
32		
2440 / 34		
36		
2435 / 38		

GEOT_NOWELLNB 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-9

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 9-6-07 END: 9-7-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2552.54

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger and NQ rock coring

DEPTH TO - WATER> INITIAL: ▽ 42.7 AFTER 24 HOURS: ▼ 43.0 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2550 – 2	6-inches of TOPSOIL Firm to stiff, brown and gray, micaceous, fine sandy, clayey SILT - (residuum)		3 4 4	●	SURFACE COMPLETION 4.12-foot stick-up
4			4 5 5	●	
	Firm, brown, silty, fine to medium SAND				
2545 – 6			5 5 6	●	
8			5 6 7	●	
10					
2540 – 12					Neat cement, 0 to 23.6 feet
14			UD		
16					
2535 – 18					
20			5 7 8	●	
	PARTIALLY WEATHERED ROCK which sampled as gray and white, silty SAND with rock fragments				
2530 – 22					
24			50/5"	50/5" ●	
	Auger refusal at 25 feet.				
	Moderately hard, slightly weathered, brown, dark gray and white, fine to coarse grained, QUARTZ FELDSPAR BIOTITE GNEISS; with moderately developed, very thin, shallow dipping foliation, and close to very closely spaced, shallow and steeply dipping, iron stained fractures R-1 recovery = 80%, RQD = 50% R-2 recovery = 75%, RQD = 62% R-3 recovery = 92%, RQD = 68% R-4 recovery = 97%, RQD = 87%		R-1		
2525 – 26					
28					Bentonite seal, 23.6 to 35.4 feet
30			R-2		
2520 – 32					
34					
36			R-3		Filter pack, sand 35.4 to 49 feet
2515 – 38					

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-9

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 9-6-07 END: 9-7-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2552.54

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger and NQ rock coring

DEPTH TO - WATER> INITIAL: ▽ 42.7 AFTER 24 HOURS: ▼ 43.0 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2510 / 42	Moderately hard, slightly weathered, brown, dark gray and white, fine to coarse grained, QUARTZ FELDSPAR BIOTITE GNEISS; with moderately developed, very thin, shallow dipping foliation, and close to very closely spaced, shallow and steeply dipping, iron stained fractures R-1 recovery = 80%, RQD = 50% R-2 recovery = 75%, RQD = 62% R-3 recovery = 92%, RQD = 68% R-4 recovery = 97%, RQD = 87%		R-4		2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 37.7 to 47.7 feet
44					
46			R-5		
2505 / 48	Soft, moderately weathered, brown and gray, fine grained BIOTITE SCHIST; with well developed, very thin, shallow dipping foliation, shallow dipping, iron stained fracture				Pipe cap
50	Hard, very slightly weathered, brown, dark gray and white, fine to coarse grained, QUARTZ-FELDSPAR-BIOTITE GNEISS; moderately developed foliation, very closely spaced fractures R-5				Total well depth, 47.9 feet
2500 / 52	Boring terminated at 49 feet. Groundwater encountered at 42.7 feet at time of drilling and at 43.0 feet after 24 hours.				
54					
56					
2495 / 58					
60					
62					
2490 / 64					
66					
2485 / 68					
70					
72					
2480 / 74					
76					
2475 / 78					

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-10

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02
CLIENT: McGill Associates — START: 7-24-07 END: 7-26-07
LOCATION: Haywood County, North Carolina — ELEVATION: 2612.97
DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston
DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger
DEPTH TO - WATER> INITIAL: ▽ 61.5 AFTER 24 HOURS: ▼ CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2610 / 2	Firm, dark red and light brown, silty, fine to medium SAND - (residuum)		4 6 6		SURFACE COMPLETION 2.78-foot stick-up
4	Very firm, light brown, silty, fine to medium SAND		6 10 15		
6	Very stiff, dark red and light brown, slightly clayey, fine to medium sandy SILT		6 11 14		
2605 / 8			6 12 13		
10					
12					
2600 / 14			10 12 15		
16					
2595 / 18					
20			8 13 16		Neat cement, 0 to 62.7 feet
22					
2590 / 24			11 16 15		
26					
2585 / 28	Very firm, red, brown and gray, silty, fine to medium SAND		11 15 13		
30					
32	Hard, red, brown and gray, fine sandy SILT				
2580 / 34			9 16 20		
36					
2575 / 38	Very hard to hard, light brown, gray and black, fine to medium sandy SILT		11 20 37		

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-10

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-24-07 END: 7-26-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2612.97

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 61.5 AFTER 24 HOURS: ▼ _____ CAVING> _____

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
42	Very hard to hard, light brown, gray and black, fine to medium sandy SILT				
2570 / 44			10 26 26		
46					
2565 / 48			11 20 21		
50					
52					
2560 / 54			10 12 20		
56					Neat cement, 0 to 62.7 feet
2555 / 58	Very stiff, brown, white and gray, fine sandy SILT		6 14 27		
60					
▽ 62					
2550 / 64	Hard, gray, brown and white, fine sandy SILT		14 28 30		Bentonite seal, 62.7 to 66.7 feet
66					
2545 / 68	Hard to very hard, gray and brown, micaceous, moist, fine sandy SILT		13 21 25		Filter pack, sand 66.7 to 78.9 feet
70					
72					
2540 / 74			11 20 50		2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 68.7 to 78.7 feet
76					
2535 / 78					Pipe cap
	Boring terminated at 78.9 feet.				

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-10

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-24-07 END: 7-26-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2612.97

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 61.5 AFTER 24 HOURS: ▼ _____ CAVING> _____

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
82, 2530, 84, 86, 2525, 88, 90, 92, 2520, 94, 96, 98, 2515, 100, 102, 2510, 104, 106, 108, 2505, 110, 112, 2500, 114, 116, 118, 2495	Groundwater encountered at 61.5 feet at time of drilling.				Total well depth, 78.9 feet

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-11

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02
CLIENT: McGill Associates — START: 8-3-07 END: 8-3-07
LOCATION: Haywood County, North Carolina — ELEVATION: 2630.61
DRILLER: Landprobe, K. Thomas — LOGGED BY: T. Livingston
DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger
DEPTH TO - WATER> INITIAL: ▽ 89.7 AFTER 24 HOURS: ▼ 84.6 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2630 – 0	Stiff to very stiff, dark red and light brown, fine sandy SILT - (residuum)		3 4 7		SURFACE COMPLETION 3.68-foot stick-up
2					
4			3 6 9		
2625 – 6			4 6 8		
8			4 9 10		
2620 – 10					
12	Stiff, dark red and light brown, fine sandy SILT		3 5 7		
14					
2615 – 16					
18			4 5 9		
2610 – 20					Neat cement, 0 to 71.0 feet
22					
24			3 5 8		
2605 – 26					
28	Stiff to very stiff, red, light brown and black, fine sandy SILT		5 7 10		
2600 – 30					
32					
34			4 5 9		
2595 – 36					
38			7 9 12		

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-11

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02
CLIENT: McGill Associates — START: 8-3-07 END: 8-3-07
LOCATION: Haywood County, North Carolina — ELEVATION: 2630.61
DRILLER: Landprobe, K. Thomas — LOGGED BY: T. Livingston
DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger
DEPTH TO - WATER> INITIAL: ▽ 89.7 AFTER 24 HOURS: ▼ 84.6 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2590 / 42	Stiff to very stiff, red, light brown and black, fine sandy SILT				
42	Very stiff, red, brown and gray, micaceous, fine sandy SILT				
44			8 11 14		
2585 / 46					
48			3 9 12		
50 / 2580					Neat cement, 0 to 71.0 feet
52	Very stiff, white and light brown, fine sandy SILT				
54			5 10 10		
2575 / 56					
58	Hard to very stiff, red and brown, clayey, fine sandy SILT		16 22 24		
60 / 2570					
62					
64			6 10 14		
2565 / 66					
68	Very stiff, gray and brown, fine sandy SILT		2 5 11		
70 / 2560					
72					
74			8 10 12		
2555 / 76					Bentonite seal, 71.0 to 90.1 feet
78	Very stiff, gray and light brown, micaceous, fine sandy SILT		10 14 16		

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-11

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 8-3-07 END: 8-3-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2630.61

DRILLER: Landprobe, K. Thomas — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 89.7 AFTER 24 HOURS: ▼ 84.6 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2550 / 82	Very stiff, gray and light brown, micaceous, fine sandy SILT				
84	Hard, red, gray and light brown, clayey, fine sandy SILT			10, 18, 20	Bentonite seal, 71.0 to 90.1 feet
2545 / 86					
88	Very stiff to hard, gray, brown and black, micaceous, moist, fine sandy SILT			14, 16, 18	
90					
2540 / 92					Filter pack, sand 90.1 to 102.8 feet
94				8, 10, 12	
2535 / 96					
98					2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 92.6 to 102.6 feet
2530 / 100					
102					Pipe cap
104	Boring terminated at 103.0 feet. Groundwater encountered at 89.7 feet at time of drilling and at 84.6 feet after 24 hours.				Total well depth, 102.8 feet
2525 / 106					
108					
2520 / 110					
112					
114					
2515 / 116					
118					

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-12

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02
CLIENT: McGill Associates — START: 8-30-07 END: 8-31-07
LOCATION: Haywood County, North Carolina — ELEVATION: 2620.95
DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston
DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger
DEPTH TO - WATER> INITIAL: ▽ 75.9 AFTER 24 HOURS: ▼ 75.9 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2620 / 0	Stiff, red, clayey SILT - (residuum)		3 4 5		SURFACE COMPLETION 3.57-foot stick-up
2			4 4 6		
4					
2615 / 6	Stiff to very stiff, red and brown, fine sandy SILT		4 5 6		
8			5 7 9		
10					
2610 / 12					
14			5 7 8		
2605 / 16	Very stiff, red and light brown, fine sandy SILT with some clay				
18			5 8 8		
20					Neat cement, 0 to 68.3 feet
2600 / 22					
24			4 8 11		
2595 / 26					
28	Very stiff, light brown and red, fine sandy SILT		4 8 11		
30					
2590 / 32					
34	Very stiff, brown, red and black, micaceous, fine sandy SILT		5 8 11		
2585 / 36					
38			10 10 16		

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-12

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 8-30-07 END: 8-31-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2620.95

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 75.9 AFTER 24 HOURS: ▼ 75.9 CAVING>



GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-12

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 8-30-07 END: 8-31-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2620.95

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 75.9 AFTER 24 HOURS: ▼ 75.9 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2540 / 82	Hard to very hard, gray, brown and black, micaceous, fine sandy SILT				
84	Hard, gray and brown, micaceous, fine sandy SILT			8, 12, 20	
2535 / 86					
88					Filter pack, sand 77.8 to 90.2 feet
90				10, 14, 22	2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 80.0 to 90.0 feet
2530 / 92	Boring terminated at 90.2 feet. Groundwater encountered at 75.9 feet at time of drilling and at 75.9 feet after 24 hours.				Pipe cap
94					Total well depth, 90.2 feet
2525 / 96					
98					
100					
2520 / 102					
104					
2515 / 106					
108					
110					
2510 / 112					
114					
2505 / 116					
118					

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-13

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02
CLIENT: McGill Associates — START: 7-22-07 END: 7-22-07
LOCATION: Haywood County, North Carolina — ELEVATION: 2609.39
DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston
DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger
DEPTH TO - WATER> INITIAL: ▽ 69.0 AFTER 24 HOURS: ▼ 67.5 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2	Stiff, dark red and brown, silty CLAY - (residuum)		7 7 7		SURFACE COMPLETION 3.29-foot stick-up
2605 4	White and pinkish, quartz GRAVEL		13 13 13		
6	Very stiff, dark red and brown, micaceous, fine to medium sandy SILT		5 7 9		
8			9 14 15		
2600 10					
12					
2595 14	Very stiff, dark red and brown, micaceous, clayey, fine to medium sandy SILT		7 10 15		
16					
18			7 10 15		
2590 20					
22					
2585 24					
26					
28					
2580 30	Hard, dark red, red and brown, micaceous, fine to medium sandy SILT		8 16 20		Neat cement, 0 to 66.8 feet
32					
2575 34			17 20 24		
36					
38					
2570			12 18 23		

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-13

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02
CLIENT: McGill Associates — START: 7-22-07 END: 7-22-07
LOCATION: Haywood County, North Carolina — ELEVATION: 2609.39
DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston
DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger
DEPTH TO - WATER> INITIAL: ▽ 69.0 AFTER 24 HOURS: ▼ 67.5 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
42	Hard, black, brown and red, micaceous, silty, fine to medium SAND				
2565 44	Dense, dark brown, micaceous, silty, fine to medium SAND			8, 15, 20	
46					
48					
2560 50	Hard, brown and light brown, micaceous, fine sandy SILT			8, 16, 26	Neat cement, 0 to 66.8 feet
52					
2555 54	Hard to very hard, brown, black and gray, moist, fine sandy SILT			13, 22, 22	
56					
58					
2550 60				15, 20, 23	
62					
2545 64				28, 30, 33	
66					Bentonite seal, 66.8 to 69.4 feet
68 ▽					
2540 70				23, 32, 40	Filter pack, sand 69.4 to 81.6 feet
72					
2535 74	PARTIALLY WEATHERED ROCK which sampled as gray and white, silty, fine to medium SAND			26, 48, 50/3"	50/3"
76					2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 71.4 to 81.4 feet
78					
2530				43, 50/5"	50/5"

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-13

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-22-07 END: 7-22-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2609.39

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 69.0 AFTER 24 HOURS: ▼ 67.5 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
82	PARTIALLY WEATHERED ROCK which sampled as gray and white, silty, fine to medium SAND				Pipe cap
2525 84			50/3"	50/3"	Total well depth, 81.6 feet
86	Auger refusal at 86 feet. Groundwater encountered at 69.0 feet at time of drilling and at 67.5 feet after 24 hours.				
88					
2520 90					
92					
2515 94					
96					
98					
2510 100					
102					
2505 104					
106					
108					
2500 110					
112					
2495 114					
116					
118					
2490					

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-14

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 9-4-07 END: 9-4-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2610.41

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 59.1 AFTER 24 HOURS: ▼ 59.2 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2610 / 0	Stiff to very stiff, red and light brown, fine sandy SILT with some clay - (residuum)			3 4 6	SURFACE COMPLETION 3.26-foot stick-up
2					
4				4 5 7	
2605 / 6				4 4 7	
8				4 6 8	
2600 / 10					
12					
14				4 7 9	
2595 / 16					
18	Very stiff, red, brown and black, micaceous, fine sandy, clayey SILT			6 9 11	
2590 / 20					Neat cement, 0 to 45.7 feet
22					
24				5 9 12	
2585 / 26					
28				10 8 12	
2580 / 30					
32	Hard to stiff, gray, brown, micaceous, fine sandy SILT				
34				11 21 30	
2575 / 36					
38				17 28 33	

GEOT_WELL 1957-02.GPJ 7/11/08

GROUNDWATER MONITORING WELL NO. BLE-14

BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02
CLIENT: McGill Associates — START: 9-4-07 END: 9-4-07
LOCATION: Haywood County, North Carolina — ELEVATION: 2610.41
DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston
DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger
DEPTH TO - WATER> INITIAL: 59.1 AFTER 24 HOURS: 59.2 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2570 / 42	Hard to stiff, gray, brown, micaceous, fine sandy SILT				Neat cement, 0 to 45.7 feet
44				11 16 21	
2565 / 46					
48				9 12 14	
2560 / 50					
52	Very stiff to hard, brown and gray, micaceous, moist, fine sandy SILT				Bentonite seal, 45.7 to 60.3 feet
54				12 13 16	
2555 / 56					
58				14 15 18	
2550 / 60					Filter pack, sand 60.3 to 73.5 feet
62					
64				13 14 17	
2545 / 66					
68	PARTIALLY WEATHERED ROCK which sampled as gray, black and white, silty, fine to medium SAND			50/1"	2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 63.3 to 73.3 feet
2540 / 70					
72					Pipe cap
74	Auger refusal at 73.5 feet. Groundwater encountered at 59.1 feet at time of drilling and at 59.2 feet after 24 hours.				Total well depth, 73.5 feet
2535 / 76					
78					

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-15

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02
CLIENT: McGill Associates — START: 7-19-07 END: 7-20-07
LOCATION: Haywood County, North Carolina — ELEVATION: 2584.11
DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston
DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger
DEPTH TO - WATER> INITIAL: ▽ 57.75 AFTER 24 HOURS: ▼ 57.1 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
0	6-inches of TOPSOIL				SURFACE COMPLETION 3.81-foot stick-up
2	Stiff to very stiff, dark red, clayey SILT - (residuum)			5 6 8	
2580 4				3 5 8	
6				5 9 10	
8				3 4 6	
2575 10					
12					
2570 14	Very stiff to hard, brown and purple, micaceous, fine sandy SILT			5 12 15	
16					
18				9 15 18	
2565 20					
22					
2560 24	Hard, brown, fine sandy SILT			9 15 19	
26					
28					
2555	Very stiff, red and brown SILT			5 6 11	Neat cement, 0 to 59.7 feet
30					
32					
2550 34	Stiff, light brown, fine sandy SILT			4 6 6	
36					
38					
2545	Very stiff, gray and brown, micaceous, fine sandy SILT			7 8 9	

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-15

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-19-07 END: 7-20-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2584.11

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 57.75 AFTER 24 HOURS: ▼ 57.1 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
42	Very stiff, gray and brown, micaceous, fine sandy SILT				Neat cement, 0 to 59.7 feet
2540 — 44				7 9 19	
46					
48					
2535 — 50				7 9 11	
52					
2530 — 54	Very stiff, brown and gray, micaceous, fine sandy SILT with rock fragments			7 8 13	
56					
58 ▽					
2525 — 60				5 9 15	Bentonite seal, 59.7 to 62.1 feet
62					Filter pack, sand 62.1 to 75 feet
2520 — 64	Very firm, white and light brown, moist, silty, fine to medium SAND			9 12 14	
66					
68					
2515 — 70	PARTIALLY WEATHERED ROCK which sampled as gray and brown, silty, fine to medium SAND			15 22 50/6" (50/6")	2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 64.13 to 74.13 feet
72					
2510 — 74	PARTIALLY WEATHERED ROCK which sampled as orange and brown, silty, fine to medium SAND with rock fragments			14 26 50/4" (50/4")	Pipe cap
76	Boring terminated at 75 feet. Groundwater encountered at 57.75 feet at time of drilling and at 57.1 feet after 24 hours.				Total well depth, 74.33 feet
78					
2505					

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-16

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-29-07 END: 7-29-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2614.70

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 68.5 AFTER 24 HOURS: ▼ _____ CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2610 / 4	Very firm, white and light brown, silty, fine SAND - (residuum)		14 12 15 / 6 10 11		SURFACE COMPLETION 3.82-foot stick-up
2605 / 10	Very stiff, light brown, red and white, fine sandy SILT		7 7 9 / 9 10 11		
2600 / 14			8 12 15		
2595 / 20	Very stiff to hard, red, dark red and black, fine sandy SILT		7 14 15		
2590 / 24			8 10 14		
2585 / 30			9 11 18		Neat cement, 0 to 64.7 feet
2580 / 34			10 12 19		
2575 / 38			10 12 27		

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-16

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-29-07 END: 7-29-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2614.70

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 68.5 AFTER 24 HOURS: ▼ _____ CAVING> _____

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
42	Very stiff to hard, red, dark red and black, fine sandy SILT				
	Dense, light red, light brown and black, silty, fine SAND				
44 / 2570				12 20 27	
46					
	Very dense, light brown and gray, silty, fine to medium SAND				
48				12 25 30	
50 / 2565					Neat cement, 0 to 64.7 feet
52	Very dense, brown, gray and red, silty, fine to medium SAND				
54				12 15 25	
56 / 2560					
	Hard, brown and gray, fine sandy SILT				
58				9 16 24	
60 / 2555					
62					
64				10 12 20	
66 / 2550					Bentonite seal, 64.7 to 67.4 feet
68 ▽					Filter pack, sand 67.4 to 80 feet
70 / 2545				10 14 20	
72	Dense, gray and light brown, fine to medium silty SAND				
74				12 24 25	2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 68.2 to 78.2 feet
76 / 2540					
	Hard, gray and brown, fine sandy SILT				
78				8 18 32	Pipe cap
2535					Total well depth, 78.4 feet

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-16

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-29-07 END: 7-29-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2614.70

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 68.5 AFTER 24 HOURS: ▼ _____ CAVING> _____

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
82, 84, 2530, 86, 88, 2525, 90, 92, 94, 2520, 96, 98, 2515, 100, 102, 104, 2510, 106, 108, 2505, 110, 112, 114, 2500, 116, 118, 2495	Boring terminated at 80 feet. Groundwater encountered at 68.5 feet at time of drilling.				

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-17

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-20-07 END: 7-21-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2611.46

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 87.6 AFTER 24 HOURS: ▼ 73.4 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2610 / 0	6-inches of TOPSOIL				SURFACE COMPLETION 4.45-foot stick-up
2	Stiff to very stiff, red, light brown and gray, fine sandy SILT - (residuum)			4 5 6	
4				5 5 7	
2605 / 6				5 10 12	
8					
10	Very stiff to stiff, red, micaceous, clayey, fine sandy SILT			12 15 15	
2600 / 12					
14				4 5 9	
2595 / 16					
18					
20	Very stiff, red and light brown, fine sandy SILT			4 8 10	Neat cement, 0 to 85 feet
2590 / 22					
24				9 10 15	
2585 / 26					
28					
30	Very stiff, purple and brown, fine sandy SILT			6 8 14	
2580 / 32					
34	Very firm, red and light brown, silty, fine SAND			9 12 15	
2575 / 36					
38				10 16 18	

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-17

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02
CLIENT: McGill Associates — START: 7-20-07 END: 7-21-07
LOCATION: Haywood County, North Carolina — ELEVATION: 2611.46
DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston
DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger
DEPTH TO - WATER> INITIAL: ▽ 87.6 AFTER 24 HOURS: ▼ 73.4 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2570 – 42	Very firm, red and light brown, silty, fine SAND				
44	Dense, purple and red, fine sandy SILT			10, 15, 19	
2565 – 46, 48					
	Very firm, purple, light brown and black, micaceous, silty, fine to medium SAND			5, 7, 12	
50					
2560 – 52					
54				9, 12, 15	
2555 – 56					
58					
	Dense to very firm, brown, silty, fine SAND			12, 15, 17	
60					Neat cement, 0 to 85 feet
2550 – 62					
64				17, 20, 22	
2545 – 66					
68				7, 12, 15	
70					
2540 – 72					
74	Hard, gray, moist, micaceous, fine sandy SILT			10, 15, 17	
2535 – 76					
78					
	Very stiff to hard, red, brown and gray, moist, clayey, fine sandy SILT			5, 12, 17	

GEOT_WELL 1957-02.GPJ 7/11/08

BLE INC.

BUNNELL-LAMMONS ENGINEERING, INC.

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS

GROUNDWATER MONITORING WELL NO. BLE-17

PROJECT: White Oak MSW Landfill — PROJECT NO.: J07-1957-02

CLIENT: McGill Associates — START: 7-20-07 END: 7-21-07

LOCATION: Haywood County, North Carolina — ELEVATION: 2611.46

DRILLER: Landprobe, T. Gradwell — LOGGED BY: T. Livingston

DRILLING METHOD: 8-1/4 inch O.D. hollow stem auger

DEPTH TO - WATER> INITIAL: ▽ 87.6 AFTER 24 HOURS: ▼ 73.4 CAVING>

ELEVATION/ DEPTH (FT)	DESCRIPTION	SOIL TYPE	SAMPLES	STANDARD PENETRATION RESULTS BLOWS/FOOT (2 5 10 20 30 40 50 70 90)	MONITOR WELL INSTALLATION DETAILS
2530 / 82	Very stiff to hard, red, brown and gray, moist, clayey, fine sandy SILT				Neat cement, 0 to 85 feet
84			15 17 20		
2525 / 86					Bentonite seal, 85 to 87.1 feet
88 ▽					Filter pack, sand 87.1 to 101 feet
90	Firm to very dense, brown, gray and black, silty, fine to medium SAND		8 14 15		
2520 / 92					
94			10 12 14		2-inch diameter, 0.010-inch slotted Schedule 40 PVC well screen, 89.7 to 99.7 feet
2515 / 96					
98	PARTIALLY WEATHERED ROCK which sampled as brown, gray and black, silty, fine to medium SAND		34 50/5"	50/5"	
100					Pipe cap
2510 / 102	Auger refusal at 101.0 feet. Groundwater encountered at 87.6 feet at time of drilling and at 73.4 feet after 24 hours.				Total well depth, 99.9 feet
104					
2505 / 106					
108					
110					
2500 / 112					
114					
2495 / 116					
118					

GEOT_WELL 1957-02.GPJ 7/11/08

DEPTH (FT.)	DESCRIPTION	ELEVATION (FT.)
0.0	FILL, consists of stiff to very stiff moist brown fine sandy micaceous silt (ML).	
12.0	Firm moist red-brown silty micaceous fine to coarse SAND (SM).	
15.0	Stiff moist brown and orange-brown fine sandy micaceous SILT (ML).	
26.0	PARTIALLY WEATHERED ROCK (PWR), sampled as dry yellow, gray, and orange-brown silty micaceous fine to coarse sand, with trace rock fragments.	
37.2	Auger refusal encountered at 37.2 feet. Boring terminated.	

● PENETRATION - BLOWS/FOOT

0 10 20 30 40 60 80 100

23
14
18
13
11
50/4"
50/2"
50/0"

REMARKS:

Borehole dry at completion of drilling. Drillers: W.Whichard and G.Copland. Drill Rig: CME-550 ATV. Boring Type: 8" HSA.

SEE KEY SHEET FOR EXPLANATION OF SYMBOLS AND ABBREVIATIONS USED ABOVE

TEST BORING RECORD

BORING NUMBER	GWM-5
DATE DRILLED	September 15, 1993
PROJECT NUMBER	472-07913-03
PROJECT	White Oak Sanitary Landfill
PAGE 1 OF 1	

LAW ENGINEERING

DEPTH (FT.)	DESCRIPTION	ELEVATION (FT.)
0.0	Firm moist brown fine to coarse sandy micaceous SILT (ML)	
8.0	Loose wet brown, gray, and white silty micaceous fine to coarse SAND (SM), with rock fragments and boulders	
18.5	PARTIALLY WEATHERED ROCK (PWR), sampled as wet brown, gray, and white silty micaceous sand, with rock fragments	
20.1	Auger refusal encountered at 20.1 feet. Boring terminated.	

● PENETRATION - BLOWS/FOOT

0 10 20 30 40 60 80 100

8

6

9

50/6"

REMARKS:

Groundwater encountered at 9.0 feet. Type II Monitoring Well Installed. Drillers: W.Whichard and G.Copland. Drill Rig: CME-550 ATV. Boring Type: 8" HSA.

SEE KEY SHEET FOR EXPLANATION OF SYMBOLS AND ABBREVIATIONS USED ABOVE

TEST BORING RECORD

BORING NUMBER	GWM-5A
DATE DRILLED	September 25, 1993
PROJECT NUMBER	472-07913-03
PROJECT	White Oak Sanitary Landfill
PAGE 1 OF 1	

LAW ENGINEERING

TYPE II MONITORING WELL INSTALLATION RECORD

JOB NAME White Oak Landfill JOB NUMBER 472-07913-03

WELL NUMBER GWM-5A INSTALLATION DATE 09/25/93

LOCATION West Drainage Feature (See Record Drawings)

GROUND SURFACE ELEVATION _____ REFERENCE POINT ELEVATION _____

GRANULAR BACKFILL MATERIAL NC #2 sand SLOT SIZE 0.010"

SCREEN MATERIAL PVC SCREEN DIAMETER 2"

RISER MATERIAL PVC RISER DIAMETER 2"

DRILLING TECHNIQUE HSA DRILLING CONTRACTOR Law Engineering

BOREHOLE DIAMETER 8" LAW ENGINEERING FIELD REPRESENTATIVE Hoda Kablawi

LOCK BRAND Master SIZE/MODEL #3

KEY CODE/COMBINATION 0536



LAW ENGINEERING TESTING COMPANY

TYPE II MONITORING WELL INSTALLATION RECORD

FIGURE 2

DIVISION OF ENVIRONMENTAL MANAGEMENT - GROUNDWATER SECTION
P.O. BOX 27687 - RALEIGH, N.C. 27611, PHONE (919) 733-6083

Quad. No. _____ Serial No. _____
Lat. _____ Long. _____ Pc _____
Minor Basin _____
Basin Code _____
Header Ent. _____ GW-1 Ent. _____

WELL CONSTRUCTION RECORD

DRILLING CONTRACTOR Law Engineering
DRILLER REGISTRATION NUMBER 332

GWM-5A
LANDFILL CONSTRUCTION PERMIT NUMBER: 44-07

1. WELL LOCATION: (Show sketch of the location below)
Nearest Town: White Oak, North Carolina
(Road, Community, or Subdivision and Lot No.)

County: Haywood

2. OWNER Haywood County, North Carolina
ADDRESS 420 N. Main Street (Street or Route No.)
Waynesville (City or Town) NC (State) 28786 (Zip Code)

3. DATE DRILLED 9/25/93 USE OF WELL Monitoring
4. TOTAL DEPTH 20.1' CUTTINGS COLLECTED ☒ Yes ☐ No
5. DOES WELL REPLACE EXISTING WELL? ☐ Yes ☒ No
6. STATIC WATER LEVEL: 11.5' FT. ☐ above ☒ below TOP OF CASING.
TOP OF CASING IS 2.5' FT. ABOVE LAND SURFACE.
7. YIELD (gpm): N/A METHOD OF TEST N/A
WATER ZONES (depth): _____

CHLORINATION: Type N/A Amount N/A

DRILLING LOG

Depth From	Depth To	Formation Description
0'	8'	Sandy SILT
8'	18.5'	Silty sand
18.5'	20.1'	Partially weathered rock

If additional space is needed use back of form.

10. CASING:

	Depth		Diameter	Wall Thickness or Weight/Ft.	Material
From	0	To 4.5 Ft.	2"		PVC
From		To Ft.			
From		To Ft.			

11. GROUT:

	Depth		Material	Method
From	0	To 2.5 Ft.	Cem-Bent	Tremie
From		To Ft.		

12. SCREEN:

	Depth		Diameter	Slot Size	Material
From	4.5	To 19.5 Ft.	2" in.	0.010 in.	PVC
From		To Ft.	in.	in.	
From		To Ft.	in.	in.	

13. GRAVEL PACK:

	Depth		Size	Material
From	3.5'	To 20.1 Ft.		NC#2 sand
From		To Ft.		

14. REMARKS: Bentonite 2.5' to 3.5'

LOCATION SKETCH
(Show direction and distance from at least two State Road or other map reference points)

I DO HEREBY CERTIFY THAT THIS WELL WAS CONSTRUCTED IN ACCORDANCE WITH 15 NCAC 2C. WELL CONSTRUCTION STANDARDS, AND THAT A COPY OF THIS RECORD HAS BEEN PROVIDED TO THE WELL OWNER.

Thomas M. Schifferli — 10/1/93
SIGNATURE OF CONTRACTOR OR AGENT — DATE

GW-1 Revised 11/84
Submit original to Division of Environmental Management and copy to well owner

DEPTH (FT.)	DESCRIPTION	ELEVATION (FT.)	● PENETRATION - BLOWS/FOOT
0.0	Overburden Soils (Brown silty sand) See Boring GWM-5A for detailed soil descriptions		0 10 20 30 40 60 80 100
20.0	Hard Rock (Brown)		
36.2	Boring terminated at 36.2 feet		



REMARKS:

Groundwater measured at 6.1 feet after stabilization. Type II Monitoring Well Installed. Driller: Caldwell Well Drilling. Drill Rig: Truck-Mount Driltech D25. Boring Type: 6-1/4" Air-Rotary.

SEE KEY SHEET FOR EXPLANATION OF SYMBOLS AND ABBREVIATIONS USED ABOVE

TEST BORING RECORD

BORING NUMBER	GWM-5D
DATE DRILLED	September 29, 1993
PROJECT NUMBER	472-07913-03
PROJECT	White Oak Sanitary Landfill
PAGE 1 OF 1	

LAW ENGINEERING

TYPE II MONITORING WELL INSTALLATION RECORD

JOB NAME White Oak Landfill — JOB NUMBER 472-07913-03

WELL NUMBER GWM-5D — INSTALLATION DATE 9/29/93 & 9/30/93

LOCATION West Drainage Feature (See Record Drawings)

GROUND SURFACE ELEVATION _____ — REFERENCE POINT ELEVATION _____

GRANULAR BACKFILL MATERIAL NC #2 Sand — SLOT SIZE 0.010"

SCREEN MATERIAL PVC — SCREEN DIAMETER 2"

RISER MATERIAL PVC — RISER DIAMETER 2"

DRILLING TECHNIQUE Air-Rotary — DRILLING CONTRACTOR Caldwell

BOREHOLE DIAMETER 6 1/4" — LAW ENGINEERING FIELD REPRESENTATIVE T. Schipporeit

LOCK BRAND Master — SIZE/MODEL #3

KEY CODE/COMBINATION 0536



LAW ENGINEERING TESTING COMPANY

TYPE II MONITORING WELL INSTALLATION RECORD

FIGURE 2

North Carolina - Department of Environment, Health, and Natural Resources
Division of Environmental Management - Groundwater Section
P.O. Box 29535 - Raleigh, N.C. 27626-0535
Phone (919) 733-3221

FOR OFFICE USE ONLY
QUAD. NO. _____ SERIAL NO. _____
Lat. _____ Long. _____ Pc _____
Minor Basin _____
Basin Code _____
Header Ent. _____ GW-1 Ent.

WELL CONSTRUCTION RECORD

GWM-5D

DRILLING CONTRACTOR: Caldwell

LANDFILL . CONSTRUCTION

DRILLER REGISTRATION NUMBER: 99 PERMIT NUMBER: 44-07

1. WELL LOCATION: (Show sketch of the location below)
   Nearest Town: White Oak County: Haywood
   (Road, Community, or Subdivision and Lot No.)
2. OWNER Haywood County, North Carolina
   ADDRESS 420 N. Main Street
   (Street or Route No.)
   Waynesville NC 28786
   City or Town State Zip Code
3. DATE DRILLED 9/29/93 USE OF WELL Monitoring
4. TOTAL DEPTH 36.2'
5. CUTTINGS COLLECTED YES [ ] NO [X]
6. DOES WELL REPLACE EXISTING WELL? YES [ ] NO [X]
7. STATIC WATER LEVEL Below Top of Casing: 7.7 FT.
   (Use "+" if Above Top of Casing)
8. TOP OF CASING IS 1.6 FT. Above Land Surface*

* Casing Terminated at/or below land surface is illegal unless a variance is issued in accordance with 15A NCAC 2C .0118

9. YIELD (gpm): N/A METHOD OF TEST N/A
10. WATER ZONES (depth): _____
11. CHLORINATION: Type N/A Amount N/A
12. CASING:

	Depth From	Depth To	Diameter	Wall Thickness or Weight/Ft.	Material
	0	25.7 Ft.	2"		PVC
		Ft.			
		Ft.			

13. GROUT:

	Depth From	Depth To	Material	Method
	0	23.5 Ft.	Cement-Bent.	Tremie
		Ft.		

14. SCREEN:

	Depth From	Depth To	Diameter	Slot Size	Material
	25.7	35.7 Ft.	2 in.	0.010 in.	PVC
		Ft.	in.	in.	
		Ft.	in.	in.	

15. SAND/GRAVEL PACK:

	Depth From	Depth To	Size	Material
	24.5	36.2 Ft.		NC #2 Sand
		Ft.		

16. REMARKS: Bentonite 23.5' to 24.5'

DEPTH From	DEPTH To	DRILLING LOG Formation Description
0'	20'	Silty sand
20'	36.2'	Hard Rock

If additional space is needed use back of form

LOCATION SKETCH
(Show direction and distance from at least two State Roads, or other map reference points)

I DO HEREBY CERTIFY THAT THIS WELL WAS CONSTRUCTED IN ACCORDANCE WITH 15A NCAC 2C, WELL CONSTRUCTION STANDARDS, AND THAT A COPY OF THIS RECORD HAS BEEN PROVIDED TO THE WELL OWNER.

Thomas M. Schifferli 10-4-93
SIGNATURE OF CONTRACTOR OR AGENT DATE

GW-1 REV. 5/91

Submit original to Division of Environmental Management and copy to well owner.

LOG OF BORING: P-4

Project: Haywood County
Project No. G98010.5
HSA SS NQ

Drilling Contractor: Graham & Currie
Registration Number: 537

Surface Elevation: 2571.66ft
Top of Casing: 2573.73ft

DEPTH (ft)	BLOWS PER FOOT	SYMBOL	SAMPLES	DESCRIPTION OF MATERIAL
	8			Topoil top 2"
				CLAYEY SILT (ML); red to brown, firm, with sand and small white and black rock fragments
5	20			SANDY SILT (ML); medium dense, saprolite, medium to coarse grained, trace clay
10	29			-grades with thin veins and rock fragments
15	30			SILTY SAND (SM); red-brown and white, medium dense, fine sand, saprolite, some fragments
	41			PARTIALLY WEATHERED ROCK, fine and coarse layers
25	58			-grades with rock fragments, highly fractured quartz vein
30	91			-rock fragments
35	50/4			SANDY SILT (ML); tan orange, dense, saprolite, iron staining on relict minerals, some mica, trace clay
40	43			
45	50/4			-grades to phyllitic texture

PIEZOMETER DIAGRAM



Completion Depth: 81ft
DATE: 5/9/98

Depth to Water: 62 ft WD

MUNICIPAL ENGINEERING SERVICES COMPANY, P.A.

LOG OF BORING: P-4

Project: Haywood County
Project No. G98010.5
Type: HSA SS NQ

Drilling Contractor: Graham & Currie
Registration Number: 537

Surface Elevation: 2571.66ft
Top of Casing: 2573.73ft



Completion Depth: 81ft
DATE: 5/9/98

Depth to Water: 62 ft WD

MUNICIPAL ENGINEERING SERVICES COMPANY, P.A.

LOG OF BORING: P-5

Project: Haywood County
Project No. G98010.5
HSA SS AH

Drilling Contractor: Graham & Currie
Registration Number: 537

Surface Elevation: 2485.54ft
Top of Casing: 2488.38ft



Completion Depth: 52.3ft
DATE: 5/25/98

Depth to Water: 25 ft WD

MUNICIPAL ENGINEERING SERVICES COMPANY, P.A.

LOG OF BORING: P-5

Project: Haywood County
Project No. G98010.5
HSA SS AH

Drilling Contractor: Graham & Currie
Registration Number: 537

Surface Elevation: 2485.54ft
Top of Casing: 2488.38ft

DEPTH (ft)	BLOWS PER FOOT	SYMBOL	SAMPLES	DESCRIPTION OF MATERIAL	PIEZOMETER DIAGRAM
45					gravel pack
50					2" sch40 PVC .010 slotted screen
				End of Boring at 52.3 feet	
55					
60					
65					
70					
75					
80					

Completion Depth: 52.3ft
DATE: 5/25/98

Depth to Water: 25 ft WD

MUNICIPAL ENGINEERING SERVICES COMPANY, P.A.

LOG OF BORING: P-6

Project: Haywood County
Project No. G98010.5
HSA SS AH

Drilling Contractor: Graham & Currie
Registration Number: 537

Surface Elevation: 2594.19ft
Top of Casing: 2597.24ft



Completion Depth: 67.5ft
DATE: 5/25/98

Depth to Water: 59 ft WD

MUNICIPAL ENGINEERING SERVICES COMPANY, P.A.

LOG OF BORING: P-6

Project: Haywood County
Project No. G98010.5
HSA SS AH

Drilling Contractor: Graham & Currie
Registration Number: 537

Surface Elevation: 2594.19ft
Top of Casing: 2597.24ft



Completion Depth: 67.5ft
DATE: 5/25/98

Depth to Water: 59 ft WD

MUNICIPAL ENGINEERING SERVICES COMPANY, P.A.

APPENDIX D

PIEZOMETER INSTALLATION PROCEDURES

APPENDIX D

PIEZOMETER INSTALLATION PROCEDURES

Groundwater piezometers were installed in the boreholes resulting from the drilling process. Approximate well locations are shown on the attached Piezometer/Boring Location Plan (Figure 3).

The piezometer consists of 2-inch diameter PVC pipe (Schedule 40 with flush-threaded joints) inserted into a 8.25-inch diameter augured borehole. The bottom 5 to 10-foot section of each piezometer was a manufactured screen with 0.010-inch slots. Washed sand backfill was placed around the outside of the pipe to at least 1 to 2 feet above the top of the well screen. A bentonite seal (minimum 2-foot thick) was installed on top of the sand backfill. A cement-bentonite grout mixture was tremied from the top the bentonite seal up to the ground surface. A PVC cap was placed over the PVC well stickup on each piezometer. Piezometer construction records are attached in Appendix C.

APPENDIX E

PRECIPITATION AND GROUNDWATER LEVEL DATA AND CHARTS

MONTHLY PRECIPITATION DATA - 1992 TO 2008

North Carolina Division 1
White Oak MSW Landfill
Haywood Co., North Carolina
BLE Job Number J07-1957-02

	Year																	
MONTH	**1992**	**1993**	**1994**	**1995**	**1996**	**1997**	**1998**	**1999**	**2000**	**2001**	**2002**	**2003**	**2004**	**2005**	**2006**	**2007**	**2008**	**Monthly Avg.**
January	3.62	5.55	6.08	7.93	8.98	5.41	10.99	6.61	4.3	3.62	4.97	2.18	2.08	2.67	5.27	4.8	3.68	5.22
February	4.43	3.23	5.49	5.12	3.88	5.43	7.6	4.68	2.67	3.49	1.65	6.03	4.61	3.8	2.35	1.81	3.47	4.10
March	4.65	7.26	9.13	3.79	5.19	7.87	4.74	3.79	4.57	5.28	5.86	5.15	2.66	4.65	1.78	4.12	5.18	5.04
April	3.83	3.9	5	1.68	3.91	5.96	8.09	3.82	6.26	1.73	2.32	6.32	3.52	4.47	4.7	2.61	3.04	4.19
May	5.96	3.96	2.71	4.57	4.09	3.69	3.25	3.9	3.17	3.46	4.7	9.88	4.78	2.87	2.71	1.48		4.07
June	6.17	2.19	7.57	7.26	4.66	6.85	5.55	5.58	3.99	5.07	3.62	5.74	6.7	8.59	5.37	4.03		5.56
July	2.9	2.79	6.47	3.64	4.77	4.05	2.69	4.44	4.01	6.13	3.46	8.43	6.88	8.7	4.04	4.56		4.87
August	7.45	4.17	7.91	7.96	6.56	0.93	2.56	2.2	3.47	3.83	3.45	6.33	4.43	7.28	5.27	2.17		4.75
September	4.4	3.57	3.9	3.3	6.55	6.51	1.98	2.57	4.19	4.9	7.66	4.64	16	0.9	7.39	2.85		5.08
October	4.75	1.64	4.59	7.35	1.45	4.4	2.82	3.55	0.06	1.48	4.15	2.25	1.83	3.1	4.35	3.21		3.19
November	7.89	4.14	3.56	4.82	5.07	2.22	3.19	4.73	4.85	1.76	4.95	5.82	6.13	4.77	4.65	2.23		4.42
December	5.53	4.73	2.99	2.19	5.58	3.7	4.78	2.44	2.73	3.04	6.47	4.17	4.64	4.57	4.18	4.67		4.15
SEASON																		**Seasonal Avg.**
Winter	12.7	16.04	20.7	16.84	18.05	18.71	**23.33**	15.08	11.54	12.39	12.48	13.36	9.35	11.12	9.4	10.73	12.33	14.36
Spring	15.96	10.05	15.28	13.51	12.66	16.5	16.89	13.3	13.42	10.26	10.64	**21.94**	15	15.93	12.78	8.12		13.89
Summer	14.75	10.53	18.28	14.9	17.88	11.49	7.23	9.21	11.67	14.86	14.57	19.4	**27.31**	16.88	16.7	9.58		14.70
Fall	**18.17**	10.51	11.14	14.36	12.1	10.32	10.79	10.72	7.64	6.28	15.57	12.24	12.6	12.44	13.18	10.11		11.76
Yearly Totals	61.58	47.13	65.40	59.61	60.69	57.02	58.24	48.31	44.27	43.79	53.26	66.94	64.26	56.37	52.06	38.54		**Yearly Avg.** 54.64

Data Source: NOAA, public information - Updated through March 2008.

PALMER DROUGHT SEVERITY INDEX

North Carolina Division 1
White Oak MSW Landfill
Haywood County, NC
BLE Project Number J07-1957-02



APPENDIX F

SLUG TEST PROCEDURES AND RESULTS

APPENDIX F

SLUG TEST PROCEDURES AND RESULTS

Slug tests were performed in the field to estimate the average hydraulic conductivity of the upper formation material. Hydraulic conductivity is a constant of proportionality relating to the ease with which a fluid passes through a porous medium. These data were used to estimate the groundwater flow velocities of groundwater beneath the site. The field procedure was as follows:

- Measure the static groundwater elevation in the well to be tested.
- Affect an instantaneous change to the static water level in the well by removing a known volume of water.
- Measure the rate at which shown on the attached sheets the water level recovers to its original level.

The resulting slug test data (time versus water level) was reduced and hydraulic conductivity values were calculated using the Bouwer and Rice Method for partially-penetrating wells in an unconfined aquifer.

Rising Head Slug Test 9/26/07

White Oak Landfill Haywood County, NC

Bouwer and Rice Graph

BLE-3



Project Number J07-1957-02 for McGill Associates

Analysis by Bunnell-Lammons Engineering, Inc.

Ho is 2.598 feet at 79.98 seconds

Rising Head Slug Test 9/26/07

White Oak Landfill Haywood County, NC

Bouwer and Rice Graph

BLE-7



Project Number J07-1957-02 for McGill Associates

Analysis by Bunnell-Lammons Engineering, Inc.

Ho is 12.01 feet at 100. seconds

Falling Head Slug Test 9/26/07

White Oak Landfill Haywood County, NC

Bouwer and Rice Graph

BLE-7D



Project Number J07-1957-02 for McGill Associates

Analysis by Bunnell-Lammons Engineering, Inc.

Ho is 4.141 feet at 70.02 seconds

Rising Head Slug Test 9/26/07

White Oak Landfill Haywood County, NC

Bouwer and Rice Graph

BLE-9



Project Number J07-1957-02 for McGill Associates

Analysis by Bunnell-Lammons Engineering, Inc.

Ho is 1.871 feet at 40.98 seconds

Rising Head Slug Test 9/26/07

White Oak Landfill Haywood County, NC

Bouwer and Rice Graph

BLE-11



Ho is 3.212 feet at 1500 seconds

Project Number J07-1957-02 for McGill Associates

Analysis by Bunnell-Lammons Engineering, Inc.

Falling Head Slug Test 9/26/07

White Oak Landfill Haywood County, NC

Bouwer and Rice Graph

BLE-14



Project Number J07-1957-02 for McGill Associates

Analysis by Bunnell-Lammons Engineering, Inc.

Ho is 5.481 feet at 110. seconds

APPENDIX G

SOIL LABORATORY TEST PROCEDURES

APPENDIX G

SOIL LABORATORY TEST PROCEDURES

MOISTURE CONTENT AND UNIT WEIGHT

An undisturbed sample is trimmed in the laboratory into a right circular cylinder approximately three to six inches long. The dimensions and weight of the specimen are determined and the total unit weight calculated. Moisture contents are determined from representative portions of the specimen. The soil is dried to a constant weight in an oven at 100 degrees C and the loss of moisture during the drying process is measured. From this data, the moisture content and dry unit weight are computed.

ATTERBERG LIMITS

The Atterberg Limits Tests, Liquid Limit (LL), and Plastic Limit (PL), are performed to aid in the classification of soils and to determine the plasticity and volume change characteristics of the materials. The Liquid Limit is the minimum moisture content at which a soil will flow as a heavy viscous fluid. The Plastic Limit is the minimum moisture content at which the solid behaves as a plastic material. The Plasticity Index (PI) is the numeric difference of Liquid Limit and the Plastic Limit and indicated the range of moisture content over which a soil remains plastic. These tests are performed in accordance with ASTM D 4318.

PARTICLE SIZE DISTRIBUTION

The distribution of soils coarser than the No. 200 (75-um) sieve is determined by passing a representative specimen through a standard set of nested sieves. The weight of material retained on each sieve is determined and the percentage retained (or passing) is calculated. A specimen may be washed through only the No. 200 sieve, if the full range of particle sizes is not required. The percentage of material passing the No. 200 sieve is reported. The distribution of materials finer than No. 200 sieve is determined by use of the hydrometer. The particle sizes and distribution are computed from the time rate of settlement of the different size particles while suspended in water. These tests are performed in accordance with ASTM D 421, D 422, and D 1140.

HYDRAULIC CONDUCTIVITY

The ease with which water flows through a soil is characterized by its hydraulic conductivity. Two general test methods are employed depending on the soil type.

The **Constant Head** method is used for coarse-grained materials (sands and gravels). The sample is confined in permeameter chamber while water is allowed to flow through it from a constant head level. The quantity of water flowing through the specimen in a given time period is used to calculate the hydraulic conductivity. See ASTM D 2434 for a complete description of this test.

Fine-grained materials (silts and clays) require the use of a **Flexible Wall Permeameter**. The sample is prepared in a similar manner as in the triaxial compression test. It is encased in a rubber membrane and place inside a permeameter chamber. The specimen is back-pressure saturated and allowed to consolidate under a specified effective stress. Water is then forced through the specimen under a controlled hydraulic gradient. The quantity of water flowing into the sample in a

given time period is used to calculate the hydraulic conductivity. This test is performed in general accordance wit ASTM D 5084.

COMPACTION

Bulk samples of potential borrow soils from the project site were collected and transported to the laboratory for compaction testing. A standard Proctor compaction test (ASTM D 698) was performed on each sample to determine compaction characteristics, including the maximum dry density and optimum moisture content. Test results are presented on the attached Compaction Test sheet.

CONSOLIDATION

A single section of the undisturbed sample was extruded from its sampling tube for consolidation testing. The sample was then trimmed into a disc 2.4 inches in diameter and 1 inch thick. The disc was confined in a stainless steel ring and sandwiched between porous plates. It was then subjected to incrementally increasing vertical loads and the resulting deformations measured with a micrometer dial gauge. The test results are presented in the form of a pressure versus percent strain curve on the accompanying Consolidation Test sheet.

TRIAXIAL SHEAR

Multi-stage consolidated undrained triaxial compression tests were conducted on relatively undisturbed soil samples. Each sample was trimmed and the initial moisture content and unit weight was determined. The trimmed sample was placed into a waterproof membrane and loaded into the test cell. The sample was subjected to an assigned confining pressure and allowed to consolidate. The sample was then subjected to an axial compressive load, which was gradually increased until incipient failure, at which point the confining pressure was increased and the process repeated. Pore pressures were measured during the test to permit determination of the total stress and effective stress parameters. The test results are used to estimate the strength parameters of the soil (angle of internal friction and cohesion). The test results are presented in the form of Stress-Strain Curves and Mohr Diagrams on the accompanying Triaxial Shear Test sheets.

APPENDIX H

SOIL LABORATORY TEST RESULTS

BLE INC.

HYDRAULIC CONDUCTIVITY TEST REPORT

CONSTANT VOLUME APPARATUS (ASTM D 5084)

WHITE OAK LANDFILL

PROJECT: HAYWOOD COUNTY, NC
PROJECT NO.: J07-1957-02
DATE RECEIVED: 11-2-07

TESTED BY: JOHN MATHEW
CHECKED BY: PAUL YARBER

SAMPLE NO. BLE-1
TYPE UNDISTURBED
SAMPLE LOCATION: 3.5-5.5'
SAMPLE DESCRIPTION: TAN FI. SANDY CLAYEY SILT

SAMPLE DIMENSIONS AND PROPERTIES

ITEM	INITIAL		FINAL	
	inches	centimeters	inches	centimeters
Sample Length	2.902	7.371	2.989	7.592
Sample Diameter	2.853	7.247	2.872	7.295
Length/Diameter Ratio		1.02		
Moisture Content (%)	WW= 158.2 DW= 119.8	32.1	WW= 231.5 DW= 174.1	33.0
Sample Wet Weight (grams)	569.9		593.0	
Wet Density (pcf)	117.0		116.7	
Dry Density (pcf)	88.6		87.7	
Saturation (%) ASSUMED SG= 2.722	95		96	

HYDRAULIC CONDUCTIVITY TESTING MEASUREMENT

FALLING HEAD TEST

Confining Pressure (psi) 64.2 | Influent Pressure (psi) 60.2 | Effluent Pressure (psi) 60

Date	Clock Time		Elapsed Time	Pipet Readings				Head		Temp	Gradient	K	Temp	K_{20}
				Initial		Final		Initial	Final					
	Start	End	seconds	in	out	in	out	cm	cm	°C		(cm/sec)	Correction	(cm/sec)
11-9-07	5:00:0	5:00:34	34	1.0	23.0	3.0	21.0	40.092	35.361	21	5	2.8E-04	0.976	2.7E-04
11-9-07	5:00:34	5:01:15	41	3.0	21.0	5.0	19.0	35.361	30.629	21	4	2.6E-04	0.976	2.6E-04
11-9-07	5:01:15	5:02:03	48	5.0	19.0	7.0	17.0	30.629	25.897	21	4	2.6E-04	0.976	2.6E-04
11-9-07	5:02:03	5:03:00	57	7.0	17.0	9.0	15.0	25.897	21.166	21	3	2.7E-04	0.976	2.6E-04
		Pipet Length, cm		28.390	28.390									
		Pipet Volume, cc		24	24									
		Cross-sectional Area of Pipet, cm^2		0.8454	0.8454									

HYDRAULIC CONDUCTIVITY (k) 2.6E-04 cm/sec

BLE INC.

HYDRAULIC CONDUCTIVITY TEST REPORT

CONSTANT VOLUME APPARATUS (ASTM D 5084)

WHITE OAK LANDFILL

PROJECT: HAYWOOD COUNTY, NC
PROJECT NO.: J07-1957-02
DATE RECEIVED: 11-2-07

TESTED BY: JOHN MATHEW
CHECKED BY: PAUL YARBER

SAMPLE NO. BLE-3
TYPE UNDISTURBED
SAMPLE LOCATION: 6.0-8.0'
SAMPLE DESCRIPTION: BROWN SILTY FI.-CO. SAND

SAMPLE DIMENSIONS AND PROPERTIES

ITEM	INITIAL		FINAL	
	inches	centimeters	inches	centimeters
Sample Length	2.898	7.361	2.902	7.371
Sample Diameter	2.850	7.239	2.874	7.300
Length/Diameter Ratio		1.02		
Moisture Content (%)	WW= 184.7 DW= 153.4	20.4	WW= 264.0 DW= 212.4	24.3
Sample Wet Weight (grams)	598.3		621.7	
Wet Density (pcf)	123.3		125.8	
Dry Density (pcf)	102.4		101.2	
Saturation (%) ASSUMED SG= 2.71	85		98	

HYDRAULIC CONDUCTIVITY TESTING MEASUREMENT

FALLING HEAD TEST

Confining Pressure (psi) 66.2 | Influent Pressure (psi) 60.2 | Effluent Pressure (psi) 60

Date	Clock Time		Elapsed Time	Pipet Readings				Head		Temp	Gradient	K	Temp	K_{20}
				Initial		Final		Initial	Final					
	Start	End	seconds	in	out	in	out	cm	cm	°C		(cm/sec)	Correction	(cm/sec)
11-9-07	3:37:00	3:37:24	24	1.0	23.0	2.0	22.0	40.092	37.726	21	5	1.9E-04	0.976	1.9E-04
11-9-07	3:37:24	3:37:49	25	2.0	22.0	3.0	21.0	37.726	35.361	21	5	2.0E-04	0.976	1.9E-04
11-9-07	3:37:47	3:38:16	29	3.0	21.0	4.0	20.0	35.361	32.995	21	5	1.8E-04	0.976	1.8E-04
11-9-07	3:38:16	3:38:46	30	4.0	20.0	5.0	19.0	32.995	30.629	21	4	1.9E-04	0.976	1.8E-04
		Pipet Length, cm		28.390	28.390									
		Pipet Volume, cc		24	24									
		Cross-sectional Area of Pipet, cm^2		0.8454	0.8454									

HYDRAULIC CONDUCTIVITY (k) 1.8E-04 cm/sec

BLE INC.

HYDRAULIC CONDUCTIVITY TEST REPORT

CONSTANT VOLUME APPARATUS (ASTM D 5084)

	WHITE OAK LANDFILL		
PROJECT:	HAYWOOD COUNTY, NC	TESTED BY:	JOHN MATHEW
PROJECT NO.:	J07-1957-02	CHECKED BY:	PAUL YARBER
DATE RECEIVED:	11-2-07		

SAMPLE NO.	BLE-3	SAMPLE LOCATION:	23.5-25.0'
TYPE	UNDISTURBED	SAMPLE DESCRIPTION:	LIGHT GREY & WHITE SILTY FI.-MED. SAND

SAMPLE DIMENSIONS AND PROPERTIES

ITEM	INITIAL		FINAL	
	inches	centimeters	inches	centimeters
Sample Length	2.957	7.511	2.920	7.417
Sample Diameter	2.856	7.254	2.860	7.264
Length/Diameter Ratio		1.04		
Moisture Content (%)	WW= 175.5 DW= 133.4	31.6	WW= 204.9 DW= 161.7	26.7
Sample Wet Weight (grams)	588.7		592.3	
Wet Density (pcf)	118.4		120.3	
Dry Density (pcf)	90.0		94.9	
Saturation (%) ASSUMED SG= 2.689	98		94	

HYDRAULIC CONDUCTIVITY TESTING MEASUREMENT

FALLING HEAD TEST

Confining Pressure (psi) 78.2 | Influent Pressure (psi) 60.2 | Effluent Pressure (psi) 60

Date	Clock Time		Elapsed Time	Pipet Readings				Head		Temp	Gradient	K	Temp	K_{20}
				Initial		Final		Initial	Final					
	Start	End	seconds	in	out	in	out	cm	cm	°C		(cm/sec)	Correction	(cm/sec)
11-9-07	4:13:00	4:15:06	126	1.0	23.0	2.0	22.0	40.092	37.726	21	5	3.7E-05	0.976	3.6E-05
11-9-07	4:15:06	4:17:22	136	2.0	22.0	3.0	21.0	37.726	35.361	21	5	3.7E-05	0.976	3.6E-05
11-9-07	4:17:22	4:19:50	148	3.0	21.0	4.0	20.0	35.361	32.995	21	5	3.6E-05	0.976	3.5E-05
11-9-07	4:19:50	4:22:31	161	4.0	20.0	5.0	19.0	32.995	30.629	21	4	3.5E-05	0.976	3.5E-05
		Pipet Length, cm		28.390	28.390									
		Pipet Volume, cc		24	24									
		Cross-sectional Area of Pipet, cm^2		0.8454	0.8454									

HYDRAULIC CONDUCTIVITY (k) 3.5E-05 cm/sec

BLE INC.

HYDRAULIC CONDUCTIVITY TEST REPORT

CONSTANT VOLUME APPARATUS (ASTM D 5084)

PROJECT:	WHITE OAK LANDFILL HAYWOOD COUNTY, NC	TESTED BY:	JOHN MATHEW
PROJECT NO.:	J07-1957-02	CHECKED BY:	PAUL YARBER
DATE RECEIVED:	11-2-07		

SAMPLE NO.	BLE-7	SAMPLE LOCATION:	1.0-3.0'
TYPE	UNDISTURBED	SAMPLE DESCRIPTION:	LIGHT BROWN FI.-MED. SANDY CLAYEY SILT

SAMPLE DIMENSIONS AND PROPERTIES

ITEM	INITIAL		FINAL	
	inches	centimeters	inches	centimeters
Sample Length	2.978	7.564	2.952	7.498
Sample Diameter	2.854	7.249	2.858	7.259
Length/Diameter Ratio		1.04		
Moisture Content (%)	WW= 146.9 DW= 108.5	35.4	WW= 264.9 DW= 186.2	42.3
Sample Wet Weight (grams)	563.1		580.1	
Wet Density (pcf)	112.6		116.7	
Dry Density (pcf)	83.2		82.0	
Saturation (%) ASSUMED SG= 2.708	93		108	

HYDRAULIC CONDUCTIVITY TESTING MEASUREMENT

(PERMOMETER)

Confining Pressure (psi) 72 | Influent Pressure (psi) 70 | Effluent Pressure (psi) 70

Reset (Y/N)	Date	Clock Time	Elapsed Time	HA_{OUT} (cm)	HA_{IN} (cm)	Temp °C	Gradient	K (cm/sec)	Temp Correction	K_{20} (cm/sec)
Y	11-8-07	4:18:06		4.8	2.20	21	5			
	11-8-07	4:18:32	0:00:26	3.5	2.25	21	3	1.2E-05	0.976	1.1E-05
	11-8-07	4:18:40	0:00:34	3.3	2.26	21	2	1.1E-05	0.976	1.1E-05
	11-8-07	4:18:55	0:00:49	3.0	2.27	21	2	1.1E-05	0.976	1.0E-05
	11-8-07	4:19:10	0:01:04	2.8	2.28	21	1	1.0E-05	0.976	1.0E-05

HYDRAULIC CONDUCTIVITY (k) 1.1E-05 cm/sec

BLE INC.

HYDRAULIC CONDUCTIVITY TEST REPORT

CONSTANT VOLUME APPARATUS (ASTM D 5084)

	WHITE OAK LANDFILL		
PROJECT:	HAYWOOD COUNTY, NC	TESTED BY:	JOHN MATHEW
PROJECT NO.:	J07-1957-02	CHECKED BY:	PAUL YARBER
DATE RECEIVED:	11-2-07		

SAMPLE NO.	BLE-9	SAMPLE LOCATION:	13.5-15.5'
TYPE	UNDISTURBED	SAMPLE DESCRIPTION:	GREY & BROWN SILTY FI.-MED. SAND

SAMPLE DIMENSIONS AND PROPERTIES

ITEM	INITIAL		FINAL	
	inches	centimeters	inches	centimeters
Sample Length	2.952	7.498	2.956	7.508
Sample Diameter	2.850	7.239	2.846	7.229
Length/Diameter Ratio		1.04		
Moisture Content (%)	WW= 179.7 DW= 145.1	23.8	WW= 248.1 DW= 186.0	33.4
Sample Wet Weight (grams)	521.5		569.5	
Wet Density (pcf)	105.5		115.4	
Dry Density (pcf)	85.2		86.5	
Saturation (%) ASSUMED SG= 2.752	65		93	

HYDRAULIC CONDUCTIVITY TESTING MEASUREMENT

FALLING HEAD TEST

Confining Pressure (psi) 82.2 | Influent Pressure (psi) 70.2 | Effluent Pressure (psi) 70

Date	Clock Time		Elapsed Time	Pipet Readings				Head		Temp	Gradient	K	Temp	K_{20}
				Initial		Final		Initial	Final					
	Start	End	seconds	in	out	in	out	cm	cm	°C		(cm/sec)	Correction	(cm/sec)
11-9-07	3:50:10	3:50:31	21	1.0	23.0	2.0	22.0	40.092	37.726	21	5	2.2E-04	0.976	2.2E-04
11-9-07	3:50:31	3:50:53	22	2.0	22.0	3.0	21.0	37.726	35.361	21	5	2.3E-04	0.976	2.2E-04
11-9-07	3:50:53	3:51:17	24	3.0	21.0	4.0	20.0	35.361	32.995	21	5	2.2E-04	0.976	2.2E-04
11-9-07	3:51:17	3:51:44	27	4.0	20.0	5.0	19.0	32.995	30.629	21	4	2.1E-04	0.976	2.1E-04
		Pipet Length, cm		28.390	28.390									
		Pipet Volume, cc		24	24									
		Cross-sectional Area of Pipet, cm^2		0.8454	0.8454									

HYDRAULIC CONDUCTIVITY (k) 2.2E-04 cm/sec

BLE INC.

HYDRAULIC CONDUCTIVITY TEST REPORT

CONSTANT VOLUME APPARATUS (ASTM D 5084)

	WHITE OAK LANDFILL		
PROJECT:	HAYWOOD COUNTY, NC	TESTED BY:	JOHN MATHEW
PROJECT NO.:	J07-1957-02	CHECKED BY:	PAUL YARBER
DATE RECEIVED:	11-2-07		

SAMPLE NO.	BLE-10	SAMPLE LOCATION:	1.0-3.0'
TYPE	UNDISTURBED	SAMPLE DESCRIPTION:	RED & BROWN SILTY FI.-MED. SAND

SAMPLE DIMENSIONS AND PROPERTIES

ITEM	INITIAL		FINAL	
	inches	centimeters	inches	centimeters
Sample Length	2.321	5.895	2.330	5.918
Sample Diameter	2.864	7.275	2.882	7.320
Length/Diameter Ratio		0.81		
Moisture Content (%)	WW= 175.6 DW= 146.0	20.3	WW= 210.8 DW= 158.3	33.2
Sample Wet Weight (grams)	430.4		466.8	
Wet Density (pcf)	109.7		117.0	
Dry Density (pcf)	91.2		87.9	
Saturation (%) ASSUMED SG= 2.693	65		98	

HYDRAULIC CONDUCTIVITY TESTING MEASUREMENT

FALLING HEAD TEST

Confining Pressure (psi) 72.2 | Influent Pressure (psi) 70.2 | Effluent Pressure (psi) 70

Date	Clock Time		Elapsed Time	Pipet Readings				Head		Temp	Gradient	K	Temp	K_{20}
				Initial		Final		Initial	Final					
	Start	End	seconds	in	out	in	out	cm	cm	°C		(cm/sec)	Correction	(cm/sec)
11-8-07	5:14:00	5:16:17	137	1.0	23.0	3.0	21.0	40.092	35.361	21	6	5.5E-05	0.976	5.4E-05
11-8-07	5:16:17	5:18:53	156	3.0	21.0	5.0	19.0	35.361	30.629	21	6	5.5E-05	0.976	5.4E-05
11-8-07	5:18:53	5:21:55	182	5.0	19.0	7.0	17.0	30.629	25.897	21	5	5.5E-05	0.976	5.4E-05
11-8-07	5:21:55	5:25:36	221	7.0	17.0	9.0	15.0	25.897	21.166	21	4	5.5E-05	0.976	5.3E-05
		Pipet Length, cm		28.390	28.390									
		Pipet Volume, cc		24	24									
		Cross-sectional Area of Pipet, cm^2		0.8454	0.8454									

HYDRAULIC CONDUCTIVITY (k) 5.4E-05 cm/sec

BLE INC.

HYDRAULIC CONDUCTIVITY TEST REPORT

CONSTANT VOLUME APPARATUS (ASTM D 5084)

	WHITE OAK LANDFILL		
PROJECT:	HAYWOOD COUNTY, NC	TESTED BY:	JOHN MATHEW
PROJECT NO.:	J07-1957-02	CHECKED BY:	PAUL YARBER
DATE RECEIVED:	11-2-07		

SAMPLE NO.	BLE-10	SAMPLE LOCATION:	9.5-11.5'
TYPE	UNDISTURBED	SAMPLE DESCRIPTION:	RED & BROWN FL-MED. SANDY SILT

SAMPLE DIMENSIONS AND PROPERTIES

ITEM	INITIAL		FINAL	
	inches	centimeters	inches	centimeters
Sample Length	2.937	7.460	2.999	7.617
Sample Diameter	2.846	7.229	2.894	7.351
Length/Diameter Ratio		1.03		
Moisture Content (%)	WW= 174.6 DW= 140.6	24.2	WW= 271.8 DW= 207.2	31.2
Sample Wet Weight (grams)	552.3		608.9	
Wet Density (pcf)	112.6		117.6	
Dry Density (pcf)	90.7		89.6	
Saturation (%) ASSUMED SG= 2.715	76		95	

HYDRAULIC CONDUCTIVITY TESTING MEASUREMENT

FALLING HEAD TEST

Confining Pressure (psi) 69.2 | Influent Pressure (psi) 60.2 | Effluent Pressure (psi) 60

Date	Clock Time		Elapsed Time	Pipet Readings				Head		Temp	Gradient	K	Temp	K_{20}
				Initial		Final		Initial	Final					
	Start	End	seconds	in	out	in	out	cm	cm	°C		(cm/sec)	Correction	(cm/sec)
11-9-07	3:17:00	3:20:06	186	1.0	23.0	2.0	22.0	40.092	37.726	21	5	2.5E-05	0.976	2.5E-05
11-9-07	3:20:06	3:23:29	203	2.0	22.0	3.0	21.0	37.726	35.361	21	5	2.5E-05	0.976	2.4E-05
11-9-07	3:23:29	3:27:09	220	3.0	21.0	4.0	20.0	35.361	32.995	21	5	2.4E-05	0.976	2.4E-05
11-9-07	3:27:09	3:31:11	242	4.0	20.0	5.0	19.0	32.995	30.629	21	4	2.4E-05	0.976	2.3E-05
		Pipet Length, cm		28.390	28.390									
		Pipet Volume, cc		24	24									
		Cross-sectional Area of Pipet, cm^2		0.8454	0.8454									

HYDRAULIC CONDUCTIVITY (k) 2.4E-05 cm/sec

BLE INC.

HYDRAULIC CONDUCTIVITY TEST REPORT

CONSTANT VOLUME APPARATUS (ASTM D 5084)

WHITE OAK LANDFILL

PROJECT: HAYWOOD COUNTY, NC
PROJECT NO.: J07-1957-02
DATE RECEIVED: 11-2-07

TESTED BY: JOHN MATHEW
CHECKED BY: PAUL YARBER

SAMPLE NO. BLE-13
TYPE UNDISTURBED
SAMPLE LOCATION: 23.5-25.0'
SAMPLE DESCRIPTION: RED & BROWN FI.-MED. SANDY SILT

SAMPLE DIMENSIONS AND PROPERTIES

ITEM	INITIAL		FINAL	
	inches	centimeters	inches	centimeters
Sample Length	3.019	7.668	2.930	7.442
Sample Diameter	2.859	7.262	2.860	7.264
Length/Diameter Ratio		1.06		
Moisture Content (%)	WW= 187.7 DW= 154.9	21.2	WW= 245.3 DW= 186.0	31.9
Sample Wet Weight (grams)	578.2		581.9	
Wet Density (pcf)	113.6		117.8	
Dry Density (pcf)	93.8		89.3	
Saturation (%) ASSUMED SG= 2.73	71		96	

HYDRAULIC CONDUCTIVITY TESTING MEASUREMENT

FALLING HEAD TEST

Confining Pressure (psi) 80.2 | Influent Pressure (psi) 60.2 | Effluent Pressure (psi) 60

Date	Clock Time		Elapsed Time	Pipet Readings				Head		Temp	Gradient	K	Temp	K_{20}
				Initial		Final		Initial	Final					
	Start	End	seconds	in	out	in	out	cm	cm	°C		(cm/sec)	Correction	(cm/sec)
11-9-07	2:58:00	3:00:19	139	1.0	23.0	3.0	21.0	40.092	35.361	21	5	7.1E-05	0.976	6.9E-05
11-9-07	3:00:19	3:02:58	159	3.0	21.0	5.0	19.0	35.361	30.629	21	4	7.1E-05	0.976	6.9E-05
11-9-07	3:02:58	3:06:03	185	5.0	19.0	7.0	17.0	30.629	25.897	21	4	7.1E-05	0.976	6.9E-05
11-9-07	3:06:03	3:09:46	223	7.0	17.0	9.0	15.0	25.897	21.166	21	3	7.1E-05	0.976	6.9E-05
		Pipet Length, cm		28.390	28.390									
		Pipet Volume, cc		24	24									
		Cross-sectional Area of Pipet, cm^2		0.8454	0.8454									

HYDRAULIC CONDUCTIVITY (k) 6.9E-05 cm/sec

BLE INC.

HYDRAULIC CONDUCTIVITY TEST REPORT

CONSTANT VOLUME APPARATUS (ASTM D 5084)

PROJECT:	**WHITE OAK LANDFILL HAYWOOD COUNTY, NC**	TESTED BY:	**JOHN MATHEW**
PROJECT NO.:	**J07-1957-02**	CHECKED BY:	**PAUL YARBER**
DATE RECEIVED:	**10-24-07**		

SAMPLE NO.	**BLE-11**	SAMPLE LOCATION:	**DEPTH 15 TO 18 FEET**
TYPE	**REMOLDED**	SAMPLE DESCRIPTION:	**BROWN FI. SANDY CLAYEY SILT**

SAMPLE DIMENSIONS AND PROPERTIES

ITEM	INITIAL		FINAL	
	inches	centimeters	inches	centimeters
Sample Length	3.000	7.620	2.961	7.521
Sample Diameter	2.850	7.239	2.845	7.226
Length/Diameter Ratio		1.05		
Moisture Content (%)	WW= 156.6 DW= 122.3	28.0	WW= 289.9 DW= 225.2	28.7
Sample Wet Weight (grams)	598.3		599.4	
Wet Density (pcf)	119.1		121.3	
Dry Density (pcf)	93.0		94.2	
Saturation (%) ASSUMED SG= 2.693	94		99	

HYDRAULIC CONDUCTIVITY TESTING MEASUREMENT

(PERMOMETER)

Cell Pressure (psi)	85	Influent Pressure (psi)	70	Effluent Pressure (psi)	70

Reset (Y/N)	Date	Clock Time	Elapsed Time	HA_{OUT} (cm)	HA_{IN} (cm)	Temp °C	Gradient	K (cm/sec)	Temp Correction	K_{20} (cm/sec)
Y	10-26-07	4:19:45		7.5	2.09	21	10			
	10-26-07	4:35:47	0:16:02	4.9	2.19	21	5	3.0E-07	0.976	2.9E-07
	10-26-07	4:36:30	0:16:45	4.8	2.20	21	5	3.0E-07	0.976	2.9E-07
	10-26-07	4:37:28	0:17:43	4.7	2.20	21	5	3.0E-07	0.976	2.9E-07
	10-26-07	4:38:33	0:18:48	4.6	2.21	21	5	3.0E-07	0.976	2.9E-07

HYDRAULIC CONDUCTIVITY (k) 2.9E-07 cm/sec

% COMPACTION OF STD. PROCTOR MAX. DRY DENSITY (ASTM D 698): 95.0

% WETTER THAN OPTIMUM MOISTURE CONTENT (ASTM D 698): +5.6

BLE INC.

HYDRAULIC CONDUCTIVITY TEST REPORT

CONSTANT VOLUME APPARATUS (ASTM D 5084)

PROJECT:	**WHITE OAK LANDFILL HAYWOOD COUNTY, NC**	TESTED BY:	**JOHN MATHEW**
PROJECT NO.:	**J07-1957-02**	CHECKED BY:	**PAUL YARBER**
DATE RECEIVED:	**10-24-07**		

SAMPLE NO.	**BLE-14**	SAMPLE LOCATION:	**DEPTH 16 TO 18 FEET**
TYPE	**REMOLDED**	SAMPLE DESCRIPTION:	**DARK BROWN FI. SANDY CLAYEY SILT**

SAMPLE DIMENSIONS AND PROPERTIES

ITEM	INITIAL		FINAL	
	inches	centimeters	inches	centimeters
Sample Length	3.000	7.620	3.004	7.630
Sample Diameter	2.850	7.239	2.859	7.262
Length/Diameter Ratio		1.05		
Moisture Content (%)	WW= 125.6 DW= 95.9	31.0	WW= 279.1 DW= 208.9	33.6
Sample Wet Weight (grams)	592.5		603.1	
Wet Density (pcf)	117.9		119.1	
Dry Density (pcf)	90.1		89.2	
Saturation (%) ASSUMED SG= 2.688	97		103	

HYDRAULIC CONDUCTIVITY TESTING MEASUREMENT

(PERMOMETER)

Cell Pressure (psi) 85 | Influent Pressure (psi) 70 | Effluent Pressure (psi) 70

Reset (Y/N)	Date	Clock Time	Elapsed Time	HA_{OUT} (cm)	HA_{IN} (cm)	Temp °C	Gradient	K (cm/sec)	Temp Correction	K_{20} (cm/sec)
Y	10-26-07	4:11:23		7.5	2.09	21	10			
	10-26-07	4:16:06	0:04:43	6.0	2.15	21	7	5.0E-07	0.976	4.8E-07
	10-26-07	4:16:30	0:05:07	5.9	2.15	21	7	4.9E-07	0.976	4.8E-07
	10-26-07	4:16:55	0:05:32	5.8	2.16	21	7	4.9E-07	0.976	4.8E-07
	10-26-07	4:17:21	0:05:58	5.7	2.16	21	7	4.9E-07	0.976	4.8E-07

HYDRAULIC CONDUCTIVITY (k) 4.8E-07 cm/sec

% COMPACTION OF STD. PROCTOR MAX. DRY DENSITY (ASTM D 698): 95.1

% WETTER THAN OPTIMUM MOISTURE CONTENT (ASTM D 698): +7.2

BLE INC.

HYDRAULIC CONDUCTIVITY TEST REPORT

CONSTANT VOLUME APPARATUS (ASTM D 5084)

PROJECT:	**WHITE OAK LANDFILL HAYWOOD COUNTY, NC**	TESTED BY:	**JOHN MATHEW**
PROJECT NO.:	**J07-1957-02**	CHECKED BY:	**PAUL YARBER**
DATE RECEIVED:	**10-24-07**		

SAMPLE NO.	**BLE-15**	SAMPLE LOCATION:	**DEPTH 1 TO 8 FEET**
TYPE	**REMOLDED**	SAMPLE DESCRIPTION:	**BROWN FI. SANDY CLAYEY SILT**

SAMPLE DIMENSIONS AND PROPERTIES

ITEM	INITIAL		FINAL	
	inches	centimeters	inches	centimeters
Sample Length	3.000	7.620	2.959	7.516
Sample Diameter	2.850	7.239	2.848	7.234
Length/Diameter Ratio		1.05		
Moisture Content (%)	WW= 101.6 DW= 77.5	31.1	WW= 254.5 DW= 193.4	31.6
Sample Wet Weight (grams)	589.8		592.9	
Wet Density (pcf)	117.4		119.8	
Dry Density (pcf)	89.6		91.1	
Saturation (%) ASSUMED SG= 2.722	94		99	

HYDRAULIC CONDUCTIVITY TESTING MEASUREMENT

(PERMOMETER)

Cell Pressure (psi)	85	Influent Pressure (psi)	70	Effluent Pressure (psi)	70

Reset (Y/N)	Date	Clock Time	Elapsed Time	HA_{OUT} (cm)	HA_{IN} (cm)	Temp °C	Gradient	K (cm/sec)	Temp Correction	K_{20} (cm/sec)
Y	10-26-07	4:10:40		7.1	1.69	21	10			
	10-26-07	4:19:56	0:09:16	6.5	1.71	21	9	9.1E-08	0.976	8.9E-08
	10-26-07	4:21:33	0:10:53	6.4	1.72	21	9	9.1E-08	0.976	8.9E-08
	10-26-07	4:23:20	0:12:40	6.3	1.72	21	9	9.1E-08	0.976	8.8E-08
	10-26-07	4:25:10	0:14:30	6.2	1.72	21	8	9.0E-08	0.976	8.8E-08

HYDRAULIC CONDUCTIVITY (k) 8.8E-08 cm/sec

% COMPACTION OF STD. PROCTOR MAX. DRY DENSITY (ASTM D 698): 95.0

% WETTER THAN OPTIMUM MOISTURE CONTENT (ASTM D 698): +5.4

MOISTURE/DENSITY RELATIONSHIP



Test specification: ASTM D 698-00a Method B Standard

Elev/ Depth	Classification		Nat. Moist.	Sp.G.	LL	PI	% > 3/8 in.	% < No.200
	USCS	AASHTO						
15.5-18.0	MH			2.693	59	22	0.0	66.7

TEST RESULTS	MATERIAL DESCRIPTION
Maximum dry density = 97.9 pcf Optimum moisture = 22.4 %	Brown fi. sandy clayey SILT

Project No. J07-1957-02 **Client:** McGill
Project: White Oak Landfill

● **Source:** Boring **Sample No.:** BLE-11 **Elev./Depth:** 15.5-18.0

Remarks:

Bunnell Lammons Engineering, Inc.
Greenville, SC

Plate

MOISTURE/DENSITY RELATIONSHIP



Test specification: ASTM D 698-00a Method B Standard

Elev/ Depth	Classification		Nat. Moist.	Sp.G.	LL	PI	% > 3/8 in.	% < No.200
	USCS	AASHTO						
16.0-18.0	MH			2.688	63	23	0.0	76.0

TEST RESULTS	MATERIAL DESCRIPTION
Maximum dry density = 94.7 pcf Optimum moisture = 23.8 %	Dark brown fi. sandy clayey SILT

Project No. J07-1957-02 **Client:** McGill
Project: White Oak Landfill

● **Source:** Boring **Sample No.:** BLE-14 **Elev./Depth:** 16.0-18.0

Remarks:

Bunnell Lammons Engineering, Inc.

Greenville, SC

Plate

MOISTURE/DENSITY RELATIONSHIP

Test specification: ASTM D 698-00a Method B Standard

Elev/ Depth	Classification		Nat. Moist.	Sp.G.	LL	PI	% > 3/8 in.	% < No.200
	USCS	AASHTO						
1.0-8.0	MH			2.722	63	28	0.0	84.0

TEST RESULTS	MATERIAL DESCRIPTION
Maximum dry density = 94.3 pcf Optimum moisture = 25.7 %	Brown fi. sandy clayey SILT

Project No. J07-1957-02 **Client:** McGill
Project: White Oak Landfill

● **Source:** Boring **Sample No.:** BLE-15 **Elev./Depth:** 1.0-8.0

Remarks:

Bunnell Lammons Engineering, Inc.

Greenville, SC

Plate

LIQUID AND PLASTIC LIMITS TEST REPORT



SOIL DATA

SYMBOL	SOURCE	SAMPLE NO.	DEPTH (ft.)	NATURAL WATER CONTENT (%)	PLASTIC LIMIT (%)	LIQUID LIMIT (%)	PLASTICITY INDEX (%)	USCS
●	Boring	BLE-1	3.5-5.5	32.1	46	59	13	MH
■	Boring	BLE-1	63.5-65.0	12.6	26	29	3	SM
▲	Boring	BLE-2	23.5-25.0	24.8	38	42	4	SM
◆	Boring	BLE-3	6.0-8.0	20.4	29	42	13	SM
▼	Boring	BLE-3	8.5-10.0	15.4	34	46	12	SM

LIQUID AND PLASTIC LIMITS TEST REPORT

Bunnell Lammons Engineering, Inc.

Greenville, SC

Client: McGill

Project: White Oak Landfill

Project No.: J07-1957-02

Plate

LIQUID AND PLASTIC LIMITS TEST REPORT



SOIL DATA								
SYMBOL	SOURCE	SAMPLE NO.	DEPTH (ft.)	NATURAL WATER CONTENT (%)	PLASTIC LIMIT (%)	LIQUID LIMIT (%)	PLASTICITY INDEX (%)	USCS
●	Boring	BLE-3	23.5-25.0	31.6	35	44	9	SM
■	Boring	BLE-6	6.0-7.5	14.4	29	34	5	SM
▲	Boring	BLE-7	1.0-3.0	35.4	43	56	13	MH
◆	Boring	BLE-7	13.5-15.0	27.4	36	42	6	SM
▼	Boring	BLE-9	13.5-15.5	23.8	33	37	4	SM

LIQUID AND PLASTIC LIMITS TEST REPORT **Bunnell Lammons Engineering, Inc.** **Greenville, SC**	**Client:** McGill **Project:** White Oak Landfill **Project No.:** J07-1957-02 **Plate**

LIQUID AND PLASTIC LIMITS TEST REPORT



SOIL DATA								
SYMBOL	SOURCE	SAMPLE NO.	DEPTH (ft.)	NATURAL WATER CONTENT (%)	PLASTIC LIMIT (%)	LIQUID LIMIT (%)	PLASTICITY INDEX (%)	USCS
●	Boring	BLE-10	1.0-3.0	20.3	49	55	6	SM
■	Boring	BLE-10	9.5-11.5	24.2	38	45	7	ML
▲	Boring	BLE-11	6.0-7.5	20.2	38	52	14	MH
◆	Boring	BLE-11	15.5-18.0		37	59	22	MH
▼	Boring	BLE-13	23.5-25.0	21.2	35	42	7	ML

LIQUID AND PLASTIC LIMITS TEST REPORT

Bunnell Lammons Engineering, Inc.

Greenville, SC

Client: McGill

Project: White Oak Landfill

Project No.: J07-1957-02

Plate

LIQUID AND PLASTIC LIMITS TEST REPORT



SOIL DATA								
SYMBOL	SOURCE	SAMPLE NO.	DEPTH (ft.)	NATURAL WATER CONTENT (%)	PLASTIC LIMIT (%)	LIQUID LIMIT (%)	PLASTICITY INDEX (%)	USCS
●	Boring	BLE-13	43.5-45.0	15.5	34	45	11	SM
■	Boring	BLE-14	16.0-18.0		40	63	23	MH
▲	Boring	BLE-15	1.0-8.0		35	63	28	MH
◆	Boring	BLE-15	8.5-10.0	27.9	34	52	18	MH
▼	Boring	BLE-16	73.5-75.0	22.2	32	37	5	SM

LIQUID AND PLASTIC LIMITS TEST REPORT **Bunnell Lammons Engineering, Inc.** **Greenville, SC**	**Client:** McGill **Project:** White Oak Landfill **Project No.:** J07-1957-02 **Plate**

LIQUID AND PLASTIC LIMITS TEST REPORT



SOIL DATA								
SYMBOL	SOURCE	SAMPLE NO.	DEPTH (ft.)	NATURAL WATER CONTENT (%)	PLASTIC LIMIT (%)	LIQUID LIMIT (%)	PLASTICITY INDEX (%)	USCS
●	Boring	BLE-17	98.5-100.0	13.7	26	30	4	SM

LIQUID AND PLASTIC LIMITS TEST REPORT

Bunnell Lammons Engineering, Inc.

Greenville, SC

Client: McGill

Project: White Oak Landfill

Project No.: J07-1957-02

Plate

Particle Size Distribution Report



	% COBBLES	% GRAVEL		% SAND			% FINES	
		CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
○	0.0	0.0	0.0	0.0	7.6	29.0	57.2	6.2
□	0.0	0.0	0.8	13.1	25.7	32.0	26.8	1.6
△	0.0	14.7	9.5	7.8	27.7	19.2	19.0	2.1
◇	0.0	0.0	4.6	6.7	20.8	18.6	27.7	21.6
▽	0.0	0.0	2.9	11.9	30.0	18.9	23.4	12.9

SOIL DATA

SYMBOL	SOURCE	SAMPLE NO.	DEPTH (ft.)	DESCRIPTION	USCS
○	Boring	BLE-1	3.5-5.5	Tan fi. sandy clayey SILT	MH
□	Boring	BLE-1	63.5-65.0	Grey & brown silty fi.-co. SAND	SM
△	Boring	BLE-2	23.5-25.0	Dark grey silty fi.-co. SAND w/gravel	SM
◇	Boring	BLE-3	6.0-8.0	Brown silty fi.-co. SAND	SM
▽	Boring	BLE-3	8.5-10.0	Light brown silty fi.-co. SAND	SM

Particle Size Distribution Report

Bunnell Lammons Engineering, Inc.

Greenville, SC

Client: McGill

Project: White Oak Landfill

Project No.: J07-1957-02 **Plate**

Particle Size Distribution Report



	% COBBLES	% GRAVEL		% SAND			% FINES	
		CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
○	0.0	0.0	0.0	2.6	26.5	26.1	38.2	6.6
□	0.0	11.6	3.9	11.9	26.7	18.3	20.7	6.9
△	0.0	0.0	0.0	0.0	13.2	30.6	42.0	14.2
◇	0.0	0.0	0.1	2.7	35.0	30.1	28.8	3.3
▽	0.0	0.0	0.0	0.1	16.2	44.1	33.0	6.6

SOIL DATA

SYMBOL	SOURCE	SAMPLE NO.	DEPTH (ft.)	DESCRIPTION	USCS
○	Boring	BLE-3	23.5-25.0	Light grey & white silty fi.-med. SAND	SM
□	Boring	BLE-6	6.0-7.5	Brown silty fi.-co. SAND w/gravel	SM
△	Boring	BLE-7	1.0-3.0	Light brown fi.-med. sandy clayey SILT	MH
◇	Boring	BLE-7	13.5-15.0	Grey & brown silty fi.-med. SAND	SM
▽	Boring	BLE-9	13.5-15.5	Grey & brown silty fi.-med. SAND	SM

Particle Size Distribution Report

Bunnell Lammons Engineering, Inc.

Greenville, SC

Client: McGill

Project: White Oak Landfill

Project No.: J07-1957-02

Plate

Particle Size Distribution Report



	% COBBLES	% GRAVEL		% SAND			% FINES	
		CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
○	0.0	0.0	0.0	0.7	13.7	51.2	30.3	4.1
□	0.0	0.0	0.0	0.5	9.4	32.4	51.3	6.4
△	0.0	0.0	0.0	0.0	6.6	41.2	43.6	8.6
◇	0.0	0.0	0.4	0.1	3.8	29.0	37.5	29.2
▽	0.0	0.0	0.0	0.0	10.4	30.8	55.8	3.0

SOIL DATA

SYMBOL	SOURCE	SAMPLE NO.	DEPTH (ft.)	DESCRIPTION	USCS
○	Boring	BLE-10	1.0-3.0	Red & brown silty fi.-med. SAND	SM
□	Boring	BLE-10	9.5-11.5	Red & brown fi.-med. sandy SILT	ML
△	Boring	BLE-11	6.0-7.5	Light red & brown fi. sandy clayey SILT	MH
◇	Boring	BLE-11	15.5-18.0	Brown fi. sandy clayey SILT	MH
▽	Boring	BLE-13	23.5-25.0	Red & brown fi.-med. sandy SILT	ML

Particle Size Distribution Report

Bunnell Lammons Engineering, Inc.

Greenville, SC

Client: McGill

Project: White Oak Landfill

Project No.: J07-1957-02

Plate

Particle Size Distribution Report



	% COBBLES	% GRAVEL		% SAND			% FINES	
		CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
○	0.0	0.0	9.2	11.3	18.1	25.5	26.4	9.5
□	0.0	0.0	0.0	0.0	5.0	19.0	46.7	29.3
△	0.0	0.0	0.5	0.5	2.0	13.0	25.6	58.4
◇	0.0	0.0	0.4	1.5	4.5	20.6	35.8	37.2
▽	0.0	0.0	0.4	2.2	17.9	31.2	41.6	6.7

SOIL DATA

SYMBOL	SOURCE	SAMPLE NO.	DEPTH (ft.)	DESCRIPTION	USCS
○	Boring	BLE-13	43.5-45.0	Grey & brown silty fi.-co. SAND	SM
□	Boring	BLE-14	16.0-18.0	Dark brown fi. sandy clayey SILT	MH
△	Boring	BLE-15	1.0-8.0	Brown fi. sandy clayey SILT	MH
◇	Boring	BLE-15	8.5-10.0	Red & brown fi. sandy clayey SILT	MH
▽	Boring	BLE-16	73.5-75.0	Grey & brown silty fi.-med. SAND	SM

Particle Size Distribution Report

Bunnell Lammons Engineering, Inc.

Greenville, SC

Client: McGill

Project: White Oak Landfill

Project No.: J07-1957-02

Plate

Particle Size Distribution Report



	% COBBLES	% GRAVEL		% SAND			% FINES	
		CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
○	0.0	0.0	1.3	5.9	24.3	28.6	31.8	8.1

SOIL DATA

SYMBOL	SOURCE	SAMPLE NO.	DEPTH (ft.)	DESCRIPTION	USCS
○	Boring	BLE-17	98.5-100.0	Grey & brown silty fi.-med. SAND	SM

Particle Size Distribution Report

Bunnell Lammons Engineering, Inc.

Greenville, SC

Client: McGill

Project: White Oak Landfill

Project No.: J07-1957-02

Plate

TRIAXIAL SHEAR TEST REPORT



Type of Test: CU with Pore Pressures **Sample Type:** Undisturbed

No.	Fluid Press. psi		Fail. Stress, ksf		Ult. Stress, ksf		Principal Stresses at Failure ksf	
	Cell	Back	Deviator	Total Pore Pressure	Deviator	Total Pore Pressure	$\bar{\sigma}_1$	$\bar{\sigma}_3$
1	73.900	60.000	1.963	10.066	2.238	9.994	2.539	0.576
2	87.800	60.000	3.866	11.434	4.087	11.232	5.075	1.210
3	102.700	60.000	9.252	11.765	9.840	10.728	12.276	3.024

No.	Consolidated Sample Parameters						
	% Water Content	Dry Dens. pcf	Satur-ation	Void Ratio	Diameter in.	Height in.	Strain Rate in/min.
1	33.1	85.6	92.2%	0.9692	2.828	5.953	0.019
2	29.1	93.8	98.7%	0.7969	2.812	5.892	0.019
3	30.3	93.2	101.2%	0.8092	2.817	5.871	0.019

Mohr-Coulomb Strength Parameters	Total	Effective
Strength intercept, c=	0.063 ksf	0.064 ksf
Friction angle, ϕ =	18.80 deg	36.73 deg
Tangent, ϕ =	0.34	0.75

Material Description

Red & brown fi.-med. sandy SILT
(BLE-9[1&2], 13.5-15.0; BLE-10[3], 9.5-11.5)

Client: McGill

Project: White Oak Landfill

Source of Sample: Boring
Sample Number: BLE-9/10

Date Sampled:
File: WHITEO$_1$
Remarks:

TRIAXIAL SHEAR TEST REPORT

Bunnell Lammons Engineering, Inc.

Proj. No.: J07-1957-02
Plate 1



Client: McGill
Project: White Oak Landfill
Source of Sample: Boring **Sample Number:** BLE-9/10
Project No.: J07-1957-02 **Plate** 2

Bunnell Lammons Engineering, Inc.

CONSOLIDATION TEST REPORT



Natural		Dry Dens. (pcf)	LL	PI	Sp. Gr.	P_c (ksf)	C_c	Initial Void Ratio
Saturation	Moisture							
63.5 %	18.2 %	94.0	55	6	2.65	8.06	0.12	0.760

MATERIAL DESCRIPTION	USCS	AASHTO
Red & brown silty fi.-med. SAND	SM	

Project No. J07-1957-02 **Client:** McGill

Project: White Oak Landfill

Source: Boring **Sample No.:** BLE-10 **Elev./Depth:** 1.0-3.0

Bunnell Lammons Engineering, Inc.

Greenville, SC

Remarks:

Plate

Dial Reading vs. Time

Project No.: J07-1957-02
Project: White Oak Landfill

Source: Boring Sample No.: BLE-10 Elev./Depth: 1.0-3.0









Bunnell Lammons Engineering, Inc.

Greenville, SC

Plate

Dial Reading vs. Time

Project No.: J07-1957-02
Project: White Oak Landfill

Source: Boring Sample No.: BLE-10 Elev./Depth: 1.0-3.0









Bunnell Lammons Engineering, Inc.
Greenville, SC

Plate

Dial Reading vs. Time

Project No.: J07-1957-02
Project: White Oak Landfill

Source: Boring Sample No.: BLE-10 Elev./Depth: 1.0-3.0





Bunnell Lammons Engineering, Inc.
Greenville, SC

Plate



FIGURE 4.11 FROM FETTER, C.W., 1994, APPLIED HYDROGEOLOGY
TEXTURAL CLASSIFICATION TRIANGLE FOR UNCONSOLIDATED MATERIALS SHOWING THE RELATION BETWEEN PARTICAL SIZE AND SPECIFIC YIELD. SOURCE: A.I. JOHNSON, U.S. GEOLOGICAL SURVEY WATER–SUPPLY PAPER 1662–D, 1967.

ID#	BORING	DEPTH (FT)
2	BLE–1	63.5 – 65.0
3	BLE–2	23.5 – 25.0
5	BLE–3	8.5 – 10.0
7	BLE–6	6.0 – 7.5
9	BLE–7	13.5 – 15.0
13	BLE–11	6.0 – 7.5
15	BLE–13	43.5 – 45.0
16	BLE–15	8.5 – 10.0
17	BLE–16	73.5 – 75.0
18	BLE–17	98.5 – 100.0

DRAWN: MSP	DATE: 06–02–08	BLE inc. BUNNELL-LAMMONS ENGINEERING, INC. 6004 PONDERS COURT GREENVILLE, SOUTH CAROLINA 29615 PHONE: (864)288–1265 FAX: (864)288–4430	EFFECTIVE POROSITY ESTIMATION WHITE OAK MSW LANDFILL HAYWOOD COUNTY, NORTH CAROLINA
CHECKED:	CAD: HCWOLF02–EFF POROS pg1		FIGURE H-1
APPROVED:	JOB NO: J07–1957–02		



FIGURE 4.11 FROM FETTER, C.W., 1994, APPLIED HYDROGEOLOGY
TEXTURAL CLASSIFICATION TRIANGLE FOR UNCONSOLIDATED MATERIALS SHOWING THE RELATION BETWEEN PARTICAL SIZE AND SPECIFIC YIELD. SOURCE: A.I. JOHNSON, U.S. GEOLOGICAL SURVEY WATER–SUPPLY PAPER 1662–D, 1967.

ID#	BORING	DEPTH (FT)
1	BLE–1	3.5 – 5.5
4	BLE–3	6.0 – 8.0
6	BLE–3	23.5 – 25.0
8	BLE–7	1.0 – 3.0
10	BLE–9	13.5 – 15.5
11	BLE–10	1.0 – 3.0
12	BLE–10	9.5 – 11.5
14	BLE–13	23.5 – 25.0

DRAWN: MSP	DATE: 06–02–08	BLE inc. BURNELL-LAMMONS ENGINEERING, INC. 6004 PONDERS COURT GREENVILLE, SOUTH CAROLINA 29615 PHONE: (864)288–1285 FAX: (864)288–4430	EFFECTIVE POROSITY ESTIMATION WHITE OAK MSW LANDFILL HAYWOOD COUNTY, NORTH CAROLINA
CHECKED:	CAD: HCWOLF02–EFF POROS pg2		FIGURE H-2
APPROVED:	JOB NO: J07–1957–02		



White Oak MSW Landfill - Phase 3 & 4 DHR
Haywood County, North Carolina
BLE Project Number J07-1957-02

(Modified from Rawls and Brankensiek, 1989)

ID#	Boring	Depth (ft)
1	BLE-1	3.5 - 5.5
2	BLE-1	63.5 - 65.0
3	BLE-2	23.5 - 25.0
4	BLE-3	6.0 - 8.0
5	BLE-3	8.5 -10.0
6	BLE-3	23.5 - 25.0
7	BLE-6	6.0 - 7.5
8	BLE-7	1.0 - 3.0
9	BLE-7	13.5 - 15.0
10	BLE-9	13.5 - 15.5
11	BLE-10	1.0 - 3.0
12	BLE-10	9.5 - 11.5
13	BLE-11	6.0 - 7.5
14	BLE-13	23.5 - 25.0
15	BLE-13	43.5 - 45.0
16	BLE-15	8.5 - 10.0
17	BLE-16	73.5 - 75.0
18	BLE-17	98.5 - 100.0

APPENDIX I

GEOTECHNICAL CALCULATIONS

APPENDIX I

GEOTECHNICAL CALCULATIONS METHODOLOGY
WHITE OAK MSW LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA
BLE Project No. J07-1957-02

SETTLEMENT CONSIDERATIONS:

Site and subsurface data obtained was evaluated to determine subgrade settlement. Settlements were evaluated utilizing data obtained from soil test borings, test pits, laboratory testing of soil samples, field observations by a geotechnical engineer and our experience with settlement monitoring of sites in the Piedmont Region.

Site grading plans for construction of Phases 3 and 4, prepared by McGill Associates, indicate a combination of earthwork cut and fill will be made to establish the cell areas. The analysis considered potential future landfill expansion which would result in a landfill final cap maximum elevation of 2687 feet msl. Foundation support conditions for the landfill liner system will consist of either residual soils over weathered rock or engineered fill overlying residual soils. The rock and partially weathered rock underlying the site are relatively incompressible and will not realize appreciable settlements under the anticipated landfill loading. The residual soils are typically firm to very firm sandy clayey silts grading coarser with depth into dense silty sands with some gravel. Modest settlements will be realized from compression of the upper zones of residual soils and the anticipated fills.

Soil elastic modulus values for settlement analyses were selected based on previously developed correlations with standard penetration resistance values in similar soils. The analyses conservatively assumed the stress increase within the soil layers was equal to the full surcharge pressure of the waste mound. The surcharge pressures were estimated based on an assumed unit weight of 70 pounds per cubic foot (pcf) of waste. Settlements were estimated for the borings within the proposed cells. Some variations in structural fill height and individual soil layer thickness occur from location to location; however, due to the general uniformity of the subsurface conditions and the broad load application, the subgrade settlement will vary primarily with the height of the waste. The magnitude of settlement is well within tolerances of a conventional base liner system.

SLOPE STABILITY CONSIDERATIONS:

The planned landfill structural fill, base liner, and closure cap slopes were analyzed for static, seismic, and interface stability. The initial and final grading plans prepared by McGill Associates, P.A., indicate base liner slopes of 3 horizontal to 1 vertical or flatter and closure cap slopes of 4 horizontal to 1 vertical. A perimeter fill slope will be constructed at 2 horizontal to 1 vertical.

According to the definition of seismic impact zones in 15A NCAC 13B.1622 (5), this site is in a seismic impact zone. The maximum horizontal acceleration expressed as a percentage of the earth's gravity (g) in rock is 0.176g with a 2% probability of being exceeded in 50 years (equal to 10% probability in 250 years; NC Building Code, 2006 IBC). The slope configurations were analyzed using the maximum horizontal acceleration of 0.176g. The analysis of the structural fill and waste mound slopes was performed using the computer program Slope/W by Geoslope International. The analysis results are attached and indicate the designed slopes are stable when subjected to both static and seismic conditions.

ROCK AND GROUNDWATER SEPARATION FROM CLAY LINER SUBGRADE

GEOTECHNICAL ANALYSIS - PHASES 3 & 4
WHITE OAK MSW LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA
BLE Project No. J07-1957-02
June 2008

Boring Number	Calculated Settlement Feet	Cap Elev. minus FML Elev. Feet	Clay Subgrade Elevation (FML-2 Feet) Feet	Groundwater Elevation Seasonal High Feet	Groundwater Elevation Separation[1] Feet	Rock or Auger Refusal Elevation Feet	Rock Elevation Separation[2] Feet
BLE-1	0.58	104	2566	2531.12	34.30	2508.23	57.19
BLE-2	1.25	118	2523	2513.76	7.99	< 2485.7	> 35.1
BLE-3	0.59	97	2511	2501.87	8.54	< 2469.8	> 40.6
BLE-5	0.36	58	2503	2493.33	9.31	2471.10	31.54
BLE-6	0.00	1	2523	2488.93	34.07	2486.96	36.04
BLE-7D	0.41	12	2506	2485.24	20.35	2459.92	45.67
BLE-9	0.00	4	2532	2509.28	22.72	2527.54	4.46
BLE-13	0.00	56	2552	2542.44	9.56	2523.39	28.61
BLE-14	0.04	88	2559	2551.21	7.75	2536.91	22.05
BLE-16	0.00	48	2563	2555.63	7.37	< 2534.7	> 28.3
BLE-17	0.14	60	2581	2537.59	43.27	2510.46	70.40
P-6	0.00	45	2543	2536.05	6.95	2536.1	6.90

References: McGill Associates, PA drawing dated June 2008.
BLE Seasonal High Water Table Map (9/20/07 to 2/14/08); Figure 7.

Notes: 1 Separation between post-settlement bottom of clay liner and seasonal high groundwater.
2 Separation between post-settlement bottom of clay liner and top of rock (refusal).

SETTLEMENT CALCULATIONS

WHITE OAK MSW LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA
Bunnell-Lammons Engineering, Inc. Project No. J07-1957-02

June 2008

Subsurface Layer (feet - feet)	Soil Type	Standard Penetration Resistance N-Value (bpf)	Layer Thickness (feet)	Total Soil Unit Weight (pcf)	Effective Soil Unit Weight (pcf)	Surcharge Pressure[1] (psf)	Soil Modulus (ksf)	Layer Settlement (inches)
Boring BLE-1								
2568-2536	Very Stiff sandy SILT	24	32	120	120	6,750	670	3.9
2536-2510	Very Stiff sandy SILT	26	26	120	58	6,750	700	3.0
2510-2508	PWR	200	2	140	78	6,750	2710	0.1
Total Thickness of Compressible Material			60	Feet				
							TOTAL ESTIMATED SETTLEMENT (inches)	**7.0**

SETTLEMENT CALCULATIONS

WHITE OAK MSW LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA
Bunnell-Lammons Engineering, Inc. Project No. J07-1957-02

June 2008

Subsurface Layer (feet - feet)	Soil Type	Standard Penetration Resistance N-Value (bpf)	Layer Thickness (feet)	Total Soil Unit Weight (pcf)	Effective Soil Unit Weight (pcf)	Surcharge Pressure[1] (psf)	Soil Modulus (ksf)	Layer Settlement (inches)
Boring BLE-2								
2525-2520	Soft sandy SILT	4	5	120	120	8,305	200	2.5
2520-2512	Firm silty SAND	14	8	120	120	8,305	470	1.7
2512-2502	Soft sandy SILT	3	10	120	58	8,305	170	5.9
2502-2471	Very Firm silty SAND	22	31	120	58	8,305	630	4.9
Total Thickness of Compressible Material			54	Feet				
						TOTAL ESTIMATED SETTLEMENT (inches)		**15.0**
Boring BLE-3								
2513-2506	Loose silty SAND	9	8	110	110	6,950	350	1.9
2506-2501	Very Firm silty SAND	25	5	120	120	6,950	690	0.6
2501-2491	Loose silty SAND	9	10	110	48	6,950	350	2.4
2491-2471	Dense silty SAND	31	20	130	68	6,950	790	2.1
2471-2470	Very Dense silty SAND	57	1	130	68	6,950	1180	0.1
Total Thickness of Compressible Material			44	Feet				
						TOTAL ESTIMATED SETTLEMENT (inches)		**7.1**

[1] Surcharge pressure assumes weight of solid waste of 70 pcf

SETTLEMENT CALCULATIONS

WHITE OAK MSW LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA
Bunnell-Lammons Engineering, Inc. Project No. J07-1957-02

June 2008

Subsurface Layer (feet - feet)	Soil Type	Standard Penetration Resistance N-Value (bpf)	Layer Thickness (feet)	Total Soil Unit Weight (pcf)	Effective Soil Unit Weight (pcf)	Surcharge Pressure[1] (psf)	Soil Modulus (ksf)	Layer Settlement (inches)
Boring BLE-5								
2505-2497	Fill	NA	8	120	120	4,220	300	1.4
2497-2489	Firm clayey SILT	5	8	120	58	4,220	240	1.7
2489-2479	Firm silty SAND	18	10	120	58	4,220	550	0.9
2479-2474	PWR	150	5	140	78	4,220	2240	0.1
2474-2471	Dense silty SAND	39	3	130	68	4,220	920	0.2
Total Thickness of Compressible Material			34	Feet				
							TOTAL ESTIMATED SETTLEMENT (inches)	**4.3**
Boring BLE-7D								
2508-2492	Fill	NA	15	120	120	2,840	300	1.7
2492-2486	Firm clayey SILT	7	6	120	120	2,840	300	0.7
2486-2479	Loose silty SAND	10	7	120	58	2,840	370	0.6
2479-2474	Loose silty SAND	5	5	120	58	2,840	240	0.7
2474-2460	Firm silty SAND	11	14	120	58	2,840	400	1.2
Total Thickness of Compressible Material			47	Feet				
							TOTAL ESTIMATED SETTLEMENT (inches)	**4.9**

[1] Surcharge pressure assumes weight of solid waste of 70 pcf

SETTLEMENT CALCULATIONS

WHITE OAK MSW LANDFILL
HAYWOOD COUNTY, NORTH CAROLINA
Bunnell-Lammons Engineering, Inc. Project No. J07-1957-02

June 2008

Subsurface Layer (feet - feet)	Soil Type	Standard Penetration Resistance N-Value (bpf)	Layer Thickness (feet)	Total Soil Unit Weight (pcf)	Effective Soil Unit Weight (pcf)	Surcharge Pressure[1] (psf)	Soil Modulus (ksf)	Layer Settlement (inches)
Boring BLE-14								
2561-2544	Very Stiff to Hard sandy SILT	30	17	120	58	685	300	0.5
2544-2537	PWR	200	7	140	78	685	2710	0.0
Total Thickness of Compressible Material			24	Feet				
						TOTAL ESTIMATED SETTLEMENT (inches)		**0.5**
Boring BLE-17								
2583-2568	Very Stiff sandy SILT	28	15	120	120	1,140	300	0.7
2568-2563	Hard sandy SILT	34	5	120	120	1,140	840	0.1
2563-2538	Very Firm silty SAND	29	25	120	120	1,140	760	0.5
2538-2514	Very Stiff to Hard sandy SILT	31	24	120	58	1,140	790	0.4
2514-2511	PWR	100	3	140	78	1,140	1710	0.0
Total Thickness of Compressible Material			72	Feet				
						TOTAL ESTIMATED SETTLEMENT (inches)		**1.7**

[1] Surcharge pressure assumes weight of solid waste of 70 pcf

SUMMARY OF GLOBAL STABILITY ANALYSIS

WHITE OAK LANDFILL
PHASES 3 & 4
HAYWOOD COUNTY, NORTH CAROLINA
June 2008

BLE Project No. J07-1957-02

Stability Analysis	Static Conditions		Seismic Conditions[1]	
	Result	Recommended Minimum[2]	Result	Recommended Minimum[2]
Waste Slope (4H : 1V) & Foundation	3.1	1.5	1.6	1.0
Fill Slope (2H : 1V)	1.6	1.5	1.1	1.0

Notes:

[1] Seismic horizontal acceleration at bedrock level = 0.176g

[2] Recommended minimum factors of safety: Static Conditions: 1.5
Seismic Conditions: 1.0



	UNIT WEIGHT PCF	TOTAL Ø DEGREES	STRESS C PSF	EFFECTIVE Ø DEGREES	STRESS C' PSF
WASTE	70	30	200	30	200
FILL	120	26	100	32	100
RESIDUUM	120	18	0	36	0

DRAWN: AEH	DATE: 06-16-08	BUNNELL-LAMMONS ENGINEERING, INC.	FIGURE
CHECKED: GLW	CAD: HCWOFL-02SECT	6004 PONDERS COURT GREENVILLE, SOUTH CAROLINA 29615 PHONE: (864)288-1265 FAX: (864)288-4430	SECTION WHITE OAK MSW LANDFILL HAYWOOD COUNTY, NORTH CAROLINA
APPROVED:	JOB NO: J08-1957-02		X

Title: White Oak Landfill - Haywood County, NC
Comments: BLE Project No. J07-1957-02
Directory: C:\Public PC033\Slope Stability\White Oak Landfill\Effective Stress - Static - Autolocate.gsz
Date: 6/5/2008
Time: 2:49:46 PM
Horz Seismic Load: 0

Description: Waste
Wt: 70
Cohesion: 200
Phi: 30

Description: Fill
Wt: 120
Cohesion: 100
Phi: 32

Description: Residuum
Wt: 120
Cohesion: 0
Phi: 36

Description: Bedrock



Title: White Oak Landfill - Haywood County, NC
Comments: BLE Project No. J07-1957-02
Directory: C:\Public PC033\Slope Stability\White Oak Landfill\Effective Stress - Seismic - Autolocate.gsz
Date: 7/2/2008
Time: 10:28:14 AM
Horz Seismic Load: 0.176

Description: Waste
Wt: 70
Cohesion: 200
Phi: 30

Description: Fill
Wt: 120
Cohesion: 100
Phi: 32

Description: Residuum
Wt: 120
Cohesion: 0
Phi: 36

Description: Bedrock



Title: White Oak Landfill - Haywood County, NC
Comments: BLE Project No. J07-1957-02
Directory: C:\Public PC033\Slope Stability\White Oak Landfill\Effective Stress - Static - Circular - Fill Slope.gsz
Date: 6/5/2008
Time: 3:01:37 PM
Horz Seismic Load: 0



Title: White Oak Landfill - Haywood County, NC
Comments: BLE Project No. J07-1957-02
Directory: C:\Public PC033\Slope Stability\White Oak Landfill\Effective Stress - Seismic - Circular - Fill Slope DBB Change.gsz
Date: 6/30/2008
Time: 3:57:07 PM
Horz Seismic Load: 0.176



BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL, ENVIRONMENTAL AND CONSTRUCTION MATERIALS CONSULTANTS
GREENVILLE, SOUTH CAROLINA · ASHEVILLE, NORTH CAROLINA

JOB NO. J07-1957 SHEET 1 OF 2
PHASE 02 TASK
JOB NAME White Oak MSW Landfill
BY G. Weekley DATE 6-16-08
CHECKED BY Hevey DATE 6-19-08

Stability of Final Cover Against Sliding

Reference: Matasovic, N (1991) Selection of Method for Seismic Slope Stability Analysis," Proceedings of Second International Conference on Recent Advances in Geotechnical Earthquake Engineering & Soil Dynamics, St. Louis, Volume 2, pages 1057-1062.

$$FS = \frac{C/(\gamma z \cos^2\beta) + \tan\phi[1 - \gamma_w(z-d_w)/(\gamma z)] - K_s \tan\beta \tan\phi}{K_s + \tan\beta}$$

FS = Factor of Safety (minimum: 1.5 static; 1.0 Dynamic)

C = Cohesion of Cover Layer

γ = Unit Weight of Cover Layer

z = Depth to Failure Surface

β = Slope Angle (4H:1V or $\beta = 14°$)

ϕ = Interface Friction Angle of assumed failure surface

γ_w = Unit Weight of Water

d_w = Depth to Seepage Surface

K_s = Seismic Coefficient

BLE INC.
BUNNELL-LAMMONS ENGINEERING, INC.
GEOTECHNICAL, ENVIRONMENTAL AND CONSTRUCTION MATERIALS CONSULTANTS
GREENVILLE, SOUTH CAROLINA • ASHEVILLE, NORTH CAROLINA

JOB NO. J07-1957 SHEET 2 OF 2
PHASE 02 TASK
JOB NAME White Oak MSW Landfill
BY G. Weekley DATE 6-16-08
CHECKED BY KELVEY DATE 6-19-08

Stability of Final Cover

$\gamma = 110$ pcf $\quad K_s = 0.176$

$\gamma_w = 62.4$ pcf

$c = 25$ psf

$\Phi = 20°$

$z = 2$ Feet

$d_w = 1.0$ Foot

Static

$$FS = \frac{50 / (110 \times 2 \times \cos^2 14°) + \tan 20° [1 - 62.4(2-1)/(110 \times 2)]}{\tan 14°}$$

$$FS = \frac{0.241 + 0.261}{0.249} = 2.02 \geq 1.5 \quad \text{ok against sliding}$$

Dynamic

$$FS = \frac{50/(110 \times 2 \times \cos^2 14) + \tan 20° [1 - 62.4(2-1)/(110 \times 2)] - 0.176 \tan 14° \tan 20°}{0.176 + \tan 14°}$$

$$FS = \frac{0.241 + 0.261 - 0.011}{0.176 + 0.249} = \frac{0.486}{0.425} = 1.14 \geq 1.0$$

ok against sliding during seismic event