



Facility Permit No: 47-02-T  
Hoke County Transfer Facility  
Permit to Operate  
May 31, 2007  
Page 1 of 5  
Doc ID No. RCO2406

**NORTH CAROLINA DEPARTMENT OF ENVIRONMENT AND NATURAL RESOURCES**

Dexter R. Matthews, Director

Division of Waste Management

Michael F. Easley, Governor  
William G. Ross Jr., Secretary

**STATE OF NORTH CAROLINA  
DEPARTMENT OF ENVIRONMENT AND NATURAL RESOURCES  
DIVISION OF WASTE MANAGEMENT**

**SOLID WASTE MANAGEMENT FACILITY  
PERMIT NO. 47-02-T**

**HOKE COUNTY**  
is hereby issued a  
**PERMIT TO OPERATE**  
A  
**TRANSFER FACILITY**

Located at 700 C.C. Steele Road (NCSR 1321) in Raeford, Hoke County, North Carolina, in accordance with Article 9, Chapter 130A, of the General Statutes of North Carolina and all rules promulgated thereunder and subject to the conditions set forth in this permit. The facility is located and described by the legal description found in the approved application.

\_\_\_\_\_  
Edward F. Mussler, III, P.E.,  
Permitting Branch Supervisor  
Solid Waste Section

**ATTACHMENT 1**  
**Permit History**

<b>FACILITY PERMIT NO: 47-02-T</b>	<b>ISSUANCE DATE</b>
<b>Permit to Operate</b>	<b>May 31, 2007</b>

**ATTACHMENT 2**  
**List of Approved Documents**

1. *Hoke County Transfer Station Operations Plan*. Prepared by Don Russell, Solid Waste Director, Hoke County, NC. January 2007.

### **ATTACHMENT 3 Conditions Of The Permit**

**General Facility:**

1. This facility is permitted to receive solid waste as defined in G.S. 130A-290(35), except that hazardous and liquid wastes are prohibited from acceptance at this facility.
2. This facility may receive solid waste that is generated within Hoke and Cumberland Counties, North Carolina and shall transport that waste to the Uwharrie Environmental Regional Municipal Solid Waste Landfill Facility, Permit No. 62-04, located in Troy, Montgomery County, North Carolina.
3. This permit shall be subject to review in accordance with 15A NCAC 13B .0201(e) on or before May 31, 2012. On or before March 1, 2012, the owner shall submit a request for review and shall update pertinent facility plans including the facility operation and waste screening plans.
4. If the performance and compliance history of this facility is determined to have been satisfactory by a review by the Division, and no permit revisions are required, a representative of the Section shall inspect the facility and issue an approval to continue operation for five (5) additional years under the terms and conditions of this permit. The Section representative shall notify the Permitting Branch Supervisor in writing, either by letter or e-mail, that the conditions have been met. The owner and operator shall be copied on the correspondence. The notification shall suffice as permission to operate as of the date of the notification.
5. The owner or operator of a municipal solid waste management facility shall not knowingly dispose of, or accept for transfer for subsequent disposal, any type or form of municipal solid waste that is generated within the boundaries of a unit of local government that by ordinance:
  - a. Prohibits generators or collectors of municipal solid waste from disposing of that type or form of municipal solid waste.
  - b. Requires generators or collectors of municipal solid waste to recycle that type or form of municipal solid waste.
6. All sedimentation and erosion control activities shall be conducted in accordance with the Sedimentation and Pollution Control Act, 15A NCAC 4, and all applicable permits shall be secured prior to construction.
7. This permit is not transferable.

**Transfer Facility Operation:**

8. Operation of the facility shall occur in accordance with 15A NCAC 13B .0402, "Operational Requirements for Transfer Facilities", and the approved operations plan, Attachment 2, Document 1. Any revisions or modifications to these plans shall be approved by the NC Solid Waste Section.
9. Floor drains, leachate collection devices, sanitary sewer connections or leachate storage tanks for the collection and disposal of wash down water and leachate shall be operational. The tipping floor shall have positive drainage away from the building entrance and toward the sump in the loading pit or a trench drain shall be installed along the entrance to the tipping floor and connected to the leachate collection system.
10. This facility shall be operated in a manner which is consistent with the State solid waste management plan and with the solid waste management plans that have been adopted by those units of local government served by the facility and approved by the Section.
11. Waste shall not be stored on the "tipping floor" after operating hours. Waste can be stored in transfer trailers, at the facility with covers in place, after operating hours, but no longer than 48 hours.
12. The "tipping floor" and "transfer trailer loading area" shall be maintained in a clean, sanitary condition after operating hours and shall be cleaned at least daily in accordance with the approved Operational Plan.
13. On or before 1 August of each year, the owner or operator shall report to the NC Solid Waste Section, for the previous year beginning 1 July and ending 30 June, the amount by weight of the solid waste that was received at the facility and disposed of in a landfill, incinerated, or converted to fuel. The report(s) shall indicate by weight and the COUNTY of origin of all solid waste. The owner or operator shall transmit a copy of the report to the county in which the facility is located and to each county in which waste originated.

**Operation of Other Solid Waste Management Areas**

14. The following designated areas are located within this facility and shall accept only those wastes which they are approved to receive:

White Goods Collection Area

15. Operation of these areas shall be conducted in accordance with the approved operations plan, pertinent solid waste management rules and statutes, and the following specific conditions;
- a. White goods collection areas shall provide for the proper removal of chlorofluorocarbon refrigerants.
  - b. Wastes received and product stored shall be maintained in reasonably sized piles with adequate fire breaks and lanes in accordance with the approved operational plans and the pertinent rules.
  - c. Surface water shall be diverted from all operational and storage areas to prevent standing water in operational areas and under or around storage piles. Water that comes in contact with solid waste shall be contained on-site or properly treated prior to discharge.
  - d. These areas shall be operated and maintained with sufficient dust control measures to minimize airborne emissions and to prevent dust from becoming a nuisance or safety hazard.
  - e. These areas shall be operated and maintained in a manner so as to minimize odors, prevent the creation of a nuisance, potential health hazard, or a potential fire hazard.
  - f. Effective vector control measures shall be applied as necessary to control flies, rodents, insects, or vermin.