

Permit No.	Scan Date	DIN
4204-CDLF-2013	February 5, 2013	18900

RECEIVED  
**February 4, 2013**  
Solid Waste Section  
Asheville Regional Office

## Technical Specifications

**Halifax County C&D Landfill - Area 2**  
**Halifax County, North Carolina**

APPROVED DOCUMENT  
Division of Waste Management  
Solid Waste Section  
Date **September 18, 2013** By **LY Frost**

Prepared for:

**Halifax County Department of Public Utilities**  
**Halifax, North Carolina**

**December 2012**

NC LIC. NO. C-0828 (ENGINEERING)

**SMITH+GARDNER**

14 N. Boylan Avenue, Raleigh NC 27603 | 919.828.0577



PRINTED ON 100% RECYCLED PAPER

© 2012 Smith Gardner, Inc.

*This document may not be copied without the express written authorization of Smith Gardner, Inc.*

This page intentionally left blank.

# Halifax County C&D Landfill - Area 2

## Technical Specifications

### Table of Contents

<u>Section</u>	<u>Specification</u>
02110	Site Preparation
02222	Excavation
02223	Embankment
02250	Soil Liner
02258	Vegetative Soil Layer
02270	Erosion and Sedimentation Control
02275	Rolled Erosion Control Products
02608	Precast Concrete Structures
02720	Stormwater Systems
02930	Revegetation

This page intentionally left blank.

## SECTION 02110

### SITE PREPARATION

Site Preparation: Site Preparation includes clearing, grubbing, and stripping operations which precede the proposed construction.

#### A. Description

1. General:

- a. The Contractor shall furnish all labor, material, and equipment to complete Site Preparation in accordance with the Contract Drawings and these Specifications.
- b. Principal items of work include:
  1. Notifying all authorities owning utility lines running to or on the property. Protect and maintain all utility lines to remain and cap those that are not required in accordance with instructions of the Utility Companies, and all other authorities having jurisdiction.
  2. Clearing the site within the clearing limits, including removal of grass, brush, shrubs, trees, loose debris, and other encumbrances except for trees to remain.
  3. Boxing and protecting all areas to be preserved.
  4. Disposing from the site all debris resulting from work under this Section.

2. Related Work:

Related Contract Work is described in the following sections of the Specifications:

<u>Work</u>	<u>Section</u>
Excavation	02222
Embankment	02223

B. Materials Not Used.

C. Submittals Not Used.

## **D. Construction**

### **1. Clearing of the Site:**

- a. Clearing limits, as shown on the Contract Drawings, shall be established by the Contractor's Surveyor. Once established, the clearing limits shall be inspected and approved by the Engineer prior to clearing the affected areas.
- b. Before the start of excavation and grading operations, the areas within the clearing limits shown on the Contract Drawings shall be cleared and grubbed.
- c. Clearing shall consist of cutting, removal, and satisfactory disposal of all trees, fallen timber, brush, bushes, rubbish, fencing, and other perishable and objectionable material.

Should it become necessary to remove a tree, bush, brush, or other plants outside the clearing limits, the Contractor shall do so only after permission has been granted by the Engineer.

- d. Excavation resulting from the removal of trees, roots, and the like shall be filled with suitable material, as approved by the Engineer, and thoroughly compacted per the requirements contained in Section 02223, Embankment, of these Specifications.
- e. In temporary construction easement locations, only those trees and shrubs shall be removed which are in actual interference with excavation or grading work under this Contract, and removal shall be subject to approval by the Engineer. However, the Engineer reserves the right to order additional trees and shrubs removed at no additional cost to the Owner, if such, in his opinion, they are too close to the work to be maintained or have become damaged due to the Contractor's operations.

### **2. Grubbing:**

- a. Grubbing shall consist of the removal and disposal of all stumps, roots, logs, sticks, and other perishable materials to a depth of at least 6 inches below ground surfaces.
- b. Large stumps located in areas to be excavated may be removed during grading operations, subject to the approval of the Engineer.

### **3. Disposal of Cleared and Grubbed Material:**

No open burning of clearing debris will be allowed on this project. All trees, stumps, roots, bushes, etc. shall be removed from the site and disposed of by the Contractor.

END OF SECTION

# SECTION 02222

## EXCAVATION

Excavation: Excavation includes excavating, sealing, hauling, scraping, undercutting, removal of accumulated surface water or ground water, stockpiling, and all necessary and incidental items as required for bringing the landfill and related structures to the specified lines and grades.

### A. Description

1. General:

The Contractor shall furnish all labor, material, and equipment required to complete Excavation of the project area in accordance with the Contract Drawings and these Specifications, except as noted below:

- a. Clearing and grubbing and removal of topsoil is addressed in Section 02110, Site Preparation, of these Specifications.

2. Related Work:

Related Contract Work is described in the following sections of the Specifications:

<u>Work</u>	<u>Section</u>
Site Preparation	02110
Embankment	02223
Erosion and Sedimentation Control	02270
CQA Manual	Attached

3. Quality Assurance:

Quality Assurance during Excavation will be provided by the Owner as described in the accompanying Project CQA Manual.

4. Definitions:

- a. Excavation: shall consist of the removal and satisfactory disposal and/or stockpiling of all materials (borrow and/or unsuitable materials included) located within the limits of construction including widening cuts and shaping of slopes necessary for the preparation of roadbeds, slope areas, cutting of any ditches, channels, waterways, entrances, and other work incidental thereto.
- b. Borrow: shall consist of approved on-site material required for the construction of embankments/fills or for other portions of the work.
- c. Select Borrow (Where Applicable): shall consist of approved off-site material required for the construction of embankments/fills, roadway subgrade, backfilling, or for other portions of the work as shown on Contract Drawings or in

these Specifications. The Contractor shall make his own arrangements for obtaining select borrow and pay all costs involved.

- d. Unsuitable Material: is any in-place or excavated material which contains undesirable materials or is in a state which is not appropriate, in the opinion of the CQA Engineer, for the intended use or support of planned structures, embankment, or excavation. This may include but not be limited to organic material, waste/refuse, soft, or wet material not meeting required specifications, etc.
- e. Unsuitable Material Overexcavation: shall consist of the removal and satisfactory disposal of all unsuitable material located within the limits of construction and below subgrade elevations shown or indicated on the Contract Drawings. Where excavation to the subgrade elevations results in a subgrade or slopes of unsuitable material, the Contractor shall overexcavate such material to below the grades shown or indicated on the Contract Drawings or as otherwise directed by the Engineer and CQA Engineer.

## **B. Materials**

Excavation shall include the removal of all soil, weathered rock, boulders, conduits, pipe, unsuitable material, and all other obstacles encountered and shown or indicated on the Contract Drawings and/or specified herein.

## **C. Submittals                      Not Used.**

## **D. Construction**

- 1. The Contractor shall conduct Excavation activities in such a manner that erosion of disturbed areas and off site sedimentation is absolutely minimized as outlined in Section 02270, Erosion and Sedimentation Control, of these Specifications.
- 2. The Contractor shall excavate to the lines and grades shown on the Contract Drawings and stockpile all suitable excavated materials. As the excavation is made, the materials will be examined and identified to the CQA Engineer.

The Contractor will perform all surveys necessary to establish and verify lines and grades for all Excavation, including pipe excavations, soil overexcavation, and anchor trenches.

### **3. Stockpiling:**

The Contractor shall stockpile the materials in appropriate stockpiles as approved by the CQA Engineer.

Stockpiles shall be properly sloped and the surfaces sealed by the Contractor at the end of each working day, or during the day in the event of heavy rain, to the satisfaction of the Engineer.

4. The Contractor shall protect all existing facilities and structures including, but not limited to, existing utilities, monitoring wells, signs, grade stakes, etc. during the grading and stockpiling operations.
5. All excavations shall be made in the dry and in such a manner and to such widths as will give ample room for properly constructing and inspecting the structures and/or piping they are to contain and for such sheeting, timbering, pumping, and drainage as may be required.
6. The Contractor shall be responsible for the control of surface and subsurface water when necessary. Except for certain erosion and sedimentation control measures and other areas designated to impound water, all areas shall be graded to drain.
7. Excavation slopes shall be flat enough to avoid sloughs and slides that will cause disturbance of the subgrade or damage of adjacent areas. Slides and overbreaks which occur due to negligence, carelessness, or improper construction techniques on the part of the Contractor shall be removed and disposed of by the Contractor as directed by the Engineer at no additional cost to the Owner.
8. The intersection of slopes with natural ground surfaces, including the beginning and ending of cut slopes, shall be uniformly rounded. All protruding roots and other vegetation shall be removed from slopes.
9. The bottom of all excavations for structures and pipes shall be examined by the CQA Engineer for bearing value and the presence of unsuitable material. If, in the opinion of the CQA Engineer, additional Excavation is required due to the low bearing value of the subgrade material, or if the in-place materials are soft, yielding, pumping and wet, the Contractor shall remove such material to the required width and depth and replace it with thoroughly compacted structural fill, or material directed by the CQA Engineer. No payment will be made for subgrade disturbance caused by inadequate Dewatering or improper construction methods.
10. Any areas excavated below design subgrade elevations by the Contractor, unless directed by the CQA Engineer, shall be brought back to design elevations at no cost to the Owner. The Contractor shall place and compact such material in accordance with Section 02223, Embankment, of these Specifications.
11. The Contractor shall dispose of excess or unsuitable excavation materials on-site at location(s) approved by the Owner.
12. The Contractor shall properly level-off bottoms of all excavations. Proof-rolling shall be conducted with appropriate equipment.
13. Upon reaching subgrade elevations shown in excavation areas, the Contractor shall scarify subgrade soils to a minimum depth of 6" and obtain the CQA Engineer's approval of quality. If unsuitable materials are encountered at the subgrade elevation, perform additional excavations as approved by the CQA Engineer to remove unsuitable materials.

14. Overexcavation and Backfill:

- a. Where subgrade materials are determined to be unsuitable, such materials shall be removed by the Contractor to the lengths, widths, and depths approved by the Engineer and CQA Engineer in advance and backfilled with compacted Embankment in accordance with Section 02223, Embankment, of these Specifications.
- b. No additional payment will be made for such overexcavation and backfill 1 foot or less than the finished subgrade as this is considered superficial.
- c. Where overexcavation of unsuitable material is greater than 1 foot beneath the finished subgrade, payment shall be made on a unit price basis for overexcavation and backfill and the measured quantity shall include the entire excavation quantity below the finished subgrade elevations. The unit price for overexcavation and backfill shall include disposal of unsuitable materials.

15. All cuts shall be brought to the grade and cross section shown or indicated on the Contract Drawings, or established by the Engineer, prior to final inspection.

16. The Contractor shall protect finished lines and grades of completed excavation against excessive erosion, damage from trafficking, or other causes and shall repair any damage at no additional cost to the Owner.

17. Trench Excavation:

- a. All pipe Excavation and trenching shall be done in strict accordance with these Specifications, all applicable parts of the OSHA Regulations, 29 CFR 1926, Subpart P, and other applicable regulations. In the event of any conflicts in this information, safe working conditions as established by the appropriate OSHA guidelines shall govern.
- b. The minimum trench widths shall be as indicated on the Contract Drawings. Enlargements of the trench shall be made as needed to give ample space for operations at pipe joints. The width of the trench shall be limited to the maximum dimensions shown on the Contract Drawings, except where a wider trench is needed for the installation of and work within sheeting and bracing.
- c. Except where otherwise specified, excavation slopes shall be flat enough to avoid slides which will cause disturbance of the subgrade, damage to adjacent areas, or endanger the lives or safety of persons in the vicinity.
- d. Hand excavation shall be employed wherever, in the opinion of the Engineer, it is necessary for the protection of existing utilities, poles, trees, pavements, obstructions, or structures.
- e. No greater length of trench in any location shall be left open, in advance of pipe laying, than shall be authorized or directed by the Engineer and, in general, such length shall be limited to approximately one hundred (100) feet.

- f. Pipe Bedding: All pipe bedding shall be as shown on the Contract Drawings, unless otherwise specified herein.
18. Sheeting and Bracing:
- a. The Contractor shall furnish, place, and maintain such sheeting and bracing which may be required to support sides of Excavation or to protect pipes and structures from possible damage and to provide safe working conditions in accordance with current OSHA requirements. If the Engineer is of the opinion that at any point sufficient or proper supports have not been provided, he may order additional supports put in at the sole expense of the Contractor. The Contractor shall be responsible for the adequacy of all sheeting and bracing used and for all damage resulting from sheeting and bracing failure or from placing, maintaining, and removing it.
  - b. The Contractor shall exercise caution in the installation and removal of sheeting to insure that excessive or unusual loadings are not transmitted to any new or existing structure. The Contractor shall promptly repair at his expense any and all damage that can be reasonably attributed to sheeting installation or removal.
  - c. All sheeting and bracing shall be removed upon completion of the work.
19. If grading operations are suspended for any reason whatsoever, partially completed cut and fill slopes shall be brought to the required slope and the work of seeding and mulching or other required erosion and sedimentation control operations shall be performed at the Contractor's sole expense.

END OF SECTION

This page intentionally left blank.

# SECTION 02223

## EMBANKMENT

Embankment: Embankment is the on-site compacted fill that provides the foundation and the berms for the containment area, the subgrade for some access roadways and structures, and backfill around structures and piping.

### A. Description

1. General:

The Contractor shall furnish all labor, material, and equipment to complete Embankment including borrowing, hauling, screening, discing, drying, compaction, control of surface and subsurface water, final grading, sealing, and all necessary and incidental items as detailed or required to complete the Embankment, all in accordance with the Contract Drawings and these Specifications.

2. Related Work:

Related Contract Work is described in the following sections of the Specifications:

<u>Work</u>	<u>Section</u>
Excavation	02222
Erosion and Sedimentation Control	02270
CQA Manual	Attached

3. Reference Standards:

The latest revision of the following standards of the American Society of Testing and Materials (ASTM) are hereby made a part of these Specifications.

ASTM D 698	Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/ft <sup>3</sup> ).
ASTM D 1556	Standard Test Method for Density and Unit Weight of Soil in Place by the Sand-Cone Method.
ASTM D 2167	Standard Test Method for Density and Unit Weight of Soil in Place by the Rubber Balloon Method.
ASTM D 2216	Standard Test Method for Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass.
ASTM D 2487	Standard Practice for Classification of Soils for Engineering Purposes (Unified Soil Classification System).

ASTM D 2488	Standard Practice for Description and Identification of Soils (Visual-Manual Procedure).
ASTM D 2937	Standard Test Method for Density of Soil in Place by the Drive Cylinder Method.
ASTM D 4643	Standard Test Method for Determination of Water (Moisture) Content of Soil by the Microwave Oven Method.
ASTM D 4959	Standard Test Method for Determination of Water (Moisture) Content of Soil by Direct Heating Method.
ASTM D 6938	Standard Test Methods for In-Place Density and Water Content of Soil and Soil-Aggregate in Place by Nuclear Methods (Shallow Depth).

4. Quality Assurance:

Quality Assurance during placement of Embankment will be provided by the Owner as described in the accompanying Project CQA Manual.

5. Definitions:

- a. Embankment: Shall include construction of all site earthwork including roadways, subgrade, perimeter berm embankments, including preparation of the areas upon which materials are to be placed. Embankment may also be referred to as structural and/or controlled fill. All Embankment materials may be either (off-site) Select Borrow or (on-site) Borrow unless otherwise noted on Contract Drawings or specified by the Engineer.
- b. Prepared Subgrade: The ground surface after clearing, grubbing, stripping, excavation, scarification, and/or compaction, and/or proof rolling to the satisfaction of the CQA Engineer.
- c. Well-Graded: A mixture of particle sizes that has no specific concentration or lack thereof of one or more sizes. Well-graded does not define any numerical value that must be placed on the coefficient of uniformity, coefficient of curvature, or other specific grain size distribution parameters. Well-graded is used to define a material type that, when compacted, produces a strong and relatively incompressible soil mass free from detrimental voids.
- d. Unclassified Fill: The nature of materials to be used is not identified or described herein but must be approved by the Engineer prior to use.

**B. Materials**

- 1. Embankment materials shall consist of clean well-graded natural soil classified as SP, SW, SM, SC, ML, or CL (ASTM D 2487) containing no topsoil or other deleterious material. Other material classifications may be approved by the Engineer.

2. Stones or rock fragments shall not exceed one half the maximum lift thickness as compacted in any dimension. Isolated rocks shall be a maximum of 24-inches in any dimension.

**C. Submittals** Not Used.

**D. Construction**

1. The Contractor shall conduct Embankment activities in such a manner that erosion of disturbed areas and off-site sedimentation is absolutely minimized as outlined in Section 02270, Erosion and Sedimentation Control, of these Specifications.
2. All placement and compaction of Embankment shall be performed only when the CQA Engineer is informed by the Contractor of intent to perform such work.
3. Embankment shall be placed and compacted to the lines and grades shown on the Contract Drawings. Placement of Embankment outside the construction limits shall occur only as directed and approved by the Engineer.

The Contractor will perform all surveys necessary to establish and verify lines and grades for all Embankment.

4. The Contractor shall protect all existing facilities including, but not limited to, utilities and monitoring wells.
5. Subgrade Preparation:
  - a. The CQA Engineer shall inspect the exposed subgrade prior to placement of Embankment to assure that all rocks, topsoil, vegetation, roots, debris, or other deleterious materials have been removed.
  - b. Prior to placement of Embankment, the exposed subgrade shall be proofrolled using a static smooth-drum roller, loaded tandem axle dump truck, or other suitable equipment in the presence of the CQA Engineer. Any soft or unsuitable materials revealed before or during the in-place compaction shall be removed as directed by the CQA Engineer and replaced with suitable Embankment.
6. Surfaces on which Embankment is to be placed, shall be scarified or stepped in a manner which will permit bonding of the Embankment with the existing surface.
7. The Contractor shall be responsible for preparing the materials for the Embankment, including but not limited to, in-place drying or wetting of the soil necessary to achieve the compaction criteria of these Specifications.
8. The Contractor shall be responsible for the control of surface and subsurface water when necessary. Except for certain erosion and sedimentation control measures and other areas designated to impound water, all areas shall be graded to drain.

9. Embankment materials shall be placed in a manner permitting drainage and in continuous, approximately horizontal layers.
10. Compaction Requirements:
  - a. The Contractor shall compact Embankment in accordance with the requirements shown in Table 1 of this section. If Embankment does not meet the specified requirements, the Contractor shall rework the material, as may be necessary and continue compaction to achieve these requirements, or remove and replace the material to achieve the specified requirements, at Contractor's expense.
  - b. Each lift shall be compacted prior to placement of succeeding lifts. In confined areas, mechanical equipment, suitable for small areas and capable of achieving the density requirements, shall be required.
  - c. Lift compaction shall be performed with an appropriately heavy, properly ballasted, penetrating-foot or smooth-drum vibratory compactor depending on soil type. Compaction equipment shall be subject to approval by the CQA Engineer.
11. Embankment that becomes excessively eroded, soft, or otherwise unsuitable shall be removed or repaired by the Contractor as directed by the CQA Engineer, at no cost to the Owner.
12. The exposed surface of Embankment shall be rolled with a smooth-drum roller at the end of each work day to protect from adverse weather conditions.
13. Where Embankment is to be placed and compacted on slopes that are steeper than 3H:1V, the subgrade shall be benched to a minimum depth of 6 inches and the Embankment shall be placed in horizontal lifts.
14. Backfilling for Structures and Piping:
  - a. All structures, including manholes and pipes shall be backfilled with Embankment as shown in the Contract Drawings and as described in these Specifications.
  - b. Where sheeting is used, the Contractor shall take all reasonable measures to prevent loss of support beneath and adjacent to pipes and existing structures when sheeting is removed. If significant volumes of soil cannot be prevented from clinging to the extracted sheets, the voids shall be continuously backfilled as rapidly as possible. The Contractor shall thereafter limit the depth below subgrade that sheeting will be driven in similar soil conditions or employ other appropriate means to prevent loss of support.
  - c. When backfilling around structures, do not backfill until concrete has sufficiently cured (as determined by the CQA Engineer) and is properly supported. Place backfill in a manner to avoid displacement or damage of structures.

**Table 1: Required Embankment Properties**

Item	Required % Standard Proctor (ASTM D698) <sup>2</sup>	Required Moisture Content <sup>3</sup>	Maximum Lift Thickness (Compacted) (inches)
Embankment Beneath Structures and Roads <sup>1</sup>	100	+/- 2% of Optimum (std. Proctor)	8
Embankment	95	As Required for Compaction	8
Backfill Around Structures	95		8
Backfill in Pipe Trenches	95		6
Unclassified Fill	N/A	N/A	N/A

Notes:

1. Embankment beneath structures shall be considered to include a zone 10 feet out from the foundation of the structure extending down to the natural ground on a 45° slope. Embankment beneath roads shall be considered to include all embankment placed within 2 vertical feet of the final wearing surface and shall also include shoulders.
2. Determine field density using ASTM D 6938, ASTM D 1556, ASTM D 2167, or ASTM D 2937.
3. Determine field moisture content using ASTM D 6938, ASTM D 2216, ASTM D 4643, or ASTM D 4959.
4. The Engineer may allow exceptions to the above criteria for areas outside of the containment area which are not subject to significant long-term loads.

END OF SECTION

This page intentionally left blank.

# SECTION 02250

## SOIL LINER

Soil Liner: The Soil Liner(s) serves as a hydraulic containment barrier in the final cover system.

### A. Description

1. General:

- a. The Contractor shall furnish all labor, material, and equipment to complete installation of the Soil Liner including borrowing, hauling, screening, mixing, stockpiling, discing, compacting, drying or wetting, removal of surface water, removal of all previously placed material affected by adverse weather conditions or construction disturbance, final grading and sealing, and all necessary and incidental items as detailed or required to complete the Soil Liner, all in accordance with the Contract Drawings and these Specifications.
- b. The Contractor shall provide suitable soil from an on-site or off-site borrow site that meets all requirements outlined in these Specifications for Soil Liner.

Off-site borrow sources shall be approved in advance by the Engineer. The Contractor shall be responsible for all submittals required for Engineer approval of off-site borrow sources.

2. Related Work:

Related Contract Work is described in the following sections of the Specifications:

<u>Work</u>	<u>Section</u>
Excavation	02222
Embankment	02223
CQA Manual	Attached

3. Reference Standards:

The latest revision of the following standards of the American Society of Testing and Materials (ASTM) are hereby made a part of these Specifications.

ASTM D 422	Standard Test Method for Particle Size Analysis of Soils.
ASTM D 698	Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/ft <sup>3</sup> ).
ASTM D 1556	Standard Test Method for Density and Unit Weight of Soil in Place by the Sand-Cone Method.

ASTM D 2167	Standard Test Method for Density and Unit Weight of Soil in Place by the Rubber Balloon Method.
ASTM D 2216	Standard Test Method for Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass.
ASTM D 2488	Standard Practice for Description and Identification of Soils (Visual-Manual Procedure).
ASTM D 2937	Standard Test Method for Density of Soil in Place by the Drive Cylinder Method.
ASTM D 4318	Standard Test Method for Liquid Limit, Plastic Limit, and Plasticity Index of Soils.
ASTM D 4643	Standard Test Method for Determination of Water (Moisture) Content of Soil by the Microwave Oven Method.
ASTM D 4959	Standard Test Method for Determination of Water (Moisture) Content of Soil by Direct Heating Method.
ASTM D 5084	Standard Test Method for Measurement of Hydraulic Conductivity of Saturated Porous Materials Using a Flexible Wall Permeameter.
ASTM D 6938	Standard Test Methods for In-Place Density and Water Content of Soil and Soil-Aggregate in Place by Nuclear Methods (Shallow Depth).

4. Quality Assurance:

Quality Assurance during placement of Soil Liner will be provided by the Owner as described in the accompanying Project CQA Manual.

**B. Materials**

All material for Soil Liner shall conform to the requirements shown in Table 1 of this section.

**C. Submittals**

The Contractor shall submit the following to the CQA Engineer:

1. Before approval is given to proceed with test fill construction, the Contractor shall submit descriptive information on compaction equipment to be used for construction of the Soil Liner.
2. Off-Site Borrow Sources (If Applicable):
  - a. For each off-site borrow source for Soil Liner soils, the Contractor shall provide the following information at least four weeks prior to placement of the Soil Liner:

- (1) The name, location, and owner of proposed borrow site, including a topographic map and location map of the site.
- (2) A certification submitted by an independent Registered Professional Engineer that the proposed borrow site contains a minimum of double the in-place volume of Soil Liner required to complete the work.
- (3) A certification submitted by an independent Registered Professional Engineer that the proposed borrow soils meet the requirements for Soil Liner outlined in these Specifications. Certification shall include the following minimum testing and test frequency:

Test (Test Method)	Quantity (Min.)
Atterberg Limits (ASTM D 4318)	10
Grain Size (with Hydrometer) (ASTM D 422)	10
Standard Proctor (ASTM D 698)	5
Natural Moisture Content (ASTM D 2216)	10
Hydraulic Conductivity (Lab Remolded) (ASTM D 5084)	5

Testing samples for certification shall be obtained from well distributed locations within the proposed borrow area. All test data shall be submitted with the soil certification.

- b. The Contractor shall be responsible for maintaining quality of the Soil Liner borrow source throughout construction and shall ensure that the borrow soil meets the project criteria outlined in these Specifications. The Contractor shall cooperate with the CQA Engineer so that the CQA Engineer has unlimited access to the borrow area during construction for the purposes of sampling and testing borrow soil.
- c. If the borrow source does not meet the requirements outlined in these Specifications, the Contractor shall be responsible for providing an alternative borrow source at no cost to the Owner.

### 3. Survey Results

Survey results for Soil Liner subgrade shall be submitted for review prior to placement of Soil Liner. After completion of a segment of Soil Liner, survey results shall be submitted for review prior to placement of overlying layers.

## **D. Construction**

### 1. General:

- a. All placement and compaction of Soil Liner shall be performed only when the CQA Engineer is informed by the Contractor of intent to perform such work.

- b. The Contractor shall place and compact the Soil Liner to the lines and grades shown on the Contract Drawings with the exception that a 0.15 foot overbuild at the Contractor's expense is allowed. Thickness requirements are minimum values. The Contractor will perform all surveys necessary to establish and verify lines and grades for all Soil Liner.

2. Borrow Soils:

- a. The Contractor may haul borrow soil to an on-site stockpile area. Unless otherwise allowed by the Engineer, borrow soil cannot be hauled directly to the containment area for placement and compaction unless each load is monitored and approved by the CQA Engineer prior to loading at the borrow site.
- b. Any borrow soil not meeting the requirements for Soil Liner shall be rejected and removed from the project site by the Contractor at no cost to the Owner.

3. Test Fill Construction:

The Contractor shall construct a test fill prior to construction of Soil Liner. The test fill shall be at least 20 feet wide by 50 feet long and shall be compacted in lifts to the full design thickness. The Contractor shall use materials and equipment for test fill construction that the Contractor intends to use during construction.

No Soil Liner construction may be performed until the test fill construction is confirmed to be adequate in accordance with the Project CQA Manual.

The Contractor shall amend construction techniques or equipment in order to meet all criteria outlined for Soil Liner in these Specifications at no cost to the Owner.

4. Subgrade Preparation:

- a. The CQA Engineer shall inspect the exposed subgrade prior to placement of Soil Liner to assure that all rocks, topsoil, vegetation, roots, debris, or other deleterious materials have been removed.
- b. Prior to placement of Soil Liner, the exposed subgrade shall be proofrolled using a static smooth-drum roller, loaded tandem axle dump truck, or other suitable equipment in the presence of the CQA Engineer. Any soft or unsuitable subgrade materials revealed before or during the in-place compaction shall be removed as directed by the CQA Engineer and replaced with suitable materials.

5. Placement and Compaction:

- a. All Soil Liner shall be placed in loose lifts no greater than the height of the feet on compaction equipment to be used. The loose Soil Liner shall be free from clods or rocks which exceed the sizes in Table 1. Where excessive sized clods do occur, the Contractor shall break up the clods using methods approved by the CQA Engineer.

- b. Lift compaction shall be performed with an appropriately heavy, properly ballasted, penetrating-foot compactor. Compaction equipment shall be the same as used in the test fill, unless otherwise approved by the Engineer.

Each lift shall be compacted prior to placement of succeeding lifts. The maximum lift thickness shall be as shown in Table 2. In confined areas, mechanical equipment, suitable for small areas and capable of achieving the density requirements, shall be required.

- c. The exposed surface of Soil Liner shall be protected from adverse weather conditions or desiccation of the soil. This is commonly done by rolling the surface of the Soil Liner with a smooth-drum roller at the end of each work day. Alternative means of protecting the Soil Liner may be employed by the Contractor.
- d. The in-place Soil Liner shall conform to the requirements shown in Table 2 of this section. If Soil Liner does not meet the specified requirements, the Contractor shall rework the material, as may be necessary and continue compaction to achieve these requirements, or remove and replace the material to achieve the specified requirements, at Contractor's expense.
- e. Any Soil Liner surface which is smooth, has a moisture content outside of the specified moisture content range, as defined by ASTM D 698, or exhibits evidence of desiccation cracking 1/2 inch deep or greater, shall be scarified to a depth of 1 to 3 inches and brought to a proper moisture content prior to placement of a subsequent lift. This includes any Soil Liner surface that was previously seal rolled for protection.
- f. No Soil Liner shall be placed or compacted when soil temperatures are so low as to produce ice lenses in the Soil Liner borrow soil.
- g. Soil Liner placed on side slopes shall be placed and compacted in lifts which are parallel to the slope. Lift criteria shall be as described herein.
- h. Surfaces not properly maintained shall be repaired by the Contractor at no cost to the Owner. A suitable surface for geosynthetics construction shall be a surface maintained at the specified compaction and moisture content criteria provided in these Specifications.
- i. Locations of control stakes, in-place density tests, or other samples in the Soil Liner shall be patched with compacted Soil Liner or sodium bentonite compacted and hydrated in the holes.

7. Surveying:

- a. Before placement of a segment of Soil Liner, the Soil Liner subgrade shall be surveyed on 100 foot centers and at slope breaks (including all tops and toes of slope, points of grade change, etc.) to ensure the top of the Soil Liner subgrade slopes at grades specified on the Contract Drawings.

- b. After completion of a segment of Soil Liner, but before installation of subsequent layers, the Soil Liner shall be surveyed on 100 foot centers and at slope breaks to ensure:
- (1) The specified thickness has been achieved.
  - (2) The top of the Soil Liner slopes at grades specified on the Contract Drawings; and
  - (3) Soil Liner placed more than 0.15 feet beyond the limits of the lines and grades as shown on the Contract Drawings will not be accepted and must be removed at the Contractor's expense if required by the Engineer.

This work shall be performed at the Contractor's cost by a registered surveyor.

**Table 1: Soil Liner Material Requirements**

Property	Test Method	Value
Visual Classification	ASTM D 2488	Clean natural fine-grained soil free from organics, debris, or other detrimental material. Soil type as required to achieve the hydraulic conductivity criteria.
Clod Size	-----	Maximum = ¾ inch (or less if required to achieve hydraulic conductivity criteria)
Gradation	ASTM D 422	Max. = 1½ inches
Atterberg Limits	ASTM D 4318	As required based on soil type.
Hydraulic Conductivity (Lab Remolded) (Compacted Soil Barrier)	ASTM D 5084 <sup>3</sup>	≤ 1 x 10 <sup>-5</sup> cm/s at a density of ≥ 95% maximum standard dry density and a moisture content ≥ optimum moisture content <sup>4</sup>

**Table 2: In-Place Soil Liner Requirements**

Property	Test Method	Value
Density	ASTM D 6938 <sup>1</sup>	≥ 95% maximum standard dry density <sup>4</sup>
Moisture Content	ASTM D 6938 <sup>2</sup>	≥ optimum moisture content <sup>4</sup>
Maximum Lift Thickness (Compacted): (Compacted Soil Barrier)	-----	9 inches
Hydraulic Conductivity (Shelby Tube): (Compacted Soil Barrier)	ASTM D 5084 <sup>3</sup>	≤ 1 x 10 <sup>-5</sup> cm/s
Completed Thickness: (Compacted Soil Barrier)	Survey	18 inches minimum

Notes:

1. Optionally use ASTM D 1556, ASTM D 2167, or ASTM D 2937.
2. Optionally use ASTM D 2216, ASTM D 4643, or ASTM D 4959.
3. Maximum effective confining pressure and maximum hydraulic gradient as follows.  
Backpressure as recommended by ASTM D 5084. Modifications of the maximum hydraulic gradient may be allowed by the Engineer depending on actual hydraulic conductivity values.

Material	Maximum Effective Confining Pressure (psi)	Maximum Hydraulic Gradient
Compacted Soil Barrier (k ≤ 1 x 10 <sup>-5</sup> cm/s)	5	15

4. Or as otherwise determined by remolded samples to achieve hydraulic conductivity criteria.

END OF SECTION

## SECTION 02258

### VEGETATIVE SOIL LAYER

Vegetative Soil Layer (VSL): The Vegetative Soil Layer (VSL) is placed in the final cover system in order to support permanent vegetative cover. This section includes the topsoil to be placed as the upper 6 inches of the VSL.

#### A. Description

1. General:

The Contractor shall furnish all labor, material, and equipment to complete installation of the VSL (including topsoil) for the landfill cover, including borrowing, hauling, spreading, and final grading and all necessary and incidental items as detailed or required to complete the VSL, all in accordance with the Contract Drawings and these Specifications.

2. Related Work:

Related Contract Work is described in the following sections of the Specifications:

<u>Work</u>	<u>Section</u>
Soil Liner	02250
Revegetation	02930
CQA Manual	Attached

3. Reference Standards:

The latest revision of the following standards of the American Society of Testing and Materials (ASTM) are hereby made a part of these Specifications.

ASTM D 2487	Standard Practice for Classification of Soils for Engineering Purposes (Unified Soil Classification System).
-------------	--

4. Quality Assurance:

Quality Assurance during placement of Vegetative Soil Layer will be provided by the Owner as described in the accompanying Project CQA Manual.

#### B. Materials

Soil that meets all of the following requirements shall be classified as select soil fill for use in construction of the VSL.

1. Soil shall be classified according to the Unified Soil Classification System (USCS) as SM, SC, ML, ML-CL, or CL (ASTM D 2487). Alternatives to these requirements must be approved in advance by the Engineer.

2. Select soil fill materials shall be reasonably free of gypsum, ferrous, and/or calcareous concretions and nodules, refuse, roots, or other deleterious substances.
3. Continuous and repeated visual inspection of the materials being used will be performed by the Contractor to ensure proper soils are being used. In addition, the CQA Engineer shall make frequent inspections of the placement operations and materials, and will consult with the Engineer.
4. The VSL shall be uniform, smooth, and free of debris, rock, plant materials, and other foreign material larger than 3 inches in diameter. The material should contain no sharp edges. This material must be capable of supporting growth of vegetative cover.
5. Topsoil: The upper 6 inches of VSL shall be natural or blended soil material capable of supporting the growth of vegetative cover.

### **C. Submittals**

The Contractor shall submit the following to the CQA Engineer:

1. Before approval is given to proceed, the Contractor shall submit descriptive information on placement equipment to be used in construction of the VSL.
2. Survey Results:

After completion of a segment of VSL, survey results shall be submitted for review prior to VSL acceptance.

### **D. Construction**

1. All placement and compaction of VSL shall be performed only when the CQA Engineer is informed by the Contractor of intent to perform such work.
2. VSL shall be placed as specified below:
  - a. The VSL, including topsoil, shall be placed and spread using tracked equipment. The CQA Engineer shall approve the equipment used to place the VSL.
  - b. VSL shall be placed and compacted to the lines and grades shown on the Contract Drawings with the exception that a 0.15 foot overbuild at Contractor's expense is allowed. The Contractor will perform all surveys necessary to establish and verify lines and grades for all VSL.
  - c. VSL shall be compacted by tracking the final lift with tracked equipment.
3. After the specified thickness has been achieved and verified, the Contractor shall proceed immediately with seeding.
4. Surveying:

After completion of a segment of VSL, the VSL shall be surveyed on 100 foot centers and

at slope breaks (including all tops and toes of slope, points of grade change, etc.) to ensure:

- a. The specified thickness has been achieved. A hand auger or similar method may be used to check for thickness at each location.
- b. The top of the VSL slopes at grades specified on the Contract Drawings; and
- c. VSL placed more than 0.15 feet beyond the limits of the lines and grades as shown on the Contract Drawings will not be accepted and must be removed at the Contractor's sole expense if required by the Engineer.

This work shall be performed at the Contractor's cost by a registered surveyor.

END OF SECTION

This page intentionally left blank.

## SECTION 02270

### EROSION AND SEDIMENTATION CONTROL

Erosion and Sedimentation Control: Erosion and Sedimentation Control is a system of construction and engineered measures (devices, structures, practices, etc.) which act to minimize surface water induced erosion of disturbed areas and the resulting off-site sedimentation.

#### A. Description

1. General:

The Contractor shall furnish all labor, material, and equipment to complete installation of and maintain Erosion and Sedimentation Control measures and related work in accordance with the Contract Drawings and these Specifications.

All Erosion and Sedimentation Control work shall be in accordance with the latest edition of the North Carolina Erosion and Sediment Control Planning and Design Manual as well as applicable regulations.

2. Related Work:

Related Contract Work is described in the following sections of the Specifications:

<u>Work</u>	<u>Section</u>
Rolled Erosion Control Products	02275
Precast Concrete Structures	02608
Stormwater Systems	02720
Revegetation	02930

3. Reference Standards:

The latest revision of the following standards of the American Society of Testing and Materials (ASTM) are hereby made a part of these specifications.

ASTM D 3786	Test Method for Hydraulic Bursting Strength of Knitted Goods and Nonwoven Fabrics: Diaphragm Bursting Strength Tester Method.
ASTM D 4355	Standard Test Method for Deterioration of Geotextiles from Exposure to Ultraviolet Light and Water (Xenon-Arc Type Apparatus).
ASTM D 4491	Standard Test Methods for Water Permeability of Geotextiles by Permittivity.

ASTM D 4533	Standard Test Method for Trapezoid Tearing Strength of Geotextiles.
ASTM D 4632	Standard Test Method for Grab Breaking Load and Elongation of Geotextiles.
ASTM D 4751	Standard Test Method for Determining Apparent Opening Size of a Geotextile.
ASTM D 4833	Standard Test Method for Index Puncture Resistance of Geotextiles, Geomembranes, and Related Products.

## **B. Materials**

### 1. Permanent Sediment or Detention Basins:

Permanent sediment or detention basins shall be constructed as shown on the Contract Drawings.

### 2. Permanent Drainage Channels, Diversions, Swales, and Ditches:

Permanent drainage channels, diversions, swales, and ditches shall be constructed as shown on the Contract Drawings.

### 3. Silt Fence:

Silt fences shall be constructed as shown on the Contract Drawings and as needed, based on the Contractor's discretion and Engineer's approval. The silt fence is a permeable barrier erected within and downgradient of small disturbed areas to capture sediment from sheet flow. It is made of filter fabric buried at the bottom, stretched, and supported by posts and wire mesh backing. Silt fence shall conform to the following properties:

- a. Posts: Posts shall be 1.33 lb/linear foot steel (preferred) or wood with a minimum length of 5 feet. Steel posts shall be "U" or "T"-type. Wood posts shall have a minimum diameter of 4-inches.
- b. Filter Fabric: Filter fabric shall be a woven geotextile made specifically for sediment control. Filter fabric shall conform to the properties listed in Table 1 of this section.

### 4. Geotextiles:

Geotextiles placed where shown on the Contract Drawings shall be 6 oz/SY non-woven polypropylene or other product as approved by the Engineer.

### 5. Temporary Sediment Traps:

Temporary sediment traps shall be constructed as shown on the Contract Drawings.

6. Filter Berms:

Filter berms shall be constructed as shown on the Contract Drawings.

7. Stone Check Dams:

Stone check dams shall be constructed as shown on the Contract Drawings.

8. Stone Filters:

Stone filters shall be constructed as shown on the Contract Drawings.

9. Down Chutes and Pipes:

Down chutes and pipes shall be constructed as shown on the Contract Drawings.

10. Rip Rap:

Rip Rap shall conform to the requirements of the NCDOT and meet the requirements shown on the Contract Drawings.

11. Rolled Erosion Control Products (RECPs):

Rolled Erosion Control Products (RECPs) shall conform to the requirements of Section 02275, Rolled Erosion Control Products, of these Specifications.

12. Other Work:

In addition to the Erosion and Sedimentation Control measures shown on the Contract Drawings, the Contractor shall provide adequate means to prevent any sediment from entering any storm drains, drop inlets, ditches, streams, or bodies of water downstream of any area disturbed by construction. Excavation materials shall be placed upstream of any trench or other excavation to prevent sedimentation of off-site areas. In areas where a natural buffer area exists between the work area and the closest stream or water course, this area shall not be disturbed. All paved areas shall be scraped and swept as necessary to prevent the accumulation of dirt and debris. Work associated with this provision shall be considered incidental to the project and no separate payment will be made.

13. Temporary and Permanent Ground Cover:

The Contractor shall provide temporary or permanent ground cover (or other acceptable measure(s)) adequate to restrain erosion on erodible slopes or other areas within 21 calendar days following completion of any phase of grading. The Contractor shall provide permanent ground cover for all disturbed areas within 15 working days or 90 calendar days (whichever is shorter) following the completion of construction.

## C. Submittals

The Contractor shall submit the following to the Engineer:

1. Submit a certification and summary of all required test results, prior to installation, that all Erosion and Sedimentation Control materials manufactured for the project have been produced in accordance with these Specifications.
2. Furnish copies of the delivery tickets or other approved receipts as evidence for materials received that will be incorporated into construction.

## D. Construction

1. Establishment of Erosion and Sedimentation Control Measures:
  - a. All Erosion and Sedimentation Control measures will be constructed according to the Contract Drawings and these Specifications.
  - b. Due to the nature of the work required by this Contract, it is anticipated that the location and nature of the Erosion and Sedimentation Control measures may need to be adjusted on several occasions to reflect the current phase of construction.
  - c. Erosion and Sedimentation Control measures shall be established prior to the work in a given area. Where such practice is not feasible, the Erosion and Sedimentation Control measure(s) shall be established immediately following completion of the clearing operation.
  - d. The construction schedule adopted by the Contractor will impact the placement and need for specific measures required for the control of erosion. The Contractor shall develop and implement such additional techniques as may be required to minimize erosion and prevent or correct the discharge of sediment outside the limits of construction (unless controlled by other on-site measure(s)).
  - e. The location and extent of Erosion and Sedimentation Control measures shall be revised at each phase of construction that results in a change in either the quantity or direction of surface runoff from construction areas. All deviations from the control provisions shown on the Contract Drawings shall have the prior approval of the Engineer.
2. Inspection and Maintenance of Erosion and Sedimentation Control Measures:
  - a. The Contractor shall furnish the labor, material, and equipment required for the inspection and maintenance of all Erosion and Sedimentation Control measures. Maintenance shall be scheduled as required for a particular measure to maintain the removal efficiency and intent of the measure.
  - b. All Erosion and Sedimentation Control measures shall be inspected at least once every seven calendar days and within 24 hours after any storm event of greater than 0.5 inches of rain per 24 hour period and appropriate maintenance

conducted. A rain gauge shall be maintained on the site and a record of the rainfall amounts and dates shall be kept properly.

- c. Maintenance shall include, but not be limited to:
  - (1) The removal and satisfactory disposal of trapped or deposited sediments from basins, traps, barriers, filters, and/or drainage features/devices;
  - (2) Replacement of filter fabrics used for silt fences upon loss of efficiency; and
  - (3) Replacement of any other components which are damaged or cannot serve the intended use.
- d. The Contractor shall accept and maintain any existing sediments that are included in existing sediment traps or basins that accept or will accept stormwater flow and or sediment accumulation from all areas within the Contractor's limits of construction.
- e. Sediments removed from Erosion and Sedimentation Control measures shall be disposed of in locations that will not result in off-site sedimentation as approved by the Engineer.
- f. All Erosion and Sedimentation Control measures shall be maintained to the satisfaction of the Engineer until the site has been stabilized.

3. Graded Slopes and Fills:

The angle for graded slopes and fills shall be no greater than the angle that can be retained by vegetated cover or other adequate measures.

4. Finish Grading:

All disturbed areas shall be uniformly graded to the lines, grades, and elevations shown on the Contract Drawings. Except for certain erosion and sedimentation control measures and other areas designated to impound water, all areas shall be graded to drain. Finished surfaces shall be reasonably smooth, compacted, and free from irregular surface changes. Unless otherwise specified, the degree of finish shall be that ordinarily obtainable from either blade or scraper operations. Areas shall be finished to a smoothness suitable for application of topsoil.

5. Revegetation:

Revegetation shall conform to the requirements of Section 02930, Revegetation, of these Specifications.

6. Cleanup:

- a. The Contractor shall remove from the site all subsoil excavated from his work and all other debris including, but not limited to, branches, paper, and rubbish in all landscape areas, and remove temporary barricades as the work proceeds.
- b. All areas shall be kept in a neat, orderly condition at all times. Prior to final acceptance, the Contractor shall clean up the entire landscaped area to the satisfaction of the Engineer.

**Table 1: Required Silt Fence Filter Fabric Properties**

Property	Test Method	Units	Value <sup>1</sup>
Grab Tensile Strength <sup>2</sup>	ASTM D 4632	lbs	90 x 90
Grab Elongation	ASTM D 4632	%	20 (Max.)
Ultraviolet Resistance (500 hrs)	ASTM D 4355	%	80
Apparent Opening Size (AOS)	ASTM D 4751	U.S. Sieve	30+
Permittivity	ASTM D 4491	sec <sup>-1</sup>	0.05

Notes:

- 1. Minimum Average Roll Value (MARV).
- 2. Values for machine and cross machine direction (MD x XD), respectively.

END OF SECTION

## SECTION 02275

### ROLLED EROSION CONTROL PRODUCTS

Rolled Erosion Control Products: Rolled Erosion Control Products (RECPs) include erosion control blankets (ECB) and turf reinforcement mats (TRM) placed in channels and on slopes.

#### A. Description

1. General:

The Contractor shall furnish all labor, material, and equipment to complete installation of all RECPs in accordance with the Contract Drawings and these Specifications.

2. Related Work:

Related Contract Work is described in the following sections of the Specifications:

<u>Work</u>	<u>Section</u>
Erosion and Sedimentation Control	02270
Revegetation	02930

3. Reference Standards:

The latest revision of the following standards of the American Society of Testing and Materials (ASTM) are hereby made a part of these specifications.

ASTM D 4355	Standard Test Method for Deterioration of Geotextiles from Exposure to Ultraviolet Light and Water (Xenon-Arc Type Apparatus).
ASTM D 6475	Standard Test Method for Measuring Mass per Unit Area of Erosion Control Blankets.
ASTM D 6524	Standard Test Method for Measuring the Resiliency of Turf Reinforcement Mats.
ASTM D 6525	Standard Test Method for Measuring Nominal Thickness of Permanent Erosion Control Products.
ASTM D 6566	Standard Test Method for Measuring Mass per Unit Area of Turf Reinforcement Mats.
ASTM D 6818	Standard Test Method for Ultimate Tensile Properties of Turf Reinforcement Mats.

## **B. Materials**

### 1. General:

The materials supplied under these Specifications shall consist of new, first-quality products designed and manufactured specifically for the purpose of this work, which shall have been satisfactorily demonstrated, by prior use, to be suitable and durable for such purposes.

Labels on each RECP shall identify the length, width, product name, and name of Manufacturer.

### 2. Erosion Control Blanket (ECB):

ECB shall consist of a machine-produced mat of straw or wood excelsior fiber covered on the top side with a photodegradable extruded plastic or woven biodegradable netting and sewn together with degradable thread. ECB shall also conform to the properties listed in Table 1 of this section. ECB shall be S75, as manufactured by North American Green, CURLEX I, as manufactured by American Excelsior Company, LANDLOK S1, as manufactured by Propex Fabrics, or approved equal.

Flexterra Flexible Growth Media (FGM), as manufactured by Profile Products, applied at a minimum rate of 3,500 lbs/acre is an acceptable substitute for ECB to be placed on 2H:1V slopes (a minimum rate of 3,000 lbs/acre shall be used on 3H:1V slopes).

### 3. Turf Reinforcement Mat (TRM):

TRM shall consist of a dense web of crimped and interlocking polypropylene fibers positioned between two biaxially oriented nets and mechanically bound together by parallel stitching with polypropylene thread. TRM shall be designed to accelerate seedling emergence, exhibit high resiliency, and possess strength and elongation properties to limit stretching in a saturated condition. TRM shall be stabilized against chemical and UV degradation which are normally found in a natural soil environment and shall have no biodegradable components. TRM shall also conform to the properties listed in Table 1 of this section. TRM shall be LANDLOK TRM 435, as manufactured by Propex Fabrics, or approved equal.

### 4. Anchors: Anchors for RECPs shall consist of machine made staples of No. 8 gauge new steel wire formed into a "U" shape. The size when formed shall be not less than 8 inches in length with a throat of not less than 1 inch in width. Longer anchors may be required for loose soils. Other anchors, such as metal pins or plastic pegs, may also be used if approved in advance by the Engineer.

## **C. Submittals**

The Contractor shall submit the following to the Engineer:

### 1. Mill Certificate and Sample: Prior to shipping to the site, the Contractor shall submit a mill certificate or affidavit signed by a legally authorized official of the Manufacturer for each RECP attesting that each RECP meets the physical and manufacturing requirements

stated in these Specifications. The Contractor shall also submit a sample of each RECP to be used. The sample shall be labeled with the product name and be accompanied by the Manufacturer's specifications.

2. Installation Guidelines/Instructions: The Manufacturer's guidelines/instructions for installation shall be submitted for review.
3. Furnish copies of delivery tickets or other approved receipts as evidence for materials received that will be incorporated into the construction.

## **D. Construction**

### 1. Shipping, Handling, and Storage:

All RECPs shall be shipped, handled, and stored in strict accordance with the Manufacturer's recommendations.

### 2. Installation - General:

- a. Placing of RECPs shall be done immediately following seeding. Seeding shall be performed in accordance with Section 02930, Revegetation, of these Specifications.
- b. RECPs shall be placed to the lines and grades shown on the Contract Drawings. The earth surface shall be smooth and free from stones, clods, or debris which will prevent the contact of the RECP with the soil. Care shall be taken to preserve the required line, grade, and cross section of the area.
- c. RECPs shall be unrolled in the direction of the flow of water and shall be applied without stretching so that it will lie smoothly but loosely on the soil surface.
- d. At the time of installation, RECPs shall be rejected, if they have defects, rips, holes, flaws, evidence of deterioration, or other damage.
- e. The Engineer may require adjustments in the installation requirements to fit individual conditions.

### 3. Installation - Channels:

RECPs installed in channels shall be unrolled parallel to the direction of water flow. The first roll shall be centered longitudinally in the channel and anchored with staples. Subsequent rolls shall be installed outward to the edges of the channel and be lapped to allow installation of a common row of anchors. RECP ends shall be overlapped with the upstream ends on top ("shingled"). Refer to the Contract Drawings and/or the Manufacturer's installation guidelines/instructions for installation details.

### 4. Installation - Slopes:

RECPs installed on slopes shall be oriented in vertical strips and anchored. Subsequent rolls shall be installed outward to the edge(s) of the original roll and be lapped to allow

installation of a common row of anchors. RECP ends shall be shingled. Refer to the Contract Drawings and/or the Manufacturer's installation guidelines/instructions for installation details.

5. Maintenance:

Maintenance of RECPs shall be in accordance with Section 02270, Erosion and Sedimentation Control, of these Specifications.

**Table 1: Required Rolled Erosion Control Product Properties**

Property	Test Method	Units	Value <sup>1</sup>
<b>Erosion Control Blanket (ECB)</b>			
Mass per Unit Area	ASTM D 6475	lbs/yd <sup>2</sup>	0.5 ± 10% (Straw) 0.7 ± 10% (Excelsior)
Tensile Strength <sup>2</sup>	ASTM D 6818	lbs/ft	50 x 65
Tensile Elongation	ASTM D 6818	%	20
Maximum Permissible Shear Stress (Un-Vegetated)	-----	lb/ft <sup>2</sup>	1.55
Functional Longevity	-----	months	12
<b>Turf Reinforcement Mat (TRM)</b>			
Mass per Unit Area	ASTM D 6566	oz/yd <sup>2</sup>	8
Thickness	ASTM D 6525	inches	0.35
Tensile Strength <sup>2</sup>	ASTM D 6818	lbs/ft	225 x 175
Tensile Elongation	ASTM D 6818	%	50 (max.)
Resiliency	ASTM D 6524	%	80
UV Resistance (1,000 Hours)	ASTM D 4355	%	80
Maximum Permissible Shear Stress (Long-Term Vegetated)	Large Scale	lb/ft <sup>2</sup>	5

Notes:

1. Typical for ECB; Minimum Average Roll Value (MARV) for TRM and HPTRM.
2. Values for machine and cross machine direction (MD x XD), respectively.

END OF SECTION

## SECTION 02608

### PRECAST CONCRETE STRUCTURES

Precast Concrete Structures: Precast Concrete Structures are used in the stormwater handling system.

#### A. Description

1. General:

The Contractor shall furnish all labor, material, and equipment to complete installation of Precast Concrete Structures in accordance with the Contract Drawings and these Specifications.

2. Related Work:

Related Contract Work is described in the following sections of the Specifications:

<u>Work</u>	<u>Section</u>
Excavation	02222
Embankment	02223
Erosion and Sedimentation Control	02270
Stormwater Systems	02720

3. Reference Standards:

The latest revision of the following standards of the American Society of Testing and Materials (ASTM) are hereby made a part of these Specifications.

ASTM A 615	Standard Specification for Deformed and Plain Billet-Steel Bars for Concrete Reinforcement.
ASTM C 443	Standard Specification for Joints for Circular Concrete Sewer and Culvert Pipe, Using Rubber Gaskets.
ASTM C 478	Standard Specification for Precast Reinforced Concrete Manhole Sections.
ASTM C 497	Standard Test Methods for Concrete Pipe, Manhole Sections, or Tile.
ASTM C 990	Standard Specification for Joints for Concrete Pipe, Manholes, and Precast Box Sections Using Preformed Flexible Joint Sealants.

**B. Materials**

1. Precast Concrete Boxes: All precast concrete boxes shall be constructed from non-shrink, 4,000 psi compressive strength concrete in conformance with ASTM C 1433 and as detailed on the Contract Drawings.
3. Joints: All joints shall be sealed with preformed plastic gaskets in conformance with ASTM C 990 or rubber gaskets in conformance with ASTM C 443.
4. Steps: All steps shall be constructed of 0.5 inch reinforcing rod completely encased in corrosion-resistant rubber or plastic. The upper surfaces of each step shall have a traction tread of self cleaning rubber cleats and guide lugs on both sides to prevent slippage.
5. Frames and Covers: Frames and covers shall consist of cast iron frames and covers (Vulcan Foundry, or equal) equipped with steel handles and shall be of the opening size as indicated on the Contract Drawings. Markings on the covers shall indicate the intended use of the structure and shall be acceptable to the Owner.
6. Markings: All Precast Concrete Structures shall include markings clearly identifying the date of manufacture, the name of the manufacturer, and any other pertinent information.

**C. Submittals**

The Contractor shall submit the following to the Engineer:

1. The Contractor shall submit shop drawings for Precast Concrete Structures for approval at least 4 weeks prior to construction. Shop drawings shall show complete design, installation, and construction information in such detail as to enable the Engineer to determine the adequacy of the proposed units for the intended purpose. Details of steel reinforcement size and placement shall be included. The shop drawings shall include a schedule which will list the size and type of precast structure at each location where the precast structures are to be used.
2. Submit a certification and summary of all required test results, prior to installation, that all Precast Concrete Structures have been produced in accordance with these Specifications.

**D. Construction**

1. The Precast Concrete Structures shall be installed at the locations and to the elevations indicated on the Contract Drawings. The Contractor shall give the Engineer sufficient notice so he may observe the field location and installation activities.
2. The Precast Concrete Structures will be bedded and backfilled as indicated on the Contract Drawings.

3. Precast Concrete Structures which are damaged or become damaged will be rejected or shall be repaired in a manner approved by the Engineer at the Contractor's sole expense.

END OF SECTION

This page intentionally left blank.

## SECTION 02720

### STORMWATER SYSTEMS

Stormwater Systems: Stormwater Systems shall include all piping, pipe fittings, flared end sections, and other appurtenances designated to convey stormwater.

#### A. Description

1. General:

The contractor shall furnish all labor, material, and equipment to complete installation of Stormwater Systems in accordance with the Contract Drawings and these Specifications.

2. Related Work:

Related Contract Work is described in the following sections of the Specifications:

<u>Work</u>	<u>Section</u>
Excavation	02222
Embankment	02223
Erosion and Sedimentation Control	02270
Precast Concrete Structures	02608

3. Reference Standards:

The latest revision of the following standards of the American Society of Testing and Materials (ASTM), the American Association of State Highway and Transportation Officials (AASHTO), and the North Carolina Department of Transportation (NCDOT) are hereby made a part of these specifications.

ASTM C 76	Standard Specification for Reinforced Concrete Culvert, Storm Drain, and Sewer Pipe.
ASTM C 150	Standard Specification for Portland Cement.
ASTM D 1248	Standard Specification for Polyethylene Plastics Molding and Extrusion Materials For Wire and Cable.
ASTM D 2321	Standard Practice for Underground Installation of Thermoplastic Pipe for Sewers and Other Gravity-Flow Applications.
ASTM D 3350	Standard Specification for Polyethylene Plastics Pipe and Fittings Materials.
AASHTO M 36	Specification for Corrugated Steel Pipe.

AASHTO M 252	Specification for Corrugated Polyethylene Drainage Tubing, 3 to 10 Inch Diameter.
AASHTO M 294	Specification for Corrugated Polyethylene Pipe, 12 to 36 Inch Diameter.
NCDOT	Standard Specifications for Roads and Structures and Roadway Standard Drawings.

## **B. Materials**

### 1. Reinforced Concrete Pipe (RCP):

- a. All reinforced concrete pipe shall be manufactured in accordance with ASTM C 76, Wall Type B or C, and shall be of the class that equals or exceeds the pipe class as shown on the Contract Drawings. All pipe shall be aged at the manufacturing plant for at least fourteen (14) days before delivery to the job site.
- b. Minimum pipe laying lengths shall be four (4) feet.
- c. Joints for reinforced concrete pipe shall have tongue and groove or bell and spigot ends with leak-resistant mastic joint sealant. Joint sealant shall be ConSeal type, or approved equal.

### 2. Corrugated Metal Pipe (CMP):

- a. Corrugated metal pipe and fittings shall be of the sizes shown or specified and shall conform to every aspect of AASHTO M 36.
- b. Corrugated metal pipe shall be fabricated from galvanized steel sheets. Corrugation profile shall be 2 $\frac{2}{3}$  inch crest to crest and  $\frac{1}{2}$  inch crest to valley, and sheet thickness shall be 16 gage/.064 inch minimum.
- c. Pipe sections shall be helically corrugated with each pipe end rerolled to obtain no less than two (2) annular corrugations.
- d. Coupling Bands: CMP shall be firmly joined by coupling bands in accordance with the manufacturer's recommendations. These bands shall be not more than two nominal sheet thicknesses lighter than the thickness of the pipe to be connected and in no case lighter than 0.052 inches.
- e. All CMP utilized for permanent installation shall have gasketed joints.
- f. Asphaltic or bituminous coatings shall be applied in conformance with the manufacturer's requirements, as applicable.

3. Corrugated Polyethylene (CPE) Pipe:

CPE pipe and fittings shall be of the sizes and type shown on the Contract Drawings and shall conform to every aspect of AASHTO M 252 (3 to 10 inch diameters) or AASHTO M 294 (12 to 36 inch diameters). All Type S CPE pipe shall have watertight joints.

4. Flared End Sections:

Flared end sections shall be reinforced and shall be fabricated from the same materials meeting the same requirements as the pipe to which they are connected. All reinforced concrete and corrugated metal flared end sections shall meet the requirements of the NCDOT. Corrugated polyethylene flared end sections shall be as recommended by the pipe manufacturer.

5. Precast Concrete Structures:

Precast Concrete Structures shall be constructed as shown in the Contract Drawings and in accordance with Section 02608, Precast Concrete Structures, of these Specifications.

**C. Submittals**

The Contractor shall submit the following to the Engineer:

1. Submit a certification and summary of all required test results, prior to installation, that all Stormwater Systems have been produced in accordance with these Specifications.
2. Furnish copies of the delivery tickets or other approved receipts as evidence for materials received that will be incorporated into construction.

**D. Construction**

1. All piping shall be installed by skilled workmen and in accordance with the best standards for piping installation. Proper tools and appliances for the safe and convenient handling and installation of the pipe and fittings shall be used.
2. All pieces shall be carefully examined for defects, and no piece shall be installed which is known to be defective. If any defective piece should be discovered after having been installed, it shall be removed and replaced at the Contractor's expense.
3. Excavation and backfilling of pipe trenches shall be as described in Section 02222, Excavation and Section 02223, Embankment, respectively, of these Specifications.
4. Following proper preparation of the trench subgrade, pipe and fittings shall be carefully lowered into the trench so as to prevent dirt and other foreign substances from gaining entrance into the pipe and fittings. Proper facilities shall be provided for lowering sections of pipe into trenches. No materials shall be dropped or dumped into the trench.
5. Water shall be kept out of the trench until jointing and backfilling are completed. When work is not in progress, open ends of pipe, fittings, and valves shall be securely closed so

that no water, earth, or other substance will enter the pipes, fittings, or valves. Pipe ends left for future connections shall be valved, plugged, or capped, and anchored as required.

6. All piping shall be erected to accurate lines and grades with no abrupt changes in line or grade.
7. The full length of each section of pipe shall rest solidly upon the bed of the trench, with recesses excavated to accommodate bells, couplings, joints, and fittings. Before joints are made, each pipe shall be well bedded on a solid foundation. No pipe shall be brought into position until the preceding length has been thoroughly bedded and secured in place. Pipe that has the grade or joint disturbed after laying shall be taken up and relaid by the Contractor at his own expense.
8. The laying of reinforced concrete pipe shall conform to the current recommendations of the American Concrete Pipe Association for Installation Type 1 or 2.

END OF SECTION

# SECTION 02930

## REVEGETATION

Revegetation: Revegetation includes permanent Revegetation of all site areas disturbed by the Contractor whether inside the Contract Limits or not.

### A. Description

1. General:

The Contractor shall furnish all labor, material, and equipment to complete Revegetation in accordance with the Contract Drawings and these Specifications.

2. Related Work:

Related Contract Work is described in the following sections of the Specifications:

<u>Work</u>	<u>Section</u>
Embankment	02223
Vegetative Soil Layer	02258
Erosion and Sedimentation Control	02270
Rolled Erosion Control Products	02275

3. Warranty:

The Contractor shall be responsible for the satisfactory establishment and growth of a permanent stand of vegetation for a period of one year following the final seeding as judged by the Engineer. During this period, the Contractor shall be responsible for the maintenance items described in Paragraph D.4 (Maintenance) of this Specification.

### B. Materials

1. Limestone: Unless otherwise defined by specific soil tests, supply agricultural grade ground limestone conforming to the current "Rules, Regulations, and Standards of the Fertilizer Board of Control."

2. Fertilizer: Unless otherwise defined by specific soil tests, supply commercial fertilizer of 10-10-10 analysis, meeting applicable requirements of State and Federal law. Do not use cyanamic compounds of hydrated lime. Deliver fertilizer in original containers labeled with content analysis.

3. Grass Seed: Supply fresh, clean, new-crop seed as specified in Table 1 of this section. Do not use seed which is wet, moldy, or otherwise damaged. Deliver seed in standard sealed containers labeled with producer's name and seed analysis, and in accord with US Department of Agriculture Rules and Regulations under Federal Seed Act.

4. Mulch: Supply clean, seed-free, threshed straw of oats, wheat, barley, rye, beans, or other locally available mulch material.
  - a. Do not use mulch containing a quantity of matured, noxious weed seeds or other species that will be detrimental to seeding, or provide a menace to surrounding land.
  - b. Do not use mulch material which is fresh or excessively brittle, or which is decomposed and will smother or retard growth of grass.
5. Binder: Supply emulsified asphalt or synthetic binder.
6. Water: Supply potable, free of substances harmful to growth.

### **C. Submittals**

The Contractor shall submit the following to the Engineer:

1. Results of soil tests performed and proposed modifications, if any, to the specified requirements.
2. Certificates for each grass seed mixture, stating botanical and common name, percentage by weight, and percentages of purity, germination, and weed seed. Certify that each container of seed delivered is fully labeled in accordance with Federal Seed Act and equals or exceeds specification requirements.
3. Copies of invoices for fertilizer, showing grade furnished and total quantity applied.

### **D. Construction**

1. The Contractor shall establish a smooth, healthy, uniform, close stand of grass from the specified seed. Prior to Revegetation, the Contractor shall adequately test the soils to be revegetated to ensure the adequacy of the specified requirements. Any modifications to these requirements deemed necessary after the review of soil test results, shall be at the Contractor's sole expense. The Engineer will perform the observations to determine when successful Revegetation is achieved.
2. Soil Preparation:
  - a. Limit preparation to areas which will be planted soon after preparation.
  - b. Loosen surface to minimum depth of four (4) inches.
  - c. Remove stones, sticks, roots, rubbish and other extraneous matter over three (3) inches in any dimension.
  - d. Spread lime uniformly over designated areas at the rate specified in Table 1 of this section.

- e. After application of lime, prior to applying fertilizer, loosen areas to be seeded with double disc or other suitable device if soil has become hard or compacted. Correct any surface irregularities in order to prevent pocket or low areas which will allow water to stand.
- f. Distribute fertilizer uniformly over areas to be seeded at the rate specified in Table 1 of this section.
  - (1) Use suitable distributor.
  - (2) Incorporate fertilizer into soil to depth of a least two (2) inches.
  - (3) Remove stones or other substances which will interfere with turf development or subsequent mowing.
- g. Grade seeded areas to smooth, even surface with loose, uniformly fine texture.
  - (1) Roll and rake, remove ridges and fill depressions, as required to meet finish grades.
  - (2) Fine grade just prior to planting.

3. Seeding:

- a. Use approved mechanical power driven drills or seeders, mechanical hand seeders, or other approved equipment.
- b. Distribute seed evenly over entire area at the rate specified in Table 1 of this section.
- c. Stop work when work extends beyond most favorable planting season for species designated, or when satisfactory results cannot be obtained because of drought, high winds, excessive moisture, or other factors.
- d. Resume work only when favorable condition develops, or as directed by the Engineer.
- e. Lightly rake seed into soil followed by light rolling or cultipacking.
- f. Immediately protect seeded areas against erosion by mulching or placing Rolled Erosion Control Products in accordance with Section 02275 of these Specifications, where applicable.
  - (1) Spread mulch in a continuous blanket at the rate specified in Table 1 of this section.
  - (2) Immediately following spreading mulch, secure with evenly distributed binder at the rate specified in Table 1 of this section.

